

भारत कोकिंग कोल लिमिटेड

(कोल इंडिया का एक उपक्रम)
पंजीकृत कार्यालय : कोयला भवन, कोयला नगर,
धनबाद-826005
सी.आइ.एन. : U10101JH1972GOI000918

परियोजना पदाधिकारी का कार्यालय
मुर्लीडीह 20/21 पिट्स कोलियरी

पोस्ट / थाना: महुदा, जिला: धनबाद (झारखण्ड)-828305
फोन नं. 0326 2273354; फेक्स: 0326 2273445 ई-मेल: cgmwj@bccl.gov.in



Bharat Coking Coal Limited

(A Subsidiary of Coal India Limited)
Regd. Off. : Koyla Bhawan, Koyla Nagar
Dhanbad - 826005
CIN : U10101JH1972GOI000918

OFFICE OF THE PROJECT OFFICER
Murulidih 20/21 Pits Colliery

PO & PS: Mahuda, DISTT: Dhanbad (Jharkhand)-828305

PHONE NO: 0326 2273354, FAX NO: 0326 2273445, e-mail : cgmwj@bccl.gov.in

Ref: - WTA/MND/ENV/2020/1189(A)

Date: - 28/05/2020

To,
The Director,
Ministry of Environment & Forest and Climate Change
Regional Office (ECZ), Bungalow No. A-2,
Shyamali Colony, Ranchi - 834002

Sub: - Submission of six monthly reports on implementation of Environment measures for the period From October '19 to March '20 in respect Cluster-XIII group of mines of BCCL.

Ref: EC Order No - J- 11015/11/2010-IA.II (M) Dated: - 06.06.2013

Dear Sir,

Please find enclosed herewith the six monthly reports on implementation of Environment protection measures for the period from Oct '18 to March '20 in respect of Cluster XIII group of mines of BCCL. We hope you will find in order.

Thanking you,

Encl: - As Above

Yours faithfully

Handwritten signature and date: 28-05-20

Project Officer
Mahuda Group of Mines

CC to:-

1. The Director, 1A Monitoring Cell, Paryavaran Bhawan, CGO Complex, New Delhi - 110003
2. The Member Secretary, Jharkhand State Pollution Control Board, TA- Division Building, Dhurwa - Ranchi - 834004
3. HoD (Env.), BCCL, Koyla Bhawan Dhanbad
4. GM, W.J. Area
5. Nodal Officer (Env.), WJ Area

"Copy for uploading online on MoEF&CC "parivesh portal" and send by e-mail"

**ENVIRONMENTAL CLEARANCE COMPLIANCE OF
CLUSTER-XIII (GRANTED VIDE LETTER NO.J-
11015/11/2010-IA.II (M) DATED 06.06.2013**

(OCTOBER'19 – MARCH'20)

Sl. No.	A. Specific Conditions by MOEF:	Compliance
i.	No mining shall be undertaken in/under the forestland until prior forestry clearance has been obtained under the provisions of FC Act 1980.	Stage-II forest clearance of 6.41 ha of forest land of proposed Murulidih O/C mine has been issued by MOEF vide letter no.5-JHC188/2010-BHU/3913 dated 24.04.2020.
ii.	The EC is granted to Murulidih 20/21 Pits U/G of 0.18 MTPA and a peak production of 2.34 MTPA in an ML area of 571.32 ha.	Coal production from cluster XIII group of mines is Nil. Production from Murulidih 20/21 Pits U/G is suspended from December 2015.
iii.	The maximum production in the cluster shall not exceed beyond that for which environmental clearance has been granted for the cluster XIII as per given below:	Being Complied. (Presently there is not any producing mine under cluster XIII) Annexure I
iv.	The measure identified in the environmental plan for cluster – XIII group of mine and the condition given in this environmental clearance letter shall be dovetailed to the implementation of Jharia Action Plan.	Being Complied.
v.	As there is no fire in cluster XIII but the measure should be adopted proponent to control spread of neighboring fire to this cluster XIII. The proponent shall prepare time series maps of Jharia Coal field through NRSA to monitor & prevent fire problems in this Jharia Coalfield by Isothermal mapping / imaging and monitoring temperatures of the coal seam (whether they are closed spontaneous ignition temperatures) and based on which, areas with potential fire problems shall be identified. Measures to prevent ingress of air (ventilation) in such areas, to prevent restart fresh/spread fire in other areas including in mines of cluster – XIV shall be undertaken.	It has been complied. NRSC was engaged for preparation of time series maps to monitor and prevent fire problems of Jharia Coalfield by Isothermal mapping/imaging and monitoring temperature of the coal seams and NRSC has submitted their final report in January 2018 in which the area of fire has been reduced 9.00 KM ² to 3.28 KM ² . NRSC report is enclosed as Annexure II.
Vi.	Underground mining should be taken up after completion of reclamation of O/C mine area after two years.	Agreed. Presently there is no running O/C mine in cluster XIII.
vii.	No mining shall be undertaken where underground fires continue. Measure shall be taken to prevent/check such fire including in	Complied.

	old OB dump.	
Viii	There shall be no external OB dumps. OB from one patch OCP mine shall be backfilled. At the end of the mining there shall be no void and the entire mined out area shall be re-vegetated. Areas where opencast mining was carried out and completed shall be reclaimed immediately thereafter.	Being complied.
ix.	A detailed calendar plan of production with plan for OB dumping and back filling (for open cast mines) and reclamation and final mine closure plan for each mine of cluster XIII shall be drawn up & implemented.	Being implemented. Mine closure plan is approved. There is no producing mine in cluster XIII.
x.	The void in 5 ha. Area shall be converted in to a water reservoir of maximum depth of 15-20 mtr in post mining stage and shall be gently sloped and upper benches of the reservoir shall be stabilized with plantation and periphery of the reservoir fenced. The abandoned pits and voids should be backfilled with OB & biologically reclaimed with plantation and or may used for pisciculture.	Complied and will be complied as per statute.
xi.	Mining shall be carried out as per statutette from the streams/nalas flowing within the lease and maintaining a safe distance from the Nalas flowing along the lease boundary. A safety barrier of a minimum 60m width shall be maintained along the nalas/water bodies. The small water bodies in OC shall be protected to the extend feasible and the embankment proposed along water body shall be strengthened with stone pitching.	Being Complied. There is no producing mine in cluster XIII.
xii.	Active OB dumps near water body and rivers should be rehandled for back filling abandoned mine voids. However, those which have been biologically reclaimed need not be disturbed.	There is no opencast project running in cluster XIII at present.
xiii.	Thick green belt shall be developed along undisturbed areas, mine boundary and in mine reclamation. During post mining stage, a total of 91.75 ha would be reclaimed and afforested by planting native species in consultation with local DFO/Agriculture deptt. /Institutions with the relevant discipline. The density of the trees should be around 2500 plants per ha.	It is being complied. Four Eco-restoration Sites of total area 8.4 Ha. (Site-A= 4.2 Ha. Site-B =1.5 Ha, Site-C =1.8 Ha and Site-D= 0.9 Ha) reclaimed area are developed and maintained at Murulidih (More than 2500 plants per ha).

xiv	The roads should be provided with avenue plantation on both sides as trees act as sink of carbon and other pollutant.	Agreed. Being complied.
xv.	Specific mitigative measures identified for the Jharia Coalfields in the Environmental Action Plan prepared for Dhanbad as a critically polluted are and relevant for Cluster XIII shall be implemented.	Being Implemented.
xvi.	The locations of monitoring stations in the Jharia Coalfields should be finalized in consultation with the Jharkhand State Pollution Control Board. The Committee stated that smoke/dust emission vary from source to source (fuel wood, coal, fly ash from TPPs, silica from natural dust, etc.) and a Source Apportionment Study should be got carried out for the entire Jharia Coalfields. Mineralogical composition study should be undertaken on the composition of the suspended particulate matter (PM10 and PM2.5) in Jharia Coalfields and also quantified. These studies would help ascertain source and extent of the air pollution, based on which appropriate mitigative measures could be taken.	Location of monitoring stations was already finalized with the consultation of Jharkhand State Pollution Control Board. Source Apportionment Study: - Work Order had already been issued to NEERI Nagpur on 12.05.2018. And work has been started in September 2018. Field data collection for Summer season has been done, winter data collection is in process. The progress report sent by NEERI is attached.
xvii.	No ground water shall be used for mining activities. Additional water required, if any, shall be met from mine water or by recycling/ reused of the water from the existing activities and from rain water harvesting measures. The project authority shall meet water requirement of nearby village (s) in case the village wells go dry to dewatering of mine.	Agreed. Being implemented.
xviii.	Regular monitoring of groundwater level and quality of the study area shall be carried out by establishing a network of existing wells and construction of new piezometers. The monitoring for quantity shall be done four times a year in pre-monsoon (May), monsoon (August), post-monsoon (November) and winter (January) seasons and for quality including Arsenic and Fluoride during the month of May. Data thus collected shall be submitted to the Ministry of Environment & Forest and to the Central Pollution Control Board/SPCB quarterly within one month of monitoring. Rainwater harvesting measures shall be undertaken in case monitoring of water table indicates a declining trend.	Complied. CMPDI RI-II has prepared a report for Location and design of Piezometers. Groundwater monitoring data has been enclosed as Annexure II

xix.	Mine discharge water shall be treated to meet standards prescribed standards before discharge into natural water courses/agriculture. The quality of the water discharged shall be monitored at the outlet points and proper records maintained thereof and uploaded regularly on the company website.	Agreed. Being implemented. CMPDIL, Dhanbad is monitoring the same. Annexure- IV
xx.	ETP shall also be provided for workshop, and CHP, if any. Effluents shall be treated to confirm to prescribe standards in case discharge into the natural water course.	Presently there is no producing mine in Cluster-XIII. There is no effluent discharge into natural water course. However there is arrangement for treatment of effluent discharge to prescribed standards. There is neither Open Cast mine running nor CHP nor such workshop from where effluent discharge is found.
xxi.	Regular monitoring of subsidence movement on the surface over and around the working area and impact natural drainage pattern, water bodies, vegetation, structure, roads and surroundings shall be continued till movement ceases completely. In case observation of any high rate of subsidence movement, appropriate effective corrective measure shall be taken to avoid loss of life and material. Cracks shall be effectively plugged with ballast and clayey soil /suitable material.	Being implemented. Subsidence study is being conducted by ISM Dhanbad before the start of panel. Extraction done in Non-Effective Width Method so that there is no subsidence on the surface.
xxii.	Sufficient coal pillars shall be left un extracted around the air shaft (within subsidence influence area) to protect from any damage from subsidence, if any.	Complied.
xxiii.	High root density tree species shall be selected and planted over areas likely to be affected by subsidence.	Plantation in BCCL is being done on 3-tier basis, in which both, Monocotyledonae (Monocots) such as grasses, bamboo etc and Dicotyledonae (Dicots) such as sheesham, mango etc are being planted for developing an extensive root system. The Monocots having fibrous root system helps in developing the root density at the topsoil level while, Dicots having the tap root system have a distributed root density in topsoil, subsoil and regolith layer of soil. These two root system together forms the high root density system.
Xxiv.	Depression due to subsidence resulting in water accumulating within low lying areas shall be filled up or drained out by cutting drains.	Complied.
Xxv.	Solid barriers shall be left below the roads falling within the blocks to avoid any damage to the road.	Already complied as per statute.

xxvi.	No depillaring operation shall be carried out below the township/colony.	Complied. Depillaring operation are being carried out after getting written permission from DGMS which is statutory binding.
xxvii.	The transportation plan for conveyor – cum – rail for cluster XIII should be dovetailed with Jharia Action Plan. Road transportation of coal during phase I should be by mechanically covered trucks, which should be introduced at the earliest. The plan for conveyor – cum – rail for cluster XIV should be dovetailed with Jharia Action Plan. The road transportation of coal during phase I should be by mechanically covered trucks.	Will be Complied. Presently there is no coal production from mines under cluster-XIII.
xxviii.	A study should be initiated to analyze extent of reduction in pollution load every year by reducing road transport.	Pollution load study report for has been submitted by CMPDI. Presently there is no producing mine under cluster-XIII.
.xxix.	R & R of 2187 nos. of PAF's involved. They should be rehabilitated at cost of Rs. 11199.89 lakhs as per the approved Jharia Action Plan.	PAF's /PAP's involved is being rehabilitated as per cost specified as per Jharia Action Plan.

Xxx.	Details of transportation, CSR, R&R and implementation of environmental action plan for each of the 17 clusters should be brought out in a booklet for and submitted to Ministry.	Being Complied. Will be submitted.
.Xxxi.	A detailed CSR action plan shall be prepared for cluster XIII group of mines. Specific activities shall be identified for CSR of Rs. 20.25 / annum @of Rs.5/ton of coal production as recurring expenditure. The area within the cluster XIII ML that would be existing waste land and not being acquired shall be put to productive use under CSR and developed with fruit bearing and other useful species for the local communities . Third party evaluation shall be got carried out regularly for the proper implementation of activities under taken in the project area under CSR. Issue raised in the public hearing	Agreed. Being implemented.

	<p>should also be integrated with activities being taken up under CSR. The details of CSR undertaken along with budgetary provisions for the village wise various activities and the expenditure thereon shall be uploaded on the company website every year. The company must give priority to capacity building both within the company and to the local youth, who are motivated to carry out the work in future.</p>	
xxxii.	<p>For monitoring land use pattern and for post mining land use, a time series of land use maps, based on satellite imagery (on a scale of 1: 5000) of the core zone and buffer zone, from the start of the project until end of mine life shall be prepared once in 3 years (for any one particular season which is consistent in the time series), and the report submitted to MoEF and its Regional office at Bhubaneswar.</p>	<p>Time series map of vegetation cover in the Jharia Coal field has been carried out through CMPDI in the year 2014 and 2017 (which is enclosed as Annexure- V)</p>
xxxiii.	<p>A Final Mine Closure Plan along with details of Corpus Fund shall be submitted to the Ministry of Environment & Forests five year before mine closure for approval. Habitat Restoration Plan of the mine area shall be carried out using a mix of native species found in the original ecosystem, which were conserved in-situ and ex-situ in an identified area within the lease for reintroduction in the mine during mine reclamation and at the post mining stage for habitat restoration.</p>	<p>Agreed .Eco-restoration sites (4 no. of total area 8.4 ha) using native species are maintained. Mine closer plan is approved and implemented for Murulidih 20/21 Pits Colliery.</p>
xxxiv.	<p>A separate environmental management cell with suitable qualified personnel shall be set up under the control of a Senior Executive, who will report directly to the head of Company for implementing environment policy and socio – economic issues and the capacity building required in this regard.</p>	<p>A full-fledged Environment Department, headed by a HOD (Environment) along with a suitable qualified multidisciplinary team of executives which includes Environment, Mining & Excavation, has been established in Headquarters. They are also trained in ecological restoration, sustainable development, rainwater Harvesting methods etc. At the project level, one Executive in each area has also been nominated as Project Nodal Officer (Environment) and is also entrusted with the responsibility of compliance and observance of the environmental Acts/ Laws including environment protection measures .The activities are monitored on regular basis at Area and at Headquarters levels. GM (Environment) at head quarter level, co-ordinates with all the Areas and reports to the Director (Technical) and in turn he reports to the CMD of the company. The team is multidisciplinary and very much motivated under the guidance of company's Director (Technical) and CMD. Further capacity building at both corporate and operating level is being done.</p>

xxxv.	Implementation of final mine closure plan for cluster XIII, subject to obtaining prior approval of the DGMS in regard to Mines Safety issues.	Will be implemented.
xxxvi.	Corporate Environment Responsibility:	Annexure- V
a)	The Company shall have a well laid down Environment Policy approved by the Board of Directors.	Agreed.
b)	The Environment Policy shall prescribe for standard operating process/procedures to bring into focus any infringements/deviation/violation of the environmental or forest norms/conditions.	Already complied.
c)	The hierarchical system or Administrative Order of the company to deal with environmental issues and for ensuring compliance with the environmental clearance conditions shall be furnished.	Already complied.
d)	To have proper checks and balances, the company shall have a well laid down system of Reporting of non-compliances/violations of environmental norms to the Board of Directors of the company and/or shareholders or stakeholders at large.	Being followed.
Sl. No	B. General Conditions Conditions by MOEF:	Compliance
i.	No change in mining technology and scope of working shall be made without prior approval of the Ministry of Environment and Forests.	Being complied.
ii.	No change in the calendar plan of production for quantum of mineral coal shall be made.	Being Followed.
iii.	Four ambient air quality monitoring stations shall be established in the core zone as well as in the buffer zone for PM10, PM 2.5, SO 2 and NOx monitoring. Location of the stations shall be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets in consultation with the State Pollution Control Board. Monitoring of heavy metals such as Hg, As, Ni, Cd, Cr, etc carried out at least once in six months.	The locations of monitoring stations in the Jharia Coalfields has finalized in consultation with the Jharkhand State Pollution Control Board. The work of monitoring of ambient environment is being done through Central Mine Planning and Design Institute (CMPDI) having laboratory recognized under the EP Rules. Records for the same are maintained. Annexure - IV

iv.	Data on ambient air quality (PM 10, PM 2.5, SO 2 and NO x) and heavy metals such as Hg, As, Ni, Cd, Cr and other monitoring data shall be regularly submitted to the Ministry including its Regional Office at Bhubaneswar and to the State Pollution Control Board and the Central Pollution Control Board once in six months. Random verification of samples through analysis from independent laboratories recognized under the EPA rules, 1986 shall be furnished as part of compliance report.	Being complied. Monitoring done by CMPDIL. Enclosed as Annexure- IV
v.	Adequate measures shall be taken for control of noise levels below 85 dBA in the work environment. Workers engaged in blasting and drilling operations, operation of HEMM, etc shall be provided with Ear plugs/muffs.	Being Complied.
vi.	Industrial wastewater (workshop and wastewater from the mine) shall be properly collected, treated so as to conform to the standards prescribed under GSR 422 (E) dated 19th May 1993 and 31st December 1993 or as amended from time to time before discharge. Oil and grease trap shall be installed before discharge of workshop effluents.	The work of monitoring of ambient environment done through Central Mine Planning and Design Institute RI-II (CMPDI), Dhanbad which is having laboratory recognized under the EP Rules. There is no effluent discharge from workshop presently no coal production from any mines of Cluster-XIII.
vii.	Vehicular emissions shall be kept under control and regularly monitored. Vehicles used for transporting the mineral shall be covered with tarpaulins and optimally loaded.	Already Complied.
viii.	Monitoring of environmental quality parameters shall be carried out through establishment of adequate number and type of pollution monitoring and analysis equipment in consultation with the State Pollution Control Board and data got analyzed through a laboratory recognized under EPA Rules, Monitoring of environmental quality parameters shall be carried out through establishment of adequate number and type of pollution monitoring and analysis equipment in consultation with the State Pollution Control Board and data got analyzed through a laboratory recognized under EPA Rules, 1986.	It is being complied. Monitoring is done by CMPDIL having laboratory recognized under EPA Rules, 1986.
ix.	Personnel working in dusty areas shall wear protective respiratory devices and they shall also be provided with adequate training and information on safety and health aspects.	Being Complied. Vocational training Centers under Separate Human Resource Development Deptt. is Conducting regular training programme on these issues.

x.	Occupational health surveillance program of the workers shall be undertaken periodically to observe any contractions due to exposure to dust and to take corrective measures, if needed and records maintained thereof. The quality of environment due to outsourcing and the health and safety issues of the outsourced manpower should be addressed by the company while outsourcing.	Initial Medical Examination (IME) and Periodical Medical Examination (PME) of all the personnel are carried out as per the Statutes and Director General of Mines Safety (DGMS) 's guideline.
xi.	A separate environmental management cell with suitable qualified personnel shall be set up under the control of a Senior Executive, who will report directly to the Head of the company.	A full-fledged Environment Department, headed by a HOD (Environment) along with a suitable qualified multidisciplinary team of executives which includes Environment, Mining, Excavation, have been established in Headquarters. They are also trained in ecological restoration, sustainable development, rainwater Harvesting methods etc. At the project level, one Executive in each area has also been nominated as Project Nodal Officer (Environment) and is also entrusted with the responsibility of compliance and observance of the environmental Acts/ Laws including environment protection measures .The activities are monitored on regular basis at Area and at Head quarters levels. GM (Environment) at head quarter level, co-ordinates with all the Areas and reports to the Director (Technical) and in turn he reports to the CMD of the company. The team is multidisciplinary and very much motivated under the guidance of company's Director (Technical) and CMD. Further capacity building at both corporate and operating level is being done.
xii.	The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year-wise expenditure shall be reported to this Ministry and its Regional Office at Bhubaneswar.	It is being initiated to comply the same. Agreed to report the same.

xiii.	The Project authorities shall advertise at least in two local newspapers widely circulated around the project, one of which shall be in the vernacular language of the locality concerned within seven days of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution control Board and may also be seen at the website of the ministry of Environment & Forests at http://envfor.nic.in.	It has been complied.
xiv.	A copy of the environmental clearance letter shall be marked to concern Panchayat/Zila Parishad, Municipal Corporation or Urban local body and local NGO, if any, from whom any suggestion/representation has been received while processing the proposal. A copy of the clearance letter shall also be displayed on company's website.	Complied.
xv.	A copy of the environmental clearance letter shall be shall also be displayed on the website of the concerned State Pollution Control Board. The EC letter shall also be displayed at the Regional Office, District Industry Sector and Collector's Office/Tehsildar's Office for 30 days.	Complied.
xvi.	The clearance letter shall be uploaded on the company's website. The compliance status of the stipulated environmental clearance conditions shall also be uploaded by the project authorities on their website and updated at least once every six months so as to bring the same in public domain. The monitoring data of environmental quality parameter (air, water, noise and soil) and critical pollutant such as PM10, PM2.5, SO 2 and NOx (ambient) and critical sectoral parameters shall also be displayed at the entrance of the project premises and mine office and in corporate office and on company's website.	Complied.

xvii.	The project proponent shall submit six monthly compliance reports on status of compliance of the stipulated environmental clearance conditions (both in hard copy and in e-mail) to the respective Regional Office of the Ministry, respective Zonal Office s of CPCB and the SPCB.	Being complied.
xviii.	The Regional Office of this Ministry located at Bhubaneswar shall monitor compliance of the stipulated conditions. The Project authorities shall extend full cooperation to the office(s) of the Regional Office by furnishing the requisite data/information/monitoring reports.	Agreed. Being and shall be complied.
xix.	The Environmental statement for each financial year ending 31 March in For –V is mandated to be submitted by the project proponent for the concerned State Pollution Control Board as prescribed Under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be uploaded on the company’s website along with the status of compliance of EC conditions and shall be sent to the respective Regional Offices of the MoEF by E-mail.	Being complied. Agreed.
7	The Ministry or any other competent authority may stipulate any further condition(s) for environmental protection.	Agreed
8	Failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract the provisions of the Environment (Protection) Act, 1986.	Agreed

9	<p>The above conditions will be enforced inter-alia, under the provisions of the Water (Prevention & Control of Pollution) Act, 1974, the Air (Prevention & Control of Pollution) Act, 1981, the Environment (Protection) Act, 1986 and the Public Liability Insurance Act, 1991 along with their amendments and Rules. The proponent shall ensure to undertake and provide for the costs incurred for taking up remedial measures in case of soil contamination, contamination of groundwater and surface water, and occupational and other diseases due to the mining operations.</p>	<p>Agreed</p>
10	<p>The Environmental Clearance is subject to the outcome of the Writ Petition filed by M/S Bharat Coking Coal Limited (BCCL) in response to the closure orders issued by the Jharkhand State Pollution Control Board which is pending in the Jharkhand High Court.</p>	<p>Agreed</p>

Done
28.05.20
 Project officer,
 Lohapada colliery / 20/21 pits Murulidih colliery
 Project Officer
 Murulidih 20/21 Pits Colliery

ANNEXURE- I

A. Production from October'19 to March'20 of Cluster XIII mines

Total Month		Oct'19	Nov'19	Dec'19	Jan'20	Feb'20	March'20 (Million ton)	
Cluster XIII	Murulidih 20/21 pits	0	0	0	0	0	0	0
	Bhurungiya Colliery	Nil						Nil
	Muchraidih Colliery							
	Hantoodih Colliery							
	Padugora Colliery							
	Murulidih Colliery							
	Bhatdeeh Colliery							
	Total (in Million ton)							0
	Remarks:- Murulidih 2/21 pits colliery temporarily closed for production from Dec'2015							

DELINEATION OF SURFACE COAL FIRE AND LAND SUBSIDENCE IN THE JHARIA COALFIELD, DHANBAD, JHARKHAND FROM REMOTE SENSING DATA

**GEOSCIENCES GROUP
REMOTE SENSING APPLICATIONS AREA
NATIONAL REMOTE SENSING CENTRE
INDIAN SPACE RESEARCH ORGANISATION
DEPT. OF SPACE, GOVT. OF INDIA
HYDERABAD-500 037**



JANUARY, 2018

**DELINEATION OF SURFACE COAL FIRE AND
LAND SUBSIDENCE IN THE JHARIA COALFIELD,
DHANBAD, JHARKHAND FROM REMOTE
SENSING DATA**

Report for

BHARAT COKING COAL LIMITED (BCCL)

(A SUBSIDIARY OF COAL INDIA LTD.)

ENVIRONMENT DEPARTMENT, KOYLA BHAWAN

KOYLA NAGAR, DHANBAD – 826 005, JHARKHAND

GEOSCIENCES GROUP

REMOTE SENSING APPLICATIONS AREA

NATIONAL REMOTE SENSING CENTRE

INDIAN SPACE RESEARCH ORGANISATION

DEPT. OF SPACE, GOVT. OF INDIA

HYDERABAD-500 037

JANUARY, 2018



1. **Dr. K VINOD KUMAR**, Group Head, Geosciences Group
Project formulation and coordination
2. **Dr. Tapas R. Martha**, Scientist ‘SF’
Field survey and report preparation
3. **Shri Priyom Roy**, Scientist ‘SD’
Image processing, interpretation, field survey, maps and report preparation

- 1. Dr. K VINOD KUMAR**, Group Head, Geosciences Group
Project formulation and coordination
- 2. Dr. Tapas R. Martha**, Scientist ‘SF’
Field survey and report preparation
- 3. Shri Priyom Roy**, Scientist ‘SD’
Image processing, interpretation, field survey, maps and report preparation

CONTENTS

ACKNOWLEDGEMENTS	i
EXECUTIVE SUMMARY	ii
LIST OF FIGURES AND TABLES	iii
CHAPTER – I INTRODUCTION	1
1.1 BACKGROUND	2
1.2 OBJECTIVES	2
1.3 STUDY AREA	3
CHAPTER – II GENERAL DESCRIPTION OF THE STUDY AREA	4
2.1 LOCATION AND ACCESSIBILITY	4
2.2 PHYSIOGRAPHY, DRAINAGE AND CLIMATE	4
2.3 GENERAL GEOLOGY	4
CHAPTER – III DATA REQUIREMENTS	7
3.1 REMOTE SENSING DATA	7
3.2 ANCILLARY DATA	7
CHAPTER – IV REMOTE SENSING DATA ANALYSIS	8
4.1 METHODOLOGY	8
4.1.1 PROCESSING OF LANDSAT 8 DATA	8
4.1.2 THRESHOLDING OF RADIANT TEMPERATURE IMAGE	9
4.2 METHODOLOGY FOR SUBSIDENCE DETECTION	12
4.2.1 PROCESSING OF ALOS-PALSAR-2 DATA	12
CHAPTER – V FIELDWORK	17
CHAPTER – VI POST FIELD WORK ANALYSIS	19
CHAPTER – VII DISCUSSIONS AND CONCLUSIONS	20
7.1 DISCUSSION	20
7.2 CONCLUSIONS	22
CHAPTER – VIII LIMITATIONS	24
REFERENCES	26
Annexure – I	27
Annexure - II	29
Annexure - III	31
Annexure - IV	34

ACKNOWLEDGEMENTS

The project team is grateful to Dr. Y.V.N. Krishnamurthy, Director, NRSC, for his support at various stages during execution of this project. We are extremely grateful to Dr. P.V.N. Rao, Deputy Director (RSAA), NRSC for his overall guidance and encouragement. We thank Shri D. Gangopadhyay (Director, P&P). BCCL, for this project initiative and for providing Geosciences group, NRSC, the opportunity to carry out the task. We are thankful to Shri A. K. Singh (GM, I/C), BCCL for taking keen interest in the project work and for the support during our fieldwork. We also thank Shri Dipankar Maity, Surveyor (Mining) and Shri Mithilesh Kumar, Sr. Manager (Mining) for their support and fruitful discussion during the fieldwork. The support of all the BCCL officials in the various collieries visited during the course of the ground truth verification is duly acknowledged.

EXECUTIVE SUMMARY

Coal fire is a serious problem in Jharia coal field, where high ranking coals are gradually burnt due to these fires. The combined effect of surface and sub-surface fires and mining related subsidence has endangered the environmental stability of Jharia coal field. Coupled with the ecological changes instigated by open cast mining, the landscape in and around Jharia have changed drastically over the years. In the present study, delineation of coal fire and mining related land subsidence have been addressed. Thermal band of Landsat-8 (100m resolution) have been used to demarcate the coal mine fire areas from non fire areas. For this study, Landsat-8 data of May, 2017 have been used. The band 10 (10.60-11.19 μm) of Landsat-8 data is used to derive the relative radiant temperature. Further ALOS-PALSAR 2, L band microwave data has been used to delineate zone of probable land subsidence (using differential interferometry) due to mining. The study reflects that, compared to 2012, the eastern flanks (Lodna and Tisra) show a larger fire area. The western flank (Nadkhurkee and Shatabdi) and the northern flank (Katrass and Gaslitand) show isolated fire pockets in active mines as well as OB dumps. Among all the colliery areas, Kusunda and Lodna area is most affected by coal mine fire. The current fire area mapped is 3.28 sq.km. Apart from this, five distinctive areas of land subsidence have been identified using interferometric method. These are primarily caused by older or active underground mining. The Moonidih Project is most affected by subsidence. The coal mine fire and subsidence areas are further verified on the ground. The final coal mine fire and subsidence map of Jharia coal field is prepared by using remote sensing data analysis with field validation.

LIST OF FIGURES AND TABLES

- Figure 1 : Study area map of Jharia Coalfield, Jharkhand
- Figure 2 : Geological map of Jharia coal field, Dhanbad, Jharkhand (published by CMPDIL)
- Figure 3 : False colour composite image of Jharia Coalfield (VNIR 3N,2,1) , with subset blocks (in red) to obtain temperature values (from radiant temperature image) within the Barakar formation across the Jharia coalfield.
- Figure 4 : Maximum temperature plotted against mean temperature for various locations; cluster separation observed around 39 °C (marked with arrow)
- Figure 5 : Coal mine fire map (May, 2017) of Jharia coal field, Dhanbad. The fire areas shown in this map have been verified in the field as per field points in figure 13.
- Figure 6 : DInSAR acquisition scheme
- Figure 7 : Work flow diagram for generating land subsidence map using DInSAR technique
- Figure 8 : ALOS-PALSAR - 2 Master-Slave pairs for short and long temporal base line processing
- Figure 9 : Fringe patterns generated from short baseline processing (e.g. Master: Oct, 16, Slave: Feb, 17)
- Figure 10 : Fringe patterns generated from long baseline processing (e.g. Master: Oct, 15, Slave: Feb, 17)
- Figure 11 : Subsidence map of Jharia coal field, Dhanbad
- Figure 12 : Total fire area statistics
- Figure 13 : Field data points for coal fire verification
- Figure 14 : Field data points for subsidence verification

Field Photographs

- Figure 15 : Fume cracks in Lodna-Tisra Area. (point 39 in figure 13 and table 4)
- Figure 16 : Burnt area near OB dump in Lodna area (point 41 in figure 13 and table 4).

- Figure 17 : Coalfries in active seams in Kusunda (point 23 in figure 13 and table 4)
- Figure 18 : Sagged area due to subsidence, south of Block II OCP. (point 1 in figure 14 and table 5).
- Figure 19 : Fire in OB dumps in Kusunda area. (point 24 in figure 13 and table 4).
- Figure 20 : Fume cracks in the Bhulanbarari area.

List of Tables

- Table 1 : Generalised stratigraphy of JCF
- Table 2 : List of satellite data used in the present study
- Table 3 : Threshold temperature for fire area estimation of individual mines.
- Table 4 : Coal Fire observations during fieldwork (see figure 13 for reference)
- Table 5 : Coal Fire observations during fieldwork (see figure 14 for reference)
- Table 6 : Colliery wise break-up of change in fire area from 2012 to 2017

CHAPTER I

INTRODUCTION

Coal fire is a perennial problem in Jharia coal field (JCF) covering 447 sq. km. area in the Dhanbad district of Jharkhand state. Subsurface and surface coal fires are a serious problem in many coal-producing countries. The severity and extent of mine fires in some of the Indian coalfields, particularly Jharia and Raniganj coalfields, are quite alarming. Combustion can occur either within coal or in coal dumps on the surface. Considerable economic loss and environmental problem arises due to the coal fire. Coal fire burns valuable coal and also creates difficulties in mining by increasing the cost of production or making existing operations difficult. Noxious gases like sulphur dioxide, nitrogen oxide, carbon monoxide, carbon dioxides, which are the result of coal burning processes, often affect the immediate surroundings of an active coal fire area (Gangopadhyay, 2003). These greenhouse gases not only affect local atmosphere but also play a crucial role in the damages, found associated with coal fire such as land surface subsidence and surface cracking. Coal fires are caused by oxidation of coal but the reaction involved in oxidation of coal is not understood till date. Broadly, the potential for spontaneous combustion lies in its ability to react with oxygen at ambient temperature. This occurs through the reaction of oxygen at the surface of the coal resulting in an exothermic reaction. As a consequence, the temperature of coal rises and if temperature reaches the threshold temperature, ranging between 80⁰ to 120⁰C, a steady reaction starts, which produces carbon dioxide. Temperature keeps on increasing once CO₂ started to form and at 2300⁰C, the exothermic reaction becomes rapid. It is known that high grade coals (high carbon content) are more fire prone, though the reason behind this is not well understood. Another important parameter, which controls fire, is the size of the particles. Larger the effective area of coal (fire particles), more rapidly the reaction proceeds. Cracks, fissures play a role like positive catalysts to coal oxidation by slowly supplying oxygen / air through their conduits.

Coal mining in Jharia Coal Field (JCF) started way back in 1895. History of fire in Jharia Coal Field date back to 1916 when the first incidence of fire was reported from XIV seam of Bhowrah colliery. JCF was nationalised in 1972 and over the decades, the fire has spread or been contained but never extinguished. The combination of underground fire and subsidence have affected vast areas of JCF.

1.1 Background

Remote sensing technique in thermal band offers a cost-effective and time-saving technology for mapping various geoenvironmental / hazardous features such as coal fires, forest fires, oil well fires, volcanic eruptions etc. NRSC has carried out coal fire mapping projects in the past; conducting an airborne campaign in 1989 and using Landsat-5 TM data in 1995 (Bhattacharya *et. al.*, 1995), over Jharia coalfield, Jharkhand and using Landsat-5 TM data for 2001 over Raniganj coalfield, West Bengal. Further, projects were executed in 2006 and 2012 in which coal fires of the JCF were mapped using Landsat-7 ETM+ and ASTER data, respectively. Additionally, a R&D study was taken up in 2013 to delineate subsidence areas using differential interferometric (DInSAR) technique. In view of the past experiences, based on the letter (Ref. no. NRSC/16/76) from Director (Tech.), Operations, BCCL addressed to Director, NRSC on 01 February 2016. a project was formulated to take up Coal fire and Land Subsidence study of the Jharia Coal Field using space-borne remote sensing technique. The formal Memorandum of Understanding between BCCL and NRSC was signed on 23rd of Dec, 2016.

1.2 Objectives

The following objectives are formulated on the basis of the above mentioned background:

- I. To map Coal fire in the study area based on pixel integrated relative radiant temperature derived from latest available Landsat-8 data of 2016-17 time period.
- II. To compare the change in the coal fire distribution in the Jharia coalfield within the period of 2012 and 2016-17.
- III. To delineate probable subsidence areas in the region using differential interferometry method.

1.3 Study Area

Jharia Coalfield is located in the Dhanbad district of Jharkhand state (Figure 1) and it is named after the main coal mining town of Jharia. It is situated in the Damodar River valley and is about 250 km NW of Kolkata. The coalfield is contained roughly within latitudes $23^{\circ} 42' N$ and $23^{\circ} 50' N$ and longitudes $86^{\circ} 09' E$ and $86^{\circ} 30' E$.




Figure 1: Study area map of Jharia Coalfield, Jharkhand

CHAPTER II

GENERAL DESCRIPTION OF THE STUDY AREA

2.1 Location and Accessibility

Jharia is an old mining town in the Dhanbad district of Jharkhand. This town is famous for its surrounding mines producing high grade coal and supplying mainly to the neighbouring industrial areas. Jharia is approximately 6 km in south western direction from Dhanbad town and connected by metal road. Dhanbad is well connected to Kolkata by road and rail.

2.2 Physiography, Drainage and Climate

Jharia coalfield is characterised by undulatory topography with very low rolling slope towards the eastern part of the area. The average height of the area is around 200 meters above the mean sea level. Damodar is the major river in the study area. The other tributaries to the Damodar River in this area are Jamuniya Nadi, Khudia Nadi, Khatri Nadi, Jarian Nala, Kari Jora and Domohani Nadi. Damodar River flows from west to east in this area. The minimum temperature is $<10^{\circ}$ C in the month of December – January and maximum temperature is $>50^{\circ}$ C in the month of May – June.

2.3 General Geology

Gondwana Super Groups of rocks of Up. Carboniferous to Lr. Cretaceous age (i.e. from 320 MY to 98 MY) are exposed here. Gondwana Super Group rocks unconformably overlie Archaean rocks. In Gondwana Rocks, Raniganj and Barakar Formations of Permian age have more potential as far as the coal production is concerned. Barakar Formation is exposed in north and north eastern part of the basin (Figure 2). Most of the coal mines are confined to the Barakar Formation in JCF. Barakars consists of coarse, medium grey and white sandstones, shales and coal seams. Raniganj consists of grey and greenish soft feldspathic sandstones, shales and coal seams. Faults are prevalent in this portion of basins (Figure 2). NW trending faults are conspicuous north to Jharia. Many lamprophyre and dolerite dykes are also exposed in this area in a criss-cross manner. The Raniganj Formation though coal bearing, has suffered much deformation due to faulting, thus causing difficulty for

mining in the area. The generalised stratigraphy of JCF is mentioned below (after Saraf, et al., 1995).

FORMATION	LITHOLOGY	MAXIMUM THICKNESS
Supra Panchet	Red and Grey sandstones and shales	300m
Panchet	Micaceous Yellow and Grey sandstones, Red and Greenish shales	600m
Raniganj	Grey and Greenish soft feldspathic sandstones, shales and coal seams	1050m
Ironstone Shales	Dark carbonaceous shales with ironstone bands	360m
Barakar	Coarse and medium Grey and white sandstones, shales and coal seams	630m
Talchir Boulder Bed	Coarse sandstones above and Greenish shales below	300m

Table 1: Generalised stratigraphy of JCF.




Figure 2 : Geological map of Jharia coal field, Dhanbad, Jharkhand (published by CMPDIL)

CHAPTER III

DATA REQUIREMENTS

3.1 Remote Sensing Data

The most recent available thermal satellite data was used in conjunction with the fieldwork for mapping coal fire in JCF. A coal fire map generated from the same, would serve as a reference for the fieldwork, as the observations can be verified in the field. For this purpose, a coal fire map was created from LANDSAT 8 TIRS data of 14-May 2017 .

Further, the coal fire map of 2012 prepared by NRSC (NRSC, 2012) from ASTER data was used as a reference to identify the changes that has occurred in the extent and disposition of the fires from 2012 to 2017.

For the land subsidence study, L-band microwave data from ALOS-PALSAR satellite (JAXA) were used. Five scenes of "Fine mode" SLC data were taken from PALSAR-2 archives over a period from October, 2014 to February, 2017. This was done to identify long term terrain changes and differentiate the same from short term changes due to mining excavations and overburden dumping.

Table 2: List of satellite data used in the present study.

Sl. No	Satellite	Sensor	Time	Date	Data source
1	LANDSAT-8	TIRS	Daytime	14 May 2017	USGS, USA
2	ALOS-PALSAR-2 (Fine mode)	PALSAR-2	-	4 October. 2014	JAXA, Japan
3				3 October, 2015	
4				20 February. 2016	
5				01 October, 2016	
6				18 February. 2017	

3.2 Ancillary data

1. Geological map of Jharia coal field.
2. Mine surface plans as provided by BCCL.

CHAPTER IV**REMOTE SENSING DATA ANALYSIS****4.1 Methodology****4.1.1 Processing of Landsat 8 Data**

With the launch of the LANDSAT-8 mission in February, 2013; thermal space borne data is available from its thermal infrared sensor (TIRS). This has enabled monitoring of the earth with a spatial resolution of 100 m in the thermal domain with a repeat cycle of 16 days. The LANDSAT-8 has two channels (Band 10 and Band 11) in the thermal infrared region (Table 1) which ranges from 10.4 micrometer to 12.5 micrometer. In present study, band 10 of TIRS sensor (acquired on 14 May, 2017) has been used coal fire mapping (Gangopadhyay et al. 2012). The spectral domain of the band is known for its maximum transmittance (Chatterjee et al. 2007; Martha et al. 2010). The data are freely accessible through USGS portal (Landsat 8 download source: <http://landsatlook.usgs.gov>).

Landsat-8 data are available in GeoTiff format and the data are converted to top of the atmosphere spectral radiance using the radiance rescaling factors provided in the metadata file, using equation 1.

$$L_{\lambda} = M_L Q_{cal} + A_L \dots\dots\dots (1)$$

Where:

L_{λ} = Spectral radiance (Watts/ (m² * srad * μ m)).

M_L = Band-specific multiplicative rescaling factor from the metadata.

A_L = Band-specific additive rescaling factor from the metadata.

Q_{cal} = Quantized and calibrated standard product pixel values (DN).

Once the spectral radiance (L_{λ}) for ASTER Band 13 and Landsat-8 band 10 data is generated, it is possible to calculate radiant (brightness) temperature directly using equation 2. Planck's radiation function (Planck, 1914) forms the basis of radiant temperature derivation from spectral radiances and the theory is discussed in detail in existing literatures (Gupta, 2003).

$$T_R = K_2 / \ln ((K_1 / L_{\lambda}) + 1) \dots\dots\dots (2)$$

T_R = Radiant (brightness) temperature,

K_1 = Calibration constant (1260.56 K),

K_2 = Calibration constant (666.09 watts/ (m² *ster* μ m)),

L_λ = Spectral radiance

4.1.2 Thresholding of radiant temperature image

Once the Landsat-8 data are converted to radiant temperature image, the next step was to segregate fire pixels from the background, which requires the estimation of the cut-off temperature (Roy et al. 2015). This has been attempted by the statistical analysis of sensor derived radiant temperature to delineate clusters (in the scatter-plot) indicative for fire and non-fire pixels. Mean and maximum radiant temperatures are derived from randomly sampled uniform sized pixel blocks distributed in entire spatial extent of Barakar formation (Figure 3) known for fire bearing coal seams. The pixel block sizes are chosen to adequately represent the overall areal extent of the coalfield and homogeneously encompass all the mining blocks (27x27 pixels for Landsat-8, Figure 3). The maximum temperature value recorded in each representative area, derived from each of the datasets, is plotted against the mean temperature. The maximum temperature represents that of fire (wherever present), whereas the mean temperature represents the average background temperature, for normalization. The fire and background populations show considerable variance, separating coal fire and background radiant temperatures. The cut-off temperature derived is the maximum temperature of the background cluster, above which all temperatures represent coal fires. In the case of the Landsat-8 data used in this study, the cut-off temperature was determined around 39°C (Figure 4). Based on this cut-offs, regional coal fire map was prepared (Figure 5).




Figure 3. False colour composite image of Jharia Coalfield, with subset blocks (in red boxes) to obtain temperature values (from radiant temperature image) within the Barakar formation across the Jharia coalfield.




Figure 4. Maximum temperature plotted against mean temperature for various locations; cluster separation observed around 39 °C (marked with arrow)




Figure 5: Coal mine fire map (May, 2017) of Jharia coal field, Dhanbad. The fire areas shown in this map have been verified in the field as per field points in figure 13.

4.2 Methodology For Subsidence Detection

4.2.1 Processing of ALOS-PALSAR 2 Data

Differential Interferometric SAR (DInSAR) techniques consist of combination of two SAR images of the same area acquired from slightly different positions (Figure 6).




Figure 6. DInSAR acquisition scheme.

The result of this combination provides a new image, known as 'interferogram', whose phase component is formed by the following term:

$$\Delta\Phi_{Int} = \Phi_{Topo} + \Phi_{Mov} + \Phi_{Atm} + \Phi_{Noise} \quad (3)$$

where, Φ_{Topo} denotes the topographic component, Φ_{Mov} denotes the terrain deformation/ displacement component, Φ_{Atm} is the noise component and Φ_{Noise} is the thermal noise.

Topography, atmospheric effects and thermal noise needs to be removed or optimized to obtain precise measurements of terrain movement. When working with classical DInSAR interferograms (combination of two SAR images) the main problem is the presence of atmospheric artefacts, since there is no way to cancel them without a priori information. On the other hand, the term related with topography can be cancelled out using an external Digital Elevation Model (DEM) and the orbital ephemeris from the SAR acquisitions, considering no height errors on the DEM.

$$\Delta\Phi_{dif} = \Phi_{ErrorTopo} + \Phi_{Mov} + \Phi_{Atm} + \Phi_{Noise} \quad (ii)$$

Since the coal mine area is very dynamic in terms of its surfacial changes (open cast mine, abandoned mine, fire affected waste/reclaimed land, over burden dumps) over time, it is proposed to utilize an advanced DInSAR technique. It is a recent remarkable improvements in SAR differential interferometry that has led to an innovative approach based on the use of a large dataset of SAR images over the same area to overcome the intrinsic limitations of conventional DInSAR in terms of temporal and geometrical decorrelation as well as atmospheric disturbances (Ferretti et al 2001; Hooper et al 2004; Kampes, 2006; Lanari et al 2004; Mora et al 2003; Werner et al 2003).

Broad work flow diagram for generating land subsidence map using satellite based DInSAR technique is shown in Figure 7.




Figure 7. Work flow diagram for generating land subsidence map using DInSAR technique.

In the present study, 5 sets of ALOS-PALSAR L-band microwave data (as mentioned in table 1) were procured. The datasets were paired into master-slave pairs as per short and long temporal baselines. The short temporal baselines include master slave pairs of time difference of six months or less, whereas long temporal baselines include data pairs of time difference of one year or more. This has been illustrated in figure 8.

		SLAVE IMAGE				
		October, 2014	October, 2015	February, 2016	October, 2016	February, 2017
MASTER IMAGE	October, 2014					
	October, 2015					
	February, 2016					
	October, 2016					
	February, 2017					
		Short Temporal Baseline Pair (less than 1 year)				
		Long Temporal Baseline Pair (more than 1 year)				

Figure 8. ALOS-PALSAR - 2 Master-Slave pairs for short and long temporal baseline processing

The interferometric fringes generating from short baseline pairs will generally indicate terrain changes due to mining activity happening over a short period of time. This will include mining excavations and creation of new OB dumps adjacent to the mining area. Any incidences of slow land subsidence will not be demarcated in the results (figure 9).




Figure 9. Fringe patterns generated from short baseline processing (e.g. Master: Oct, 16, Slave: Feb, 17).

On the other hand, master-slave pairs of long temporal baseline (one year or more, as shown in figure 8) will incorporate terrain changes due to mining activities as well, as long term ground subsidence from underground mining where ever present (figure 10).




Figure 10. Fringe patterns generated from long baseline processing (e.g. Master: Oct, 15, Slave: Feb, 17).

The results from the long and short baseline processing can be compared and zone where fringes have been developed due to terrain changes due to mining excavation and dumping, can be systematically identified and demarcated. The remaining fringes from the long temporal baseline processing will then indicated towards zones where subsidence has taken place due to underground mining. Using this, a terrain change

map of the Jharia Coalfield was generated demarcating terrain changes due to mining activities and subsidence areas (Figure 11).




Figure 11: Subsidence map of Jharia coal field, Dhanbad.

CHAPTER V

FIELD WORK

A field work for verification of the coal fire locations and the subsidence zones as identified by the satellite data were taken up in December, 2017. A total of 53 coal fire points and 37 land subsidence locations were identified from the satellite data analysis. The locations of these points along with geographic coordinates were given to BCCL prior to the December, 2017 field work for their feedback on the status of these points. Out of the 53 coal fire locations identified, 52 points were confirmed to be fire bearing as per the present masterplan of the Jharia coalfield created by BCCL. Both the coal fire and the subsidence locations were further independently verified by NRSC during the fieldwork in December, 2017. The locations and the observations are coal fire and subsidence are provided in annexure 1 and annexure 2 of this report respectively.

The salient overview of the field observations are as follows:

Coal-fire observations:

1. The coal fires as observed identified by the Landsat-8 data are mostly accurately delineated. Fires have been identified in the western, northern and eastern flank of the coalfield with considerable accuracy in the spatial locations.
2. In the eastern flank, the main fire affected mines are Kusunda, Lodna and Tisra. Active fires area present in the mines and fumes can be seen from the OB dumps. The Bhowra and Bhulanbarari mines also show presence of fire, however, the extent of the fire area appears to be underestimated in the data. Similarly, the extent of fires in Lodna and Tisra appears to have been overestimated in the data. The largest extent of fire in the single mine block is that in Kusunda.
3. In the northern flank, the main fire bearing mines are Katras, Gaslitand and Mudidih, However, it is seen that in these areas, the fires appears in pockets and are not pervasively present. The spatial extent of the fires on the ground and as estimated in the data can be correlated.

4. In the western flank, the Block II OCP is the primary fire affected region. However, it is seen that the Shatabdi OCP also bears fire pockets along semi-vertical mine walls, This is not identified in the data.

Subsidence location observations:

1. Subsidence locations as identified by the data area difficult to verify in the field, unless there are tell-tale signatures like large cracks or fissures on the ground or damage to anthropogenic constructions like vertical cracks on building cracks etc.
2. Out of the 37 identified subsidence locations from the microwave data, it is seen that 32 are due to terrain changes resulting from mining activities like ongoing excavations or formation of new mining dump. These decrease or increase in elevations has resulted in forming of interferometric fringes in the data thus creating false positives.
3. Five areas were firmly established as subsidence zones. Out of these, the main area where subsidence is occurring in a pervasive scale, is that in the Moonidih Underground Project. The Moonidih Project is an underground long wall mine where excavations are going on for over decades. This may have resulted in pervasive subsidence in the region. The signatures of subsidence such as ground cracks are observed in the area.
4. Two adjacent locations are observed south of the Block II OCP and in Phularitand mining block. This may be resulted due to older underground mining in the area. Signatures such as sagging of ground is seen.
5. Another minor subsidence region was identified around the Simlabahal underground mining project. This is again due to active underground mining in the area. A similar region was also observed in the northern part of the Bastacolla mines where active underground mining is ongoing.

In lieu of the observations in field on the fire and subsidence locations, few post field work correction in the coal fire and subsidence maps was necessitated and has been discussed in the next chapter.

CHAPTER VI**POST FIELDWORK ANALYSIS**

As observed in the fieldwork, there were certain mine areas where the presence of fire was not detected by the satellite data. For example in Shatabdi and Bhulanbarari mine areas, the fire appears in small pockets on mine faces and was possibly not detected by the threshold temperature calculated for the entire mine area. On the other hand, in the Bhowra, Lodna and Tisra mine areas, the spatial extent of fire appears to have been overestimated by the regional threshold temperature use to separate the fire and the background areas.

Therefore, mine specific threshold temperature analysis was carried out for Shatabdi, Bhulanbarari, Bhowra, Lodna and Tisra mine areas to correctly depict the fire areas on the ground. The threshold temperature selected from each of these mine areas are given in Table 3.

Table 3: Threshold temperature for fire area estimation of individual mines.

Name of the Mine Block	Threshold Temperature (in °C)
Bhowra	38.5
Tisra (north and south)	North : 41; South : 40.5
Lodna	41
Bhulanbarari	38.5
Shatabdi	38

Using the threshold temperatures as mentioned in the table 3, the previously undetected fire areas in the Shatabdi and Bhulanbarari mines were detected. Further the spatial extent of the fire areas in Bhowra, Lodna and Tisra mines were changed to adequately represent the actual extent of the fire on the ground. These were incorporated in the coalfire map shown in figure 5.

DISCUSSIONS AND CONCLUSIONS

CHAPTER VII

7.1 Discussions

7.1.1 Coal fire analysis

The present study is aimed to provide the status of coal fire in the Jharia coal field for the period of 2017. Landsat-8 data of May, 2012 was used to prepare the coal mine fire map (Figure 5) for the year 2017. The data have 100 m spatial resolution in the thermal bands and is as on study date, the best thermal satellite data available. The Coal fire maps of 2017 when compared to map of 2012 (NRSC, 2014) depicts the dynamics of coal fire. Coal fire is difficult to mitigate because of its dynamic nature. But the understanding the trend in the shift of coal fire zones and over all distribution of coal fire will help in environmental and risk management related to coal mining activities.

The coal mine fire map for the year 2017 (Figure 5 illustrates the overall fire distribution in the area). The maps reveal that the coal fires are distributed across the Jharia coal field in pockets associated with major open cast mining activities. All most all the coal mine fires are restricted to the Barakar Formation where coal seams are exposed. In the eastern flank of the arcuate shaped mining extent, the collieries in Lodna and Tisra (North and South) is the highest fire affected mining blocks and Bhowra, Bhulanbarari, Kujama and Jharia are also affected by multiple smaller fire pockets. The fire in the areas is mostly manifested by high temperature fume cracks with occasional presence of active flames especially the the Lodna-Tisra area. Further, towards the north east, in Ena and Kusunda active fires are more prevalent and the area is extensively affected. The highest radiant temperatures (in order of ~50°C) are recorded by the satellite sensors in these areas. In the north, a large number of moderate to small fire pockets are seen in the areas around Shyambazar (Figure 5 & 6). These are related to the mining areas of Katras, Gaslitand, Mudidih and Kankanee. Mining activity, over the last few of years has exposed new, isolated and discontinuous fires in these regions.

In the western flank, three distinguishable fire affected zones are seen. Toward the western end of the mining area, the Benedih and Block II OCP are affected by smaller fires from isolated coal seams. These again are surfacially manifested in the

form of fume cracks with smoke emanating from them. The Shatabdi OCP are also affected but fire is manifested in the along vertical mining wall sections.

Comparison of the 2017 coal fire map with that of 2012 (NRSC, 2014) indicated the dynamism in the spatial extent and distribution of the coal fires. The changes are highlighted as follows:

- i. In reference to the map generated in 2012, the 2017 map shows that the emergence/re-emergence of fires in the eastern flank, namely Kujama, Tisra, Lodna and Jharia etc. The entire zone has been affected by multiple fire occurrences. The spatial disposition of fires in Bastacolla, Jharia and Bhulanbarari appear to have a minor increase.
- ii. The areal extent of major fire zone around Kusunda/Kenduadih and Ena appears to remain the same, though here again the spatial location of the anomalies has changed. This is probably due to the mitigation and active mining in this region.
- iii. The fire zones in Benedih/Block II OCP and Shatabdi OCP have also changed/diminished in areal extent with presence of isolated smaller anomalies. There has been a considerable reduction in fire areas in and around the Shatabdi OCP.
- iv. The spatial disposition of fire areas around Katras, Gaslitand and Mudidih show minor change. In 2012, a number of small fire pockets were seen, however presently those fire pockets have given away to a few fire zones of moderate disposition.
- v. It needs to be noted that the 2012 study was carried out using ASTER data whereas the present study is carried out using Landsat-8 data. Therefore, the difference of sensor sensitivities will have a influence on the way the fires are sensed on the ground. Difference of sensor sensitivities will influence the number of fires identified as well as the areal extent of the fires in the data.

In summary, there is a change in the areal disposition of the fires from 2012 to 2017. Observations suggest the emergence/re-emergence of new areas in the eastern flanks in areas around Lodna and Tisra. Concurrently, there is a decrease in extent of fire areas Shatabdi, Nadkhurkee area in the western flank from 2012 to 2017. A quantitative comparison of the 2012 and 2017 data was carried out. As compared

2012, when the total fire affected extent of about 2.18 km²; in 2017 total fire affected extent is about 3.28 km². The colliery wise break-up of change in fire area from 2012 to 2017 is given in Annexure III.

7.1.2 Subsidence analysis

An attempt to identify subsidence zones in the Jharia Coalfield was also carried out using ALOS-PALSAR-2 L band microwave data using differential interferometric technique. 5 scenes of PALSAR-2 data spanning over a period of 2014 to 2017 were used to delineate the subsidence if any in the region and separately identify them from the terrain changes due to mining. Verification of the subsidence zones as seen from data is difficult as it requires visible signatures of subsidence in the form of cracks on the ground and damage to anthropogenic structures. In this study, data analysis and consequent field verification resulted in identification of 5 prominent subsidence areas. Of these, the major area where considerable ground subsidence is occurring is the Moonidih UG project. Long term underground mining has resulted in continuous subsidence in the area. Apart from this, the other four areas are south of Block II OCP, Simlabahal and Bastacolla. No quantitative estimates of the subsidence has been carried out in the study.

7.2 Conclusions

The following conclusions can be made:

1. As of the date of study in the year 2017 and in comparison with the previous study done in 2012, there has been a change in areal extent and disposition of the fire affected areas.
2. Compared to 2012, the eastern flanks (Lodna, Tisra areas) show considerable increase in fire disposition and the western flank (Shatabdi and Block II area) show diminished fire presence.
3. The major new fire areas are observed in the northern flank in the areas around Lodna and Tisra etc. These areas were not mapped as fire in the 2012 study.
4. The mines in Kenduadih and Lodna remain to be the worst affected with maximum presence of active fires.
5. There is an increase in areal extent of the fire (Figure 12) from 2012 to 2017.

Note: Estimations of fire extent (in terms of sq.km.) both in 2012 and in the present 2017 study are pixel based. They do not represent the actual ground area under fire. These estimations are made for comparative purpose only, to indicate the increase or decrease of areal disposition of fire. Hence, they should not be quoted as fire area on the ground.




Figure 12: Total fire area statistics

CHAPTER VIII

LIMITATIONS

Delineation and mapping of coal fire from thermal data of remote sensing platforms carries with it some inherent limitations which needs to be understood in order to decipher the results obtained from it. This will assist in deducing the correct information and remove any ambiguity associated with the results. The key limitations of the data and the results obtained are as follows:

- 1) An anomalous pixel from LANDSAT data represents an area of 30m x 30m (resampled from spatial resolution of 100m) on the ground whose temperature is considerably higher than its surroundings. This can be attributed to two circumstances, namely the area has a very high intensity fire located within a smaller pocket or there are a number of low intensity fires spread across it. In both the mentioned cases the actual areal extent of the fire on the surface differs, but appears as a single anomalous pixel in the data. Hence, representation of fire affected ground area by means of pixel area is ambiguous and hence should be considered with caution.
- 2) There are locations as observed during the fieldwork, where coal seams are affected by active fires along vertical/semi-vertical sections of open cast mines (see cover page). In such cases, the actual areal expression of the fire affected area as seen by the sensor changes considerably and the representation from the same is not accurate.
- 3) As discussed in section 4.2.1, thresholding the data to separate the fires from the non fire areas, is a statistical technique. However, this method is dependent on how the temperature of non-fire background area is distinctive from the fire temperature.
- 4) The background temperatures vary with the time of the day when the data is collected, topography, and season of the year when the data is acquired. Night-time data has lower background temperature as compared to day-time. Similarly a data collected in October-November will have a considerably lower background temperature than that collected in May-June due to seasonal temperature variations. Hence, identification of the background temperature range becomes essential in

estimation of threshold temperature and the same varies depending upon the discussed controlling factors.

5) Generally, a constant threshold temperature is estimated over the entire study area, and the same is applied to delineate the fire areas from those of non-fire. However, it is seen that the application of such global thresholding may mask fires which are in turn seen in the field and that the threshold temperature value may vary locally. In the current scenario, it is seen that the fire locations as verified in the fieldwork at Bhulanbarari and Shatabdi were not identified in the data on application of a global threshold of 39°C. However, a subset of the data within the Bulanbarari area only, is analyzed with a lower threshold of 38.5°C, the fire pixels are manifested in the data. Hence, the appropriateness of a singular thresholding temperature value may need to be relooked upon. Future studies can be carried out using colliery wise statistical local thresholding to create a composite coal fire map.

6) Due to the mitigation measures taking place in various mines, it is seen that in a number of places the fire affected seam is excavated and dumped as overburden. However, these overburden dumps retain the excavated burning coals and thus are seen to have active fires occasionally. There lies a possibility that the same will be identified as anomalous pixels and hence, although the fire is not a part of any active coal seam, it will be included as a fire affected area in the final map.

7) Verification of the subsidence zones as detected from the interferometric technique is sometimes difficult due to lack in observable signatures of subsidence such as cracks on the ground and damage to anthropogenic structures.

Therefore, in quantitative estimation of fire affected areas and areas denoted as subsidence, the above mentioned limitations need to be taken into account diligently, as it is inevitable that the area estimate will not define the actual fire/subsidence affected area on the ground. However, the areal extent estimated from the data can be "like to like" compared to earlier estimates of similar studies to understand the change and dynamism of the fire in terms of area affected and spatial disposition.

References

1. Gangopadhyay, P.K., Lahiri-dutt, K., Saha, K. (2005): "Application of remote Sensing to identify coal fires in the Raniganj coal belt, India." *Int. Jour of Applied Earth Observation and Geoinformation*.
2. Gangopadhyay, P.K., Malthuis.B, Van Dink (2005): "Aster Derived emissivity and coal-fire related surface temperature anomaly a case study in Wuda, North China," *Int. Jour. of Remote Sensing*, vol-26, No.-24, pp-5555-5571.
3. Schmugge, T., French, Ritchie, J.C., Rango, A., Pelgrum, H. (2002): "Temperature and emissivity separation from multispectral thermal infrared observation," *Remote Sensing of Environment*, 79, pp-189-198.
4. Saraf A.K., Prakash A., Sengupta, S., Gupta, R.P (1995): "Landsat-TM data for estimating ground temperature and depth of sub-surface coal fire in the Jharia coalfield, India," *Int. Jour. Remote sensing vol-16, no-12*, 2111-2124.
5. Gangopadhyay P.K., (2003): "Coalfire detection and monitoring in Wuda, North China, A multispectral and multi-sensor approach:-Ph.D. Thesis, ITC Netherland.
6. Gupta, R.P. (2003): "Remote Sensing Geology", *Springer-Verlag.Third ed.*pp-183-216.
7. Kealey, P.S and Hook S.J(1993): "Separating temperature and emissivity in thermal infrared Multispectral Scanner Data: Implication for recovering land surface temperatures", *IEE Transaction on Geoscience and Remote Sensing*,vol,31,no-6,pp-1155-1164
8. Zhang, J., Wagner, W., Prakash, A., Mehl,H. and Voigt,S.(2004): "Detecting coal fires using remote sensing techniques," *Int. Jour. Remote sensing*, vol-25, no-6, pp3193-3220.
9. Bhattacharya, A. and Reddy, C.S.S. (1995): Inventory and monitoring of underground and surface coal mine fire in Jharia coalfield, Bihar using thematic mapper thermal IR data: *Geosciences Group, Official report, NRSA*.
10. Coal mine fire delineation and surface features mapping using satellite data in Jharia coal field, Dhanbad, Jharkhand. Geology and Geophysics division. *Official report, NRSA, 2006*
11. Coal mine fire delineation and surface features mapping using satellite data in Jharia coal field, Dhanbad, Jharkhand. Geosciences Group. *Official report, NRSC, 2014*

Annexure –I




Table – 4: Coal Fire observations during fieldwork (see figure 13 for reference)

SL No.	Point of Observations		Comments		
	Latitude	Longitude	Type of Mining Activity	Presence of Coal Fire	Mine name and Any other Comments
1	23.7801	86.2068	OB Dump	Fire	ABOCP
2	23.7771	86.2097	Active Mine	Fire	ABOCP
3	23.7739	86.2066	Active Mine	Fire	ABOCP
4	23.7733	86.2124	OB Dump	Fire	ABOCP
5	23.7806	86.2168	No Working	Fire	ABOCP
6	23.7841	86.2192	No Working	Fire	Phularitand
7	23.7893	86.2919	No Working	Fire	Katras Chatudih
8	23.7875	86.2926	No Working	Fire	Katras Chatudih
9	23.7857	86.3049	Working	Fire	Gaslitand
10	23.7768	86.3157	Outside Jharia Mines		Tata
11	23.7887	86.3170	OB Dump	Fire	Gaslitand
12	23.7862	86.3151	OB Dump	Fire	Gaslitand
13	23.7880	86.3133	OB Dump	Fire	Gaslitand
14	23.8054	86.3191	Working	Fire	AKWMC
15	23.7855	86.3363	OB Dump	Fire	Mudidih
16	23.7826	86.3397	Working	Fire	Kankanee
17	23.7800	86.3427	Working	Fire	Kankanee
18	23.7848	86.3327	OB Dump	Fire	Mudidih
19	23.7977	86.3473	OB Dump	Fire	Sendra Bansjora
20	23.7775	86.3540	OB Dump	Fire	Loyabad
21	23.7793	86.3924	No Working	No fire	Kusunda (Domestic coal burning)
22	23.7753	86.3970	Working	Fire	Kusunda
23	23.7724	86.3858	Working	Fire	Kusunda
24	23.7669	86.3940	OB Dump	Fire	Kusunda
25	23.7578	86.3993	OB Dump	Fire	Ena
26	23.7550	86.4009	OB Dump	Fire	Ena
27	23.7645	86.4065	Working	Fire	ADIC
28	23.7580	86.4172	Old Quarry	Fire	ROCP
29	23.7515	86.4184	OB Dump	Fire	ROCP
30	23.7559	86.4137	OB Dump	Fire	ROCP
31	23.7476	86.4232	Working	Fire	ROCP
32	23.7543	86.4431	Outside Jharia Mines		Unknown site (Out side of Kuya)
33	23.7394	86.4317	Active Mine	Fire	Ghanoodih
34	23.7360	86.4362	OB dump	Fire	Goluckdih
35	23.7349	86.4293	OB Dump	Fire	Kujama
36	23.7354	86.4232	No Working	Fire	Kujama
37	23.7301	86.4369	Working	Fire	NT-ST
38	23.7305	86.4265	OB dump	Fire	Kujama
39	23.7249	86.4200	No Working	Fire	Lodna
40	23.7159	86.4327	Working	Fire	Joyrampur
41	23.7254	86.4280	No Working	No fire	Lodna
42	23.7209	86.4376	Working	Fire	NT-ST
43	23.7154	86.4296	Working	Fire	Lodna
44	23.7238	86.4427	Working	Fire	NT-ST
45	23.7309	86.4457	OB dump	Fire	NT-ST
46	23.7151	86.4412	Active Mine	Yes	NT-ST
47	23.7114	86.4419	OB Dump	Fire	NT-ST
48	23.7073	86.4360	Active Mine	Fire	Joyrampur
49	23.7097	86.4243	Working	Fire	Bagdigi/Joyrampur
50	23.7079	86.4249	Active Mine	Fire	Bagdigi/Joyrampur
51	23.7086	86.4582	Outside Jharia Mines		Unknown site (Out side of NT-ST)
52	23.6614	86.4404	Outside Jharia Mines		Chasnala
53	23.6906	86.3892	OB dump	Fire	Bhowrah (North)




Figure 14. Field data points for subsidence verification

Table – 5: Coal Fire observations during fieldwork (see figure 14 for reference)

Sr. no.	Point of Observations		Comments	
	Latitude	Longitude	Mine name and Any other Comments	Signs of Subsidence (crack on building/ground crack etc.)
0	23.7416	86.3338	Moonidih UG Project	Sagged area, Building damage
1	23.7722	86.2192	South of Block II (2 areas)	Cracks on the ground
2	23.7817	86.2409		Terrain Change due to mining
3	23.7811	86.2521		Terrain Change due to mining
4	23.7792	86.2376		Terrain Change due to mining
5	23.7983	86.2473		Terrain Change due to mining
6	23.7981	86.2510		Terrain Change due to mining
7	23.8088	86.2521		Terrain Change due to mining
8	23.7941	86.2636		Terrain Change due to mining
9	23.7926	86.2671		Terrain Change due to mining
10	23.7868	86.2724		Terrain Change due to mining
11	23.7928	86.2746		Terrain Change due to mining
12	23.7800	86.2857		Terrain Change due to mining
13	23.7713	86.3171		Terrain Change due to mining
14	23.7783	86.3270		Terrain Change due to mining
15	23.7893	86.3419		Terrain Change due to mining
16	23.7734	86.3556		Terrain Change due to mining
17	23.7734	86.3762		Terrain Change due to mining
18	23.7804	86.3742		Terrain Change due to mining
19	23.7865	86.3769		Terrain Change due to mining
20	23.7855	86.3890		Terrain Change due to mining
21	23.7679	86.4199	Bastacolla	Sagged areas
22	23.7390	86.4071	Simlabahal UG	Sagged areas
23	23.7417	86.4431		Terrain Change due to mining
24	23.7176	86.4163		Terrain Change due to mining
25	23.7085	86.4339		Terrain Change due to mining
26	23.6986	86.4304		Terrain Change due to mining
27	23.6923	86.4312		Terrain Change due to mining
28	23.6977	86.4466		Terrain Change due to mining
29	23.7092	86.3967		Terrain Change due to mining
30	23.6985	86.3942		Terrain Change due to mining
31	23.6845	86.3681		Terrain Change due to mining
32	23.6804	86.4083		Terrain Change due to mining
33	23.6685	86.4110		Terrain Change due to mining
34	23.6706	86.4211		Terrain Change due to mining
35	23.6603	86.4366		Terrain Change due to mining
36	23.6568	86.4454		Terrain Change due to mining
37	23.6760	86.4516		Terrain Change due to mining
38	23.7603	86.3836		Terrain Change due to mining
39	23.7734	86.3609		Terrain Change due to mining
40	23.7948	86.3715		Terrain Change due to mining

Annexure –III

SL. NO.	COLLIERY AREA NAME	FIRE AREA 2012 (SQ. KM.)	FIRE AREA 2017 (SQ. KM.)	AREA CHANGE (SQ. KM.)	Increase/Decrease
1	DAMODA	0.0000	0.0000	0.000	NO FIRE
2	TISCO (west)	0.0000	0.0000	0.000	NO FIRE
3	IISCO	0.0000	0.0000	0.000	NO FIRE
4	TISCO (north)	0.0885	0.0153	-0.073	DECREASE
5	NUDKHURKEE OCP	0.0000	0.0000	0.000	NO FIRE
6	BENEDIH OCP	0.0530	0.0453	-0.008	DECREASE
7	BLOCK-II OCP	0.0530	0.1353	0.082	INCREASE
8	MURAIH OCP	0.1478	0.0022	-0.146	DECREASE
9	SHATABDI OCP	0.0378	0.0361	-0.002	DECREASE
10	TETURIA	0.0000	0.0000	0.000	NO FIRE
11	S.GOVINDPUR	0.0000	0.0000	0.000	NO FIRE
12	KORIDIH BLOCK-IV OCP	0.0000	0.0000	0.000	NO FIRE
13	JOGIDIH	0.0000	0.0000	0.000	NO FIRE
14	DHARAMABAND	0.0000	0.0000	0.000	NO FIRE
15	MAHESHPUR	0.0000	0.0000	0.000	NO FIRE
16	PHULARITAND	0.0133	0.0205	0.007	INCREASE
17	MADHUBAND	0.0000	0.0000	0.000	NO FIRE
18	AKASH KINARI	0.0000	0.0000	0.000	NO FIRE
19	GOVINDPUR	0.0000	0.0000	0.000	NO FIRE
20	E. KATRAS	0.0133	0.0000	-0.013	DECREASE
21	KATRAS-CHOITUDIH	0.1021	0.1368	0.035	INCREASE
22	KESHALPUR	0.0000	0.0013	0.001	INCREASE
23	RAMKANALI	0.0000	0.0000	0.000	NO FIRE
24	NICHITPUR	0.0000	0.0000	0.000	NO FIRE
25	E. BASURIA	0.0000	0.0000	0.000	NO FIRE
26	KHAS KUSUNDA	0.0000	0.0000	0.000	NO FIRE
27	GONDUDIH	0.0000	0.0000	0.000	NO FIRE
28	W. GODHAR	0.0012	0.0000	-0.001	DECREASE
29	BASURIA	0.0000	0.0000	0.000	NO FIRE
30	TETULMARI	0.0223	0.0220	0.000	DECREASE
31	DHANSAR	0.0000	0.0000	0.000	NO FIRE
32	GODHAR	0.1073	0.0000	-0.107	DECREASE
33	INDUSTRY	0.0119	0.0513	0.039	INCREASE
34	KUSUNDA	0.4243	0.7398	0.315	INCREASE
35	SENDRA-BANSJORA	0.0796	0.0275	-0.052	DECREASE
36	BASTACOLLA	0.0663	0.0810	0.015	INCREASE
37	BERA	0.0000	0.0000	0.000	NO FIRE
38	KUYA	0.0000	0.0000	0.000	NO FIRE
39	GOLUCKDIH	0.0301	0.1122	0.082	INCREASE
40	KUJAMA	0.0398	0.2404	0.201	INCREASE

41	S. JHARIA-R. OCP	0.0244	0.1118	0.087	INCREASE
42	DOBARI	0.0000	0.0000	0.000	NO FIRE
43	GONHOODIH	0.0398	0.0322	-0.008	DECREASE
44	SIMLABAHAL	0.0000	0.0000	0.000	NO FIRE
45	HURRILADIH&STD	0.0000	0.0000	0.000	NO FIRE
46	ENA	0.0918	0.0432	-0.049	DECREASE
47	BURRAGARH	0.0000	0.0000	0.000	NO FIRE
48	N. TISRA	0.0098	0.1802	0.170	INCREASE
49	LODNA	0.0000	0.3527	0.353	INCREASE
50	S. TISRA	0.0000	0.1015	0.102	INCREASE
51	BARAREE	0.1037	0.1074	0.004	INCREASE
52	AMLABAD	0.0000	0.0000	0.000	NO FIRE
53	PATHERDIH	0.0000	0.0000	0.000	NO FIRE
54	SUDAMDIH	0.0000	0.0000	0.000	NO FIRE
55	SITANALA	0.0000	0.0000	0.000	NO FIRE
56	MURULIDIH 20/21 PIT	0.0000	0.0000	0.000	NO FIRE
57	MURULIDIH	0.0000	0.0000	0.000	NO FIRE
58	BHATDIH	0.0000	0.0000	0.000	NO FIRE
59	LOHAPATTY	0.0000	0.0000	0.000	NO FIRE
60	IISCO	0.0000	0.0000	0.000	NO FIRE
61	TASRA-IISCO	0.0000	0.0000	0.000	NO FIRE
62	KENDUADIH	0.0610	0.0000	-0.061	DECREASE
63	BULLIHARY	0.0000	0.0000	0.000	NO FIRE
64	GOPALICHUCK	0.0000	0.0000	0.000	NO FIRE
65	POOTKEE	0.0000	0.0000	0.000	NO FIRE
66	BHURUNGIA	0.0000	0.0000	0.000	NO FIRE
67	KHARKHAREE	0.0000	0.0000	0.000	NO FIRE
68	GASLITAND	0.1194	0.1215	0.002	INCREASE
69	KANKANEE	0.0530	0.0525	-0.001	DECREASE
70	MUDIDIH	0.1141	0.1104	-0.004	DECREASE
71	W. MUDIDIH	0.0171	0.0000	-0.017	DECREASE
72	LOYABAD	0.0133	0.0063	-0.007	DECREASE
73	BHAGABAND	0.0000	0.0000	0.000	NO FIRE
74	MOONIDIH PROJECT	0.0000	0.0000	0.000	NO FIRE
75	E.BHUGGATDIH	0.0022	0.0214	0.019	INCREASE
76	ALKUSHA	0.0326	0.0294	-0.003	DECREASE
77	KUSTORE	0.0524	0.0463	-0.006	DECREASE
78	ANGARAPATRA	0.1331	0.0149	-0.118	DECREASE
79	SALANPUR	0.0000	0.0000	0.000	NO FIRE
80	BHOWRAH. N	0.0133	0.0980	0.085	INCREASE
81	BHOWRAH. S	0.0000	0.0000	0.000	NO FIRE
82	BAGDIGI	0.0000	0.0209	0.021	INCREASE
83	JEALGORA	0.0000	0.0067	0.007	INCREASE
84	JEENAGORA	0.0000	0.0470	0.047	NO FIRE

85	JOYRAMPUR	0.0099	0.1042	0.094	INCREASE
86	CHANDAN OCP	0.0000	0.0000	0.000	NO FIRE
87	BANSDEOPUR	0.0000	0.0000	0.000	NO FIRE
	TOTAL AREA	2.18	3.28	1.10	INCREASE

Table 6: Colliery wise break-up of change in fire area from 2012 to 2017

Note:

- 1) "**NO FIRE**" implicates that the fire has not been identified satellite data (*either absent or below sensor resolution*)
- 2) "**INCREASE**" implies, increase in fire area OR emergence of fire areas not identified in 2012 study.
- 3) "**DECREASE**" implies, decrease in fire area OR fire areas of 2012, which are not identified in present study (*either absent or below sensor resolution*).
- 4) Estimations of fire extent (in terms of sq.km.) both 2012 and in present 2017 study are pixel based. They do not represent the actual ground area under fire. These estimations are made for comparative purpose only, to indicate the increase or decrease of areal disposition of fire. Hence, they should not be quoted as fire area on the ground.

Annexure –IV



Figure 15: Fume cracks in Lodna-Tisra Area. (point 39 in figure 13 and table 4)



Figure 16: Burnt area near OB dump in Lodna area (point 41 in figure 13 and table 4)



Figure 17: Coalfries in active seams in Kusunda (point 23 in figure 13 and table 4)



Figure 18: Sagged area due to subsidence, south of Block II OCP. (point 1 in figure 14 and table 5)



Figure 19: Fire in OB dumps in Kusunda area. (point 24 in figure 13 and table 4)



Figure 20: Fume cracks in the Bhulanbarari area.



GROUNDWATER LEVEL & QUALITY REPORT FOR CLUSTER OF MINES, BCCL

(Assessment year – 2019-20)

[CLUSTER – I, II, III, IV, V, VI, VII, VIII, IX, X, XI, XIII, XIV, XV & XVI of Mines, BCCL]

JHARIA COALFIELD AND RANIGANJ COALFIELD (PART)

**For
(BHARAT COKING COAL LIMITED)**

(A Subsidiary of Coal India Limited)

KOYLA BHAWAN (DHANBAD)

**Prepared by
Hydrogeology Department
Exploration Division
CMPDI (HQ), Ranchi**

MARCH – 2020



**GROUNDWATER LEVEL & QUALITY REPORT
FOR CLUSTER OF MINES, BCCL**

(Assessment year – 2019-20)

[CLUSTER – I, II, III, IV, V, VI, VII, VIII, IX, X, XI, XIII, XIV, XV & XVI of Mines, BCCL]

JHARIA COALFIELD AND RANIGANJ COALFIELD (PART)

**For
(BHARAT COKING COAL LIMITED)**

(A Subsidiary of Coal India Limited)

KOYLA BHAWAN (DHANBAD)

**Prepared by
Hydrogeology Department
Exploration Division
CMPDI (HQ), Ranchi**

MARCH – 2020

PERSONNEL ASSOCIATED

FIELD EXERTION

Debasis Bandyopadhyay Manager (Geology)

HYDROGEOLOGICAL DOCUMENTATION

Debasis Bandyopadhyay Manager (Geology)

OVERALL GUIDANCE

Dr. A.K. Panda General Manager (Exploration)

CONTENT

	<u>Page No.</u>
DETAILS OF THE REPORT	1
1.0 Introduction	2 - 3
1.1 Climate, Temperature & Rainfall	2
1.2 Geomorphology	2
1.3 Drainage	3
2.0 Groundwater system	3 - 5
2.1 Geology of the area	3
2.2 Hydrogeology of the study area	4
2.3 Aquifer Description	5
2.4 Aquifer parameters	5
3.0 Groundwater level monitoring	6 - 24
3.1 Historical groundwater level	7
3.2 Groundwater level scenario (mining/non-mining)	8
3.3 Quarterly groundwater level, Cluster of mines	09
A Monitoring of Ground Water Levels of Cluster-I	09
B. Monitoring of Ground Water Levels of Cluster-II	10
C. Monitoring of Ground Water Levels of Cluster-III	11
D. Monitoring of Ground Water Levels of Cluster-IV	12
E. Monitoring of Ground Water Levels of Cluster-V	13
F. Monitoring of Ground Water Levels of Cluster-VI	14
G. Monitoring of Ground Water Levels of Cluster-VII	15
H. Monitoring of Ground Water Levels of Cluster-VIII	16
I. Monitoring of Ground Water Levels of Cluster-IX	17
J. Monitoring of Ground Water Levels of Cluster-X	18
K. Monitoring of Ground Water Levels of Cluster-XI	19
L. Monitoring of Ground Water Levels of Cluster-XIII	20
M. Monitoring of Ground Water Levels of Cluster-XIV	21
N. Monitoring of Ground Water Levels of Cluster-XV	22
O. Monitoring of Ground Water Levels of Cluster-XVI	23
4.0 Ground water level scenario	24 – 25
5.0 Groundwater Quality	26
6.0 Stage of Groundwater Extraction	27-28
7.0 Conservation measures & future strategy	29 – 30
 Annexure-I: Location of Hydrograph Stations	 31
Annexure-IIA: Details of Hydrograph Stations	32 - 33
Annexure-IIB: Historical water level data	34 - 35
Annexure-III: CGWB well Hydrographs	36 - 37
Annexure-IV: Groundwater sample location details	38
Annexure-V (A-D): Groundwater sample quality analysis	39 – 43
Annexure-VI: Hydrographs of Cluster-I to XVI	44 – 58
 Abbreviations	 59

LIST OF TABLES

<u>Table No</u>	<u>Description</u>	<u>Page No.</u>
Table No – 1	Historical Groundwater Level	8
Table No – 2	Depth to water table	9
Table No – 3	Average hydraulic gradient	9
Table No – 4	GW level data Cluster wise	26
Table No – 5	Block wise Stage of GW Development	29
Table No – 6	Cluster wise GW Development scenario	30

LIST OF FIGURES

<u>Nos.</u>	<u>Description</u>
Figure No - 1	Groundwater monitoring station location map
Figure No - 2	Groundwater Quality sample location map
Figure No – 3	Proposed Piezometers location map
Figure No – 4	Water Table Contour Map: Pre-monsoon 2018

LIST OF ANNEXURES

<u>Nos.</u>	<u>Description</u>	<u>Annexure No</u>
1.	Location details of Monitoring stations	Annexure-I
2.	Details of Hydrograph Stations	Annexure-IIA
3.	Historical Water Level data	Annexure-IIB
4.	Hydrographs of CGWB observation stations	Annexure-III
5.	Groundwater sample location details	Annexure-IV
6.	Groundwater sample quality analysis	Annexure-V (A-D)
7.	Hydrographs of Cluster-I to XVI	Annexure-VI

DETAILS OF THE REPORT

SI No.	ITEMS	INFORMATIONS
1	Geographical Area	Jharia Coalfield (JCF): 453 sq. km. Raniganj Coalfield (RCF part): 19.64 sq. km. (Cluster-XVI area only)
2	Major Physiographic Units	Dissected Pediplain with surface Reduced Level (RL) varies from 160 m to 220 m above mean sea level (AMSL) in JCF and 100 m to 140 m AMSL in RCF.
3	Drainage System	Damodar River is the master drainage flowing along western boundary of the JCF. Jamunia River, Khudia River, Katri River, Jarian Nala, Ekra Jore, Kari Jore, Kashi Jore, Chatkari Jore and their tributaries are flowing through the JCF area. Damodar River, Barakar River is the master drainage of the part of RCF area (CV Area).
4	Annual Rainfall	Jharkhand State – 1264.0 mm Dhanbad District - 1271.60 mm (Source: Rainfall Statistics of India-2018, IMD, Ministry of Earth Sciences) Normal Rainfall – 1296.30 mm Dhansar Mine Rescue Station – 1315 mm (2018)
5	Geological Formations	Gondwana Formation (Talchir Formation, Barakar Formation, Barren Measure & Raniganj Formation)
6	Aquifer System	Top Unconfined/Phreatic Aquifer – average thickness 25 m Semi-confined to confined Aquifer – average thickness 50–200 m
7	Hydrogeological properties	Unconfined Aquifer (Damoda BJ Section & Block-III): Hydraulic Conductivity – upto 0.50 m/day Transmissivity – 10 - 42 m ² /day Semi-confined to confined Aquifer (Sitatala & Kumari Block): Hydraulic Conductivity – 0.0006-1.44 & 0.05-0.0027 m/day Transmissivity – 0.06 – 0.573 m ² /day
8	Groundwater Level Monitoring Network	Out of total 254 no of monitoring stations 63 nos located within core mining area and rest comes within Buffers zone. 60 Nos. of Groundwater monitoring well (Dug Wells) network is established by CMPDI to record groundwater level data in and around the Core Zone of JCF and 3 Nos. of Groundwater monitoring well (Dug Wells) in RCF (CV Area).
9	Groundwater Levels Below Ground Level (bgl)	JCF area: Pre-monsoon – 0.95 to 15.88 m (Avg. 5.46 m bgl) in '2019 Post-monsoon – 0.45 to 05.95 m (Avg. 2.34 m bgl) in '2019 RCF area (part): Pre-monsoon – 1.60 to 9.35 m (Avg. 5.29 m bgl) in '2019 Post-monsoon – 0.80 to 3.88 m (Avg. 2.10 m bgl) in '2019
10	Groundwater Quality	Potable (Annexure- IV)
11	Proposed Piezometers	New piezometers (23 nos.) have been proposed to monitor impact of coal mining on groundwater regime within the coalfield area (JCF & part of RCF) for maximum depth upto 290 m to monitor deeper aquifers.
12	Stage of Groundwater Development (CGWB)	Dhanbad District-76.30% (GWRE-2017)

1.0 INTRODUCTION

1.1 CLIMATE, TEMPERATURE & RAINFALL

The Jharia Coalfield (JCF) and part of Raniganj Coalfield (RCF) area in Dhanbad District belongs to sub-humid tropical climatic region. The maximum temperature during summer shoots upto 45° C and falls between 10° C to 5° C in winter. The maximum rainfall occurs during the period between June and September.

The annual rainfall in the Dhanbad District is 1240.70 mm (Rainfall Statistics of India-2017, IMD (Ministry of Earth Sciences), has been considered. The non-monsoon rainfall in the District is 259.50 mm (Winter-9.50 mm, Pre-monsoon-73.80 mm and Post-monsoon-176.20 mm) and the monsoon rainfall is 981.30 mm of total annual rainfall. Monsoon Rainfall is around 80% of total annual rainfall in 2017 in Dhanbad District. Rainfall is the primary source of groundwater recharge. The normal rainfall of Jharkhand is 1296.30 mm (2015) as documented in MOSPI, Govt. of India.

1.2 GEOMORPHOLOGY

Northern part of the JCF area is covered with hills and thin forest. In general, the altitude varies from 220 m AMSL in Barora area (Cluster-I) to 160 m above mean sea level (AMSL) in Sudamdih area (Cluster-X). Pediplains are developed over sedimentary rocks or Gondwana formation consisting of Sandstone, Shale, coal, etc. Dissected pediplains are developed over Gondwana formations found in Jharia, Baghmara, Katras areas etc. However, in RCF (part) areas the altitude varies from 100 m to 140 m AMSL (Cluster-XVI). The general slope of the topography is towards south, i.e. Damodar River.

1.3 DRAINAGE

The drainage pattern of the area is dendritic in nature. The drainage system of the area is the part of Damodar sub-basin. All the rivers that originate or flow through the coalfield area have an easterly or south easterly course and ultimately joins Damodar River, the master drainage. The drainage of the JCF is mainly controlled by Jamuniya River (5th order), Khudia nala (3rd order), Katri River (4th) and Chatkari nala (3rd order) flowing from north to south and joins Damodar River. Whereas, Barakar River and Khudia River are controlling the drainage pattern of RCF (part) and joins Damodar River in the south. Damodar River is the main drainage channel and flows from west to east along the southern boundary of JCF and RCF.

The drainage map of the JCF and part of RCF has been prepared on topographic map of scale 1:50,000 (**Figure No-1**). The watershed of all tributary rivers (Jamuniya River to Barakar River) falls within the north-western part of Damodar sub-basin which comes under Lower Ganga Basin.

Besides, a large number of ponds/tanks are distributed in and around JCF, out of which one prominent lake is located at Topchanchi in the north-west part. Two reservoirs, Maithon dam in Barakar River and Panchet dam in Damodar River near to Chanch Victoria Area of BCCL (part of RCF) are the main source of water supply to the nearby area. Jharia Water Board, Damodar Water Supply Scheme and Mineral Area Development Authority (MADA) are supplying water.

2.0 GROUNDWATER SYSTEM

2.1 GEOLOGY OF THE AREA

The Jharia Coalfield covers an area of 453 sq. km. located in Dhanbad District, Jharkhand. The non-coal bearing Talchir Formation is exposed in patches along the northern fringe of the Coalfield. The Barakar Formation which overlies the Talchir is covering the most part of the Jharia Coalfield and having an area of 218 sq. km. This is successively overlain by the non-coal bearing Barren Formation which is mainly exposed in the central part of the Coalfield. This, in turn, is overlain by the Raniganj formation (Coal Bearing horizon) in the south-western part of the Coalfield and covers an area of 54 sq. km.

Chanch-Victoria Area which is located in the western part of Raniganj Coalfield. The Raniganj coalfield represents the eastern most coal basin in the Damodar Valley Region and located in Burdwan District, West Bengal. The Coalfield is almost elliptical in shape and covers an area of about 1530 sq. km. out of which only 35 sq. km. comes under leasehold area of BCCL out of which 19.64 sq. km is the study area (Cluster-XVI only). The coal bearing formations of the area belongs to Barakar Formation of the Lower Gondwana.

2.2 HYDROGEOLOGY OF THE STUDY AREA

The permeable formations mainly composed of sandstone behave as aquifer units. The coal seam and shales developed in the area act as impermeable beds i.e. aquiclude. The aquifer materials of Gondwana Formation are constituted of fine to coarse grained sandstone having primary porosity of intergranular void space. The secondary porosity formed due to presence of faults, fracture, joints, etc. Sandstone of Gondwana formations in JCF and RCF are very hard, compact and cemented sandstone and forming less potential aquifer, particularly the deeper aquifer system. The secondary porosity along with primary porosity forms a conduit system making these formations good aquifers for movement and storage of ground water.

2.3 AQUIFER DISPOSITION

The aquifer system for shallow and deeper aquifer has been established through hydrogeological studies, exploration, surface and subsurface geophysical studies in the JCF and RCF (part) covering all geological formations. The aquifer can be divided into two zones – Un-confined/Phreatic (shallow) and Semi-confined to confined (deeper) aquifer.

PHREATIC/UN-CONFINED AQUIFER

The top aquifer occurred above the top most coal seam/shale bed is called un-confined or water table aquifer and it consists of relatively permeable formation such as weathered sandstone and loose soil. The thickness of the un-confined aquifer is varying from few meters to 50 m. This un-confined aquifer is more potential than deep seated semi-confined to confined aquifer.

SEMI-CONFINED TO CONFINED AQUIFER

The semi-confined to confined aquifer consisting of sandstone bed is sandwiched with coal seams/shale beds and multiple aquifer system developed due to presence of multiple numbers of coal seams/shale beds. With the presence of intercalated shale and carbonaceous shale beds and reduction in permeability with depth, the lower aquifers are poor in potential.

2.4 AQUIFER PARAMETERS

PHREATIC/UN-CONFINED AQUIFER – The wells are tested by CMPDI for determination of aquifer parameters in Damuda (BJ Section) and Block-III area of JCF. The hydraulic conductivity of the un-confined aquifer is 0.50 m/day as computed from pumping tests on the wells. The transmissivity of the unconfined aquifer ranges from 10.68 m²/day to 41.48 m²/day.

SEMI-CONFINED TO CONFINED AQUIFER – Below the un-confined aquifer, the sandstone partings in-between impervious layers of shale and coal seams is designated as semi-confined / confined aquifers. The sandstones in these aquifers are fine to coarse grained, hard and compact with very low porosity. Mostly groundwater occurs in the weak zones formed due to weathering, fracture, faults, which create the secondary porosity. The hydrogeological parameter has been determined by CMPDI in Sitanala Block by conducting aquifer performance test (APT). The hydraulic conductivity (K) of semi-confined aquifer in Barakar Formation ranges from 0.0006 m/day to 1.44 m/day. The hydrogeological parameter has also been determined at Kumari OCP Block in the central JCF by conducting aquifer performance test. The hydraulic conductivity (K) of semi-confined aquifer in Barakar Formation in this area ranges from 0.0027 m/day to 0.05 m/day.

Aquifer Type	Hydraulic Conductivity (m/day)	Transmissivity (m²/day)	Remarks
Unconfined	0.50	10.68 – 41.48	Site: Damuda (BJ Section) and Block-III area
Semi-confined	0.0006 – 1.44 (1) 0.0027 – 0.05 (2)	-	Site: (1): Sitanala Block (2): Kumari Block

3.0 GROUNDWATER LEVEL MONITORING

To collect the representative groundwater levels in the study area, CMPDI has established a monitoring network of total 254 monitoring stations out of which 64 located within core zone and rest comes within Buffer zone. 60 dug wells within JCF and 04 dug wells within RCF (part) area (Details of the Hydrograph stations & water level are given in **Annexure-I, IIA & IIB**) spread over the entire BCCL leasehold area, **Figure No-1**. Water level monitoring in 254 hydrograph stations has been done in pre-monsoon as well as in post monsoon whereas in 64 stations monitoring done in quarterly (March, May, August and November month of 2018) basis.

Depth to water level of the water table depict the inequalities in the position of water table with respect to ground surface and is useful in delineating recharge / discharge areas, planning of artificial recharge structure and shows the overall status of the groundwater level in the area. Historical groundwater level (GWL) of entire JCF and part of RCF with fluctuation, GWL of Non-mining / Mining areas and GWL of the Cluster of Mines of BCCL are shown in this report to assess the effect of Coal mining activity in the groundwater regime in and around the Coalfield area.

Mining is a dynamic phenomenon. The mining activity creates dis-equilibrium in environmental scenario of the area and disturbs the groundwater conditions/regime in particular. The impact on shallow water regime due to mining activity can be broadly viewed as under:

- Historical GWL with annual fluctuation over the years
- GWL scenario in Non-mining and Mining area (OC/UG mines)
- GWL scenario of Cluster of mines of BCCL

**Construction of piezometers within Jharia Coalfield and part of Raniganj Coalfield to monitor groundwater level of deeper aquifers is already in progress.*

3.1 HISTORICAL GROUNDWATER LEVEL

Historical GWL of JCF and part of RCF are given from 2005 to 2019 of CMPDI monitoring stations (total 63 stations within Coalfield area). Pre-monsoon and Post-monsoon GWL with Fluctuation has been mentioned below in the table.

Table No – 1: Historical Groundwater Level

Period		(Water level in metre below ground level)								
		Pre-Monsoon (April/May)			Post-Monsoon (Nov/Dec)			Fluctuation		
		From	To	Average	From	To	Average	From	To	Average
JCF	2005	0.07	19.08	6.29	0.84	12.13	3.20	0.12	12.45	3.21
	2007	0.40	19.27	5.66	0.35	8.21	2.87	0.02	16.15	2.96
	2008	0.45	18.35	5.42	0.35	14.20	3.62	0.03	9.22	2.45
	2010	0.85	14.47	5.24	0.10	15.88	4.48	0.02	5.55	1.54
	2012	1.27	18.68	5.58	0.15	7.80	2.72	0.08	13.45	2.96
	2013	0.70	19.20	5.65	0.45	8.35	2.77	0.29	15.88	3.17
	2014	0.70	16.28	4.92	0.75	14.98	3.27	0.25	10.15	2.17
	2015	1.38	17.20	6.00	0.45	14.58	3.92	0.28	7.62	2.15
	2016	0.78	16.73	5.64	0.30	12.43	3.19	0.23	6.35	2.88
	2017	0.67	16.28	5.61	0.15	6.97	2.41	0.10	12.10	3.25
	2018	1.20	14.58	5.55	0.40	7.17	2.83	0.20	9.45	2.68
	2019	0.95	15.88	5.46	0.45	5.95	2.34	0.20	13.40	3.05
RCF (part)	2008	5.02	10.50	7.59	2.85	4.90	3.71	1.82	6.60	3.87
	2010	2.20	8.85	4.74	2.78	9.58	4.63	0.68	1.10	0.89
	2011	3.57	8.02	4.98	2.50	6.21	3.75	0.55	1.90	1.23
	2012	3.10	7.34	4.59	1.55	7.00	3.66	0.05	2.78	0.94
	2013	1.70	9.87	6.54	2.90	8.85	4.71	1.02	5.54	2.84
	2014	3.27	6.48	4.57	2.13	3.03	2.63	0.54	3.45	1.94
	2015	3.38	9.52	5.33	2.68	8.20	5.11	1.06	1.32	1.81
	2016	3.61	10.65	6.24	0.90	6.50	3.18	1.63	4.40	3.06
	2017	1.93	5.80	3.25	1.63	3.78	2.47	1.63	3.78	0.78
	2018	2.34	8.70	4.35	1.75	5.70	2.75	0.41	2.55	1.59
	2019	1.60	9.35	5.29	0.80	3.88	2.10	0.80	5.47	3.20

3.2 GROUNDWATER LEVEL SCENARIO IN NON-MINING/MINING AREA

Depth to water level (DTW) range in different formations with respect of mining and non-mining areas is summarized in the Table No-2.

Table No – 2: Depth to water table

Formation	Area		DTW (bgl, m) [Year-2019]		Average GWL (m)	
			Pre-monsoon (Apr/May)	Post-monsoon (Nov/Dec)		
Sedimentary (Gondwana)	Non-mining		1.30-11.22	0.65-4.52	5.50	2.50
	Mining	OC	0.95-12.60	0.45-5.95	5.16	2.21
		UG	1.20-15.88	0.55-4.57	5.95	2.74
Metamorphics	Peripheral part of the Coalfield		0.45-15.10	0.35-9.20	7.15	3.95

The study revealed that water table is in shallow depth and there is no significant stress in the water table due to coal mining activity. Mining and Non-mining areas shows barely any difference in water table condition in the JCF and RCF (part) area. The average hydraulic gradient of the water table within mining and non-mining areas is given in Table No-3. There is no significant change in hydraulic gradient has been observed. Relatively steep gradient near active opencast mining areas w.r.t., Non-Mining, Underground mines and Metamorphics areas is observed.

Table No – 3: Average hydraulic gradient

Sl. No	Formation	Area		Average hydraulic gradient
1	Sedimentary (Gondwana)	Non-Mining		1.5×10^{-3} to 2.0×10^{-3}
2		Mining	OC	5.0×10^{-2} to 4.0×10^{-3}
3			UG	2.0×10^{-2} to 3.0×10^{-3}
4	Metamorphics	Peripheral part of the Coalfield		1.0×10^{-3} to 2.0×10^{-3}

3.3 QUARTERLY GROUNDWATER LEVEL, CLUATER OF MINES (BCCL)

3.3 A Monitoring of Ground Water Levels of Cluster-I

Cluster-I (Damuda Group of Mines) consisting of Damoda (BJ and Gutway section) UG, Damoda (Albion section) OCP, proposed Damoda (B.J.section) OCP and Closed Gutway OCP of Barora Area of BCCL. It is located in the extreme western part of JCF in Bokaro district of Jharkhand.

The present leasehold area of Cluster-I is 575 Ha. The Damoda block area is marked by more or less flat and gently undulating topography. The RL varies from 179 m to 208 m AMSL and the general slope of topography is towards east. Jamuniya River, Kari Jore, Podo Jore and its tributaries are controlling the drainage system of the area. The area comes under the watershed of Jamuniya River.

4 hydrograph stations (**B-15, B-21A, B51 and B-53**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

SI No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	B-15	Bera Basti	1.90	0.45	1.65	2.65
2	B-21A	Dugdha	9.45	1.90	-	-
3	B-51	Taranga	5.10	1.10	2.70	2.90
4	B-53	Karmatanr	3.22	0.97	1.42	2.12
Average WL (bgl)			4.92	1.11	1.92	2.56

Ground Water Level (in bgl) varies from 1.90 to 9.45 m during May'19, 0.45 to 1.90 m during August'19, 1.42 to 2.70 m during November'19 and 2.12 to 2.90 m during January'20 within the Core Zone of Cluster-I area.

3.3 B Monitoring of Ground Water Levels of Cluster-II

Cluster-II consists of seven mines namely; Block-II mixed mine (OCP & UGP), Jamunia OCP, Shatabdi OCP, Muraidih mixed mine (OCP & UGP) and Phularitand OCP is under administrative control of Block-II Area and Barora Area of BCCL. It is located in the extreme western part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-II is 2025.71 Ha. The Damoda block area is marked by more or less flat and gently undulating topography. The RL varies from 176 m to 235 m AMSL. Jamuniya River, Khudia River and its tributaries are controlling the drainage system of the area. The area comes under the watershed of Jamuniya River and Khudia River.

5 hydrograph stations (**B-1, B-59, B-60, B-61A and B-62A**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	B-1	Muraidih	3.18	1.33	1.73	1.98
2	B-59	Khodovaly	6.20	0.80	0.90	1.20
3	B-60	Bahiyardih	8.13	1.23	3.23	4.93
4	B-61A	Kesargora	3.32	1.39	0.52	1.12
5	B-62A	Sadiyardih	7.55	2.80	3.25	4.95
Average WL (bgl)			5.68	1.51	1.93	2.84

Ground Water Level (in bgl) varies from 3.18 to 8.13 m during May'19, 0.80 to 2.80 m during August'19, 0.52 to 3.25 m during November'19 and 1.12 to 4.95 m during January'20 within the Core Zone of Cluster-II area.

3.3 C Monitoring of Ground Water Levels of Cluster-III

Cluster-III consists of nine mines namely, Jogidih UG, Maheshpur UG, South Govindpur UG, Teturiya UG, Govindpur UG, New Akashkinaree mixed mine (OC & UG) and Kooridih/Block-IV mixed mine (OC & UG) under the administrative control of Govindpur Area of BCCL. This Cluster of mines is located in western part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-III is 1420.0 Ha. The area is plain with gentle undulation with RL varies from 160 m to 208.80 m AMSL. The general slope of the area is towards south. Khudia River, Baghdihi Jore, Katri River and its tributaries are controlling the drainage system of the area. The area comes under the watershed of Khudia River.

5 hydrograph stations (**A-12, A-25, A-29, B-14 and B-60**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	A-12	Jamua	2.10	0.29	0.45	0.75
2	A-25	Sinidih	6.08	1.43	1.93	2.48
3	A-29	Dharmaband	4.85	1.20	3.40	3.65
4	B-14	Mathadih	2.24	0.54	0.94	2.04
5	B-60	Sonardih	8.13	1.23	3.23	4.93
Average WL (bgl)			4.68	0.94	1.99	2.77

Ground Water Level (in bgl) varies from 2.10 to 8.13 m during May'19, 0.29 to 1.43 m during August'19, 0.45 to 3.40 m during November'19 and 0.75 to 4.93 m during January'20 within the Core Zone of Cluster-III area.

3.3 D Monitoring of Ground Water Levels of Cluster-IV

Cluster-IV consists of six mines namely, Salanpur UG, Katras-Choitudih UG, Amalgamated Keshalpur & West Mudidih OC, Amalgamated Keshalpur & West Mudidih UG, Amalgamated Angarpathra & Ramkanali UG and closed Gaslitand UG of Katras Area of BCCL. It is located in the north-central part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-IV is 1123.79 Ha. The area has a general undulating topography, with an overall gentle south-westerly slope. The RL varies from 182 m to 216 m AMSL. Katri River, Kumari Jore and its tributaries are controlling the drainage pattern of the area. The area comes under the watershed of Katri River.

4 hydrograph stations (**A-26, A28A, B-64 and B-65A**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	A-26	Malkhera	6.58	2.23	3.33	3.83
2	A28A	Lakarka	2.45	1.25	3.15	3.60
3	B-64	Keshalpur	0.95	0.30	0.45	1.20
4	B-65A	Jhinjipahari	11.05	1.85	0.95	2.95
Average WL (bgl)			5.26	1.41	1.97	2.90

Ground Water Level (in bgl) varies from 0.95 to 11.05 m during May'19, 0.30 to 2.23 m during August'19, 0.45 to 3.33 m during November'19 and 1.20 to 3.83 m during January'20 within the Core Zone of Cluster-IV area.

3.3 E Monitoring of Ground Water Levels of Cluster-V

Cluster-V consists of twelve mines namely; Tetulmari OC & UG mine, Mudidih OC & UG mine, Nichitpur OC, Sendra Bansjora OC & UG, Bansdeopur OCP (proposed) & UG, Kankanee OC & UG and closed Loyabad UG under the administrative control of Sijua Area of BCCL. This Cluster of mines is located in northern part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-V is 1957.08 Ha. The area has a general undulating topography, with an overall gentle south westerly slope. The RL varies from 210 m to 170 m AMSL. Jarian Nala, Nagri Jore, Ekra Jore and its tributaries are controlling the drainage pattern of the area. The area comes under the watershed of Jarian Nala and Ekra Jore.

4 hydrograph stations (**A-3, A-16, A-27 and D-23**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	A-3	Sijua	3.47	0.32	0.47	0.62
2	A-16	Ekra	5.45	1.65	1.95	4.55
3	A-27	Tetulmari	2.40	0.15	0.92	1.30
4	D-23	Jogta	4.70	1.65	1.40	1.50
Average WL (bgl)			4.01	0.94	1.19	1.99

Ground Water Level (in bgl) varies from 2.40 to 5.45 m during May'19, 0.15 to 1.65 m during August'19, 0.47 to 1.95 m during November'19 and 0.62 to 4.55 m during January'20 within the Core Zone of Cluster-V area.

3.3 F Monitoring of Ground Water Levels of Cluster-VI

Cluster–VI consists of four coal mines; East Bassuriya OC, Bassuriya UG, Gondudih Khas-Kusunda OC, Godhur Mixed Mines (OC and UG) are under the administrative control of Kusunda Area of BCCL. This Cluster of mines is located in central part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-VI is 876.55 Ha. The area has a general undulating topography with general slope towards south. The RL varies from 180 m to 240 m AMSL. Ekra Jore, Kari Jore and their tributaries are controlling the drainage pattern of the area. The area comes under the watershed of Ekra Jore and Kari Jore.

2 hydrograph stations (**D-25 and D-30**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	D-25	Godhur	9.90	4.35	5.38	5.50
2	D-30	Borkiboa	4.60	0.38	0.75	1.95
Average WL (bgl)			7.25	2.37	3.07	3.73

3.3 G Monitoring of Ground Water Levels of Cluster-VII

Cluster-VII consists of fourteen mines namely; Dhansar mixed mine, Kusunda OCP, Viswakarma OCP, Industry UG (closed), Alkusa UG, Ena OCP, S.Jharia/Rajapur OCP, Burragarh UG, Simlabahal UG, Hurriladih UG, Bhutgoria UG, Kustore UG (closed) and E.Bhuggatdih UG (closed) under the administrative control of Kusunda Area and Kustore Area of BCCL. This Cluster of mines is located in east central part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-VII is 2127.70 Ha. The area has a general undulating topography with general slope towards south. The RL varies from 172 m to 221 m above M.S.L. Kari Jore, Chatkari Jore and its tributaries are controlling the drainage pattern of the area. The area comes under the watershed of Kari Jore and Chatkari Jore.

7 hydrograph stations (**D-3, D-4, D-33, D-34, D-47, D-55 and D-80**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	D-3	Dhansar	1.75	1.05	1.30	1.45
2	D-4	Jharia	2.81	1.16	1.71	2.16
3	D-33	Kustore	2.35	0.25	1.65	2.35
4	D-34	Kusunda	4.75	2.10	2.40	2.55
5	D-47	Parastanr	4.55	1.90	4.35	4.20
6	D-55	Hariladih	8.42	2.97	5.47	8.62
7	D-80	Bastacolla	5.00	2.30	3.05	3.80
Average WL (bgl)			4.23	1.68	2.85	3.59

Ground Water Level (in bgl) varies from 1.75 to 8.42 m during May'19, 0.25 to 2.97 m during August'19, 1.30 to 5.47 m during November'19 and 1.45 to 8.62 m during January'20 within the Core Zone of Cluster-VII area.

3.3 H Monitoring of Ground Water Levels of Cluster-VIII

Cluster-VIII consists of ten mines namely; Bastacolla mixed mines (OC & UG), Bera mixed mines (OC & UG), Dobari UG, Kuya mixed (OC & UG), proposed Goluckdih (NC) OC, Ghanoodih OC and Kujama OC under the administrative control of Bastacolla Area of BCCL. This Cluster of mines is located in eastern part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-VIII is 1200.41 Ha. The area has a general undulating topography with general slope towards south and south-west. The ground elevation in the area ranges from 175 m to 221 m AMSL. Chatkari Jore, Tisra Jore and its tributaries controlling the drainage pattern of the area. The area comes under the watershed of Chatkari Jore.

4 hydrograph stations (**D-8, D-43, D-49 and D-51**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	D-8	Alokdiha	4.80	1.95	2.85	4.25
2	D-43	Alagdih	7.35	3.55	2.70	4.25
3	D-49	Galucdih	1.75	0.60	1.50	1.25
4	D-51	Chankuiya	9.95	8.05	5.75	7.75
Average WL (bgl)			5.96	3.54	3.20	4.38

Ground Water Level (in bgl) varies from 1.75 to 9.95 m during May'19, 0.60 to 8.05 m during August'19, 1.50 to 5.75 m during November'19 and 1.25 to 7.75 m during January'20 within the Core Zone of Cluster-VIII area.

3.3 I Monitoring of Ground Water Levels of Cluster-IX

Cluster-IX consists of eight mines namely; North Tisra/South Tisra Expansion OCP, Lodna UG, Bagdigi UG, Bararee UG and Joyrampur UG and Jealgora UG (closed) are under the administrative control of Lodna Area of BCCL. This Cluster of mines is located in eastern part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-IX is 1942.12 Ha. The topography of the area is undulating with gentle slope towards south. The RL varies from 221 m to 188.44 m AMSL. Chatkari Jore, Tisra Jore, Sulunga Jore and its tributaries controlling the drainage pattern of the area. The area comes under the watershed of Chatkari Jore.

6 hydrograph stations (**D-5, D-7, D-39, D-40A, D-41 and D-74**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	D-5	Jiyalgora	8.25	2.90	4.85	8.20
2	D-7	Golden Pahari	8.23	1.88	3.28	4.86
3	D-39	Tilaboni	12.60	4.00	5.95	12.45
4	D-40A	Khapa Dhawra	1.85	1.50	1.45	1.95
5	D-41	Joyrampur	2.30	0.70	1.25	1.40
6	D-74	Bhulan Bararee	5.80	2.35	3.57	4.95
Average WL (bgl)			6.51	2.22	3.39	5.64

Ground Water Level (in bgl) varies from 1.85 to 12.60 m during May'19, 0.70 to 4.00 m during August'19, 1.25 to 5.95 m during November'19 and 1.40 to 12.45 m during January'20 within the Core Zone of Cluster-IX area.

3.3 J Monitoring of Ground Water Levels of Cluster-X

Cluster-X consists of ten coal mines and one coal Washery namely; Bhowrah North mixed mines (UG & OC), Bhowrah South mixed mines (UG, 3 Pit OCP, Chandan OCP), Patherdih Mixed mines (UG, Chandan OCP), Sudamdih incline UG mine, Sudamdih Shaft UG mine, Amlabad UG (Closed) and Sudamdih Coal Washery under the administrative control of Eastern Jharia Area of BCCL. This cluster of mines is located in the eastern part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-X is 2057.47 Ha. The area has an undulating topography with gentle slope towards south and south east. The RL varies from 185 m to 150.0 m AMSL. Gaurkuthi Nala and few seasonal streams are controlling the drainage pattern of the area. The area comes under the watershed of Damodar River.

4 hydrograph stations (**A-19, D-35, D-36 and D-77**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	A-19	Bhowrah	4.85	0.95	3.43	4.95
2	D-35	Patherdih	8.00	3.15	3.80	5.90
3	D-36	Sudamdih	1.20	0.10	0.55	0.65
4	D-77	Amlabad	6.40	2.80	3.20	4.50
Average WL (bgl)			5.11	1.75	2.75	4.00

Ground Water Level (in bgl) varies from 1.20 to 8.00 m during May'19, 0.95 to 3.15 m during August'19, 0.55 to 3.80 m during November'19 and 0.65 to 4.95 m during January'20 within the Core Zone of Cluster-X area.

3.3 K Monitoring of Ground Water Levels of Cluster-XI

Cluster–XI consists of eight coal mines and one coal Washery namely; Gopalichak UG Project, Kachi Balihari 10/12 Pit UG, Pootkee Balihari Project UG, Bhagaband UG, Kendwadih UG (closed), Pootkee UG (closed), Kachi Balihari 5/6 Pit UG (closed) are under the administrative control of Pootkee Balihari Area and Moonidih UG & Moonidih Washery are under the administrative control of Western Jharia Area of BCCL. This Cluster of mines is located in central part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-XI is 3527.58 Ha. The area has an undulating topography with gentle slope towards south. The RL varies from 201 m to 166 m AMSL. Katri River, Jarian Nala, Ekra Jore and Kari Jore are controlling the drainage of the area. The area comes under the watershed of Katri River and Kari Jore.

4 hydrograph stations (**A-17, A-18, A-20 and A-32**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

SI No.	Well No.	Location	Water below (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	A-17	Kachi Balihari	2.94	0.34	2.24	2.42
2	A-18	Baghaband	2.29	1.09	0.69	1.09
3	A-20	Gorbudih	4.57	3.32	1.82	4.02
4	A-32	Baludih	2.75	0.62	0.95	1.65
Average GW (bgl)			3.14	1.34	1.43	2.30

Ground Water Level (in bgl) varies from 2.29 to 4.57 m during May'19, 0.34 to 3.32 m during August'19, 0.69 to 2.24 m during November'19 and 1.09 to 4.02 m during January'20 within the Core Zone of Cluster-XI area.

3.3 L Monitoring of Ground Water Levels of Cluster-XIII

Cluster-XIII consists of one operating mine i.e. Murulidih 20/21 pits UG mine and six abandoned mines (Bhurungiya Colliery, Muchraidih colliery, Hantoodih colliery, Padugora colliery, Murulidih colliery, Bhatdee colliery) of Western Jharia Area of BCCL. It is located in the south-western part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-XIII is 1898.62 Ha. The area has an undulating topography with gentle slope towards south-east. The maximum RL is 224 m AMSL in the north-western part of the area whereas the minimum RL is 179 m AMSL at southern part. The area comes under the watershed area of Jamunia River and Katri River.

6 hydrograph stations (**A-22, A-23, A-33, A-34, B-25 and B-48**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	A-22A	Nagdah Basti	2.60	1.75	2.00	2.85
2	A-23	Machhayara	11.97	5.37	3.77	6.57
3	A-33	Mahuda Washery	3.65	0.55	1.25	1.55
4	A-34	Mahuda Mosque	6.35	3.45	3.95	5.45
5	B-25	Mahuda More	4.80	1.38	1.40	3.50
6	B-48	Mahuda	7.05	2.85	4.35	5.45
Average GW (bgl)			6.07	2.56	2.79	4.23

Ground Water Level (in bgl) varies from 2.60 to 11.97 m during May'19, 0.55 to 5.37 m during August'19, 1.40 to 4.35 m during November'19 and 1.55 to 6.57 m during January'20 within the Core Zone of Cluster-XIII area.

3.3 M Monitoring of Ground Water Levels of Cluster-XIV

Cluster-XIV consists of two mines namely; Lohapatty UG and Lohapatty Opencast Patch (proposed). These are under the administrative control of Western Jharia of BCCL. This Cluster of mines is located in western part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-XIV is 1577.22 Ha. The topography of the area is undulating with slope towards south west. The maximum RL is 224 m in the north-eastern part whereas the minimum RL is 170 m above mean sea level on the south-western part of the area. Jamunia River and its tributaries are controlling the drainage of the area. The area comes under the watershed area of Jamunia River.

3 hydrograph stations (**B-23, B-24 and B-67**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	B-23	Lohapatti	2.84	1.12	1.34	2.24
2	B-24	Telmuchu	4.58	1.23	2.33	3.63
3	B-67	Simatanr	8.57	3.37	4.35	4.65
Average GW (bgl)			5.33	1.91	2.67	3.51

Ground Water Level (in bgl) varies from 2.84 to 8.57 m during May'19, 1.12 to 3.37 m during August'19, 1.34 to 4.35 m during November'19 and 2.24 to 4.65 m during January'20 within the Core Zone of Cluster-XIV area.

3.3 N Monitoring of Ground Water Levels of Cluster-XV

Cluster–XV consists of four coal mines; Kharkharee UG and Dharmaband UG are under the administrative control of Govindpur Area and Madhuband UG & Phularitand UG are under the administrative control of Barora Area of BCCL. This Cluster of mines is located in western part of Jharia Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-XV is 1696.55 Ha. The topography of the area is undulating with slope towards south west. The maximum RL is 235 m in the Kharkharee mine area whereas the minimum RL is 165 m AMSL on the eastern & western part of the Cluster. Jamunia River and Khudia River are controlling the drainage of the area. The area comes under the watershed area of both Jamunia River and Khudia River.

3 hydrograph stations (**A-24, B-32A and B-61A**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

SI No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	A-24	Pipratn	15.88	1.73	2.48	4.08
2	B-32A	Madhuband	5.55	1.25	1.70	2.35
3	B-61A	Kesargora	3.35	1.39	0.52	1.12
Average GW (bgl)			8.25	1.46	1.57	2.52

Ground Water Level (in bgl) varies from 3.35 to 15.88 m during May'19, 1.25 to 1.73 m during August'19, 0.52 to 2.48 m during November'19 and 1.12 to 4.08 m during January'20 within the Core Zone of Cluster-XV area.

3.3 O Monitoring of Ground Water Levels of Cluster-XVI

Cluster-XVI consists of five mines namely, Dahibari-Basantimata OC, Basantimata UG, New Laikidih OC, Laikidih Deep UG and Chunch UG under the administrative control of Chanch-Victoria Area of BCCL. This cluster of mines is located in the western part of Raniganj Coalfield in Dhanbad district of Jharkhand.

The present leasehold area of Cluster-XVI is 1964.21 Ha. The topography of the area is undulating with slope towards south west. The area is plain with gently undulating with elevation varying from 100 m to 140 m AMSL. The general slope of the area is towards southeast. Barakar River and Khudia River are controlling the drainage of the area. The area comes under the watershed area of Barakar River.

3 hydrograph stations (**DB-22, DB-23, DB-24**) are located in the core zone of the mine area. Water level monitoring in these monitoring stations has been done in the months of May, August, November'2019 and January'2020, the Ground water level data is enclosed in the table below:

Sl No.	Well No.	Location	Water level (bgl in meters)			
			May'19	Aug'19	Nov'19	Jan'20
1	DB-22	Dahibari, Niche Basti	4.93	1.38	1.63	1.73
2	DB-23	Dahibari OC	1.60	0.88	0.80	1.00
3	DB-24	Dahibari	9.35	3.20	3.88	4.80
Average GW Level			4.53	1.82	2.10	2.51

Ground Water Level (in bgl) varies from 1.60 to 9.35 m during May'19, 0.88 to 3.20 m during August'19, 0.80 to 3.88 m during November'19 and 1.00 to 4.80 m during January'20 within the Core Zone of Cluster-XVI area.

4.0 GROUNDWATER LEVEL SCENARIO

During the month of May'2019 the depth to water level (in bgl) within 15 nos Cluster of mines varies from 0.95 m to 15.88 m with an average of 5.46 m. During the month of August'2019 the depth to water level varies from 0.10 m to 8.05 m with an average of 1.77 m. During the month of November'2019 the depth to water level varies from 0.45 m to 5.95 m with an average of 2.34 m. During the month of January'2020 the depth to water level varies from 0.62 m to 12.45 m with an average of 3.30 m. The summarized water level data of all clusters are given in **Table No – 4**.

Depth to water level (in bgl) values described that water level goes down to maximum 15.88 m during pre-monsoon'2019 and maximum upto 9.35 m during post-monsoon'2019. Un-confined aquifer is affected around 20 m to 30 m maximum close to active opencast mining areas, showing steep gradient towards mine void. Other than that, there is no mining effect in the water level within JCF area and RCF area (part). Historical water level data and hydrograph of permanent observation stations from CGWB shown in **Annexure–III**.

Monitoring groundwater (quantity & quality) to assess the present condition and resource has been done regularly in the coalfield areas. Well hydrographs (**Annexure–III and VI**) are prepared and studied to identify potentially adverse trends so that appropriate action can be taken to protect groundwater resource. According to the hydrograph trend analysis of CGWB monitoring wells and CMPDI observation wells, there are decline trends in both Pre and Post-monsoon GW level trends (max. upto 0.50 cm/year in Cluster-V and Cluster-VI) but no significant decline trend (>1.0 m/year) of water level is noticed in any particular area for the last 10 years within the coalfield area. Regarding quality monitoring, the water sample location map (**Figure No–2**) with collection points details (dug wells) are given in **Annexure–IV** and Quality is given in **Annexure–V**.

Table No-4: Groundwater level data Cluster-wise

Sl. No.	Cluster of BCCL	No. of Monitoring Wells	Water level fluctuation Below ground level (May, Aug, Nov'19 & Jan'20)	Avg. Fluctuation (in meters)	Formation
1	I	4 nos.	0.45 to 9.45 m	3.00 m	Barakar
2	II	5 nos.	0.80 to 8.13 m	2.85 m	Barakar
3	III	5 nos.	0.29 to 6.08 m	2.70 m	Barakar
4	IV	4 nos.	0.30 to 11.05 m	3.30 m	Barakar
5	V	4 nos.	0.15 to 4.70 m	2.80 m	Barakar
6	VI	2 nos.	0.38 to 9.90 m	4.20 m	Barakar
7	VII	7 nos.	0.25 to 8.62 m	1.50 m	Barakar
8	VIII	4 nos.	0.60 to 9.95 m	2.75 m	Barakar
9	IX	6 nos.	0.70 to 12.60 m	3.10 m	Barakar
10	X	4 nos.	0.10 to 8.00 m	2.35 m	Barakar
11	XI	4 nos.	0.34 to 4.57 m	1.70 m	Barakar & Barren Measure
12	XIII	6 nos.	0.55 to 11.93 m	3.30 m	Raniganj
13	XIV	3 nos.	1.12 to 8.57 m	2.65 m	Raniganj
14	XV	3 nos.	0.52 to 15.88 m	6.70 m	Barakar & Barren Measure
15	XVI	3 nos.	0.80 to 9.35 m	3.20 m	Barakar

Maximum water level fluctuation observed in Cluster-XV (6.70 m) and minimum fluctuation observed in Cluster-VII (1.50 m). However, 3-5 m water level fluctuation observed in Cluster-I, IV, VI, IX, XIII, XV and XVI, 5-7 m water level fluctuation observed in Cluster-XV, 7-9 m water level fluctuation and beyond 9 m is not observed in any of the Cluster of mines of BCCL.

5.0 GROUNDWATER QUALITY

The ground water sample of the study area (15 nos. of Cluster of mines, BCCL) have been collected from dug wells and analysed. Fifteen ground water samples (GW-1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 13, 14, 15 & 16) were analysed during the month of May'2019 at CMPDI, RI-II, Dhanbad. The water sampling details are given in **Annexure-IV** and Water sample locations are shown in **Figure No-2**. The water quality data are enclosed in **Annexure-V**.

The study of the variations in water quality parameters are described below:

The pH of the groundwater samples varies between 7.64 (GW-6) to 8.14 (GW-7) in May 2019, the pH is within the ISI limit of drinking water standard.

The mineral constituents dissolved in water constitute the dissolved solids. The total dissolve solids vary from 366 (GW-5) to 796 mg/l (GW-6) in May 2019, the TDS values are above the IS 10500 standards of drinking water.

During the month of May'19 the alkalinity of the water samples varies from 66 (GW-11) to 124 mg/l (GW-7) and are within the stipulated standard of (200 mg/l) drinking water. The concentrations of calcium in the water samples vary from 28 (GW-16) to 84 mg/l (GW-6) and are **slightly above** the permissible limit (75 mg/l) of drinking water standards. The total hardness ranges between 170 (GW-16) to 420 mg/l (GW-3) and the value of total hardness in water samples are **above** the permissible limit (200 mg/l). The sulphate ranges between 68 (GW-14) to 136 mg/l (GW-3) and the value of sulphate in water sample are within the permissible limit (200 mg/l). The Iron, Copper, Manganese, Lead, Zinc and Chromium concentration in the water samples are found to be below the upper ISI limits for drinking water.

6.0 STAGE OF GROUNDWATER EXTRACTION

The groundwater is mainly utilized for domestic needs and for irrigation purposes. The groundwater abstraction is mainly through dug wells and bore wells. The stage of groundwater development in Dhanbad District is 76.30% (as per 2017 GWRE). The highest stage of development is in Jharia Block (127.0%) & Dhanbad Block (107.50%) and lowest stage of development is in Baliapur Block (78.24%) as per GWRE-2013. The Gondwana sandstones in general, are known to constitute good aquifers at many places. However, the yield potential of the area adjoining to active mines in the coal belt is poor. The active mines often act as groundwater “sinks”. In contrast, the water logged abandoned mines and pits act as potential sources of groundwater. As per the assessment done by Central Ground Water Board (CGWB), Patna in 2017, the Block wise data of Dhanbad District is given below:

Table No–5: Block-wise Stage of Groundwater development

SI No.	Administrative Unit		Stage of GW Development	Category (GWRE-2013)	Category (GWRE-2017)
	District	Block			
1	Bokaro	Bermo	156.30%	Over- exploited	Over- exploited
2	Dhanbad	Baghmara	91.74%	Critical	Critical
3	Dhanbad	Baliapur	78.24%	Semi- Critical	Semi- Critical
4	Dhanbad	Dhanbad	107.50%	Over- exploited	Over- exploited
5	Dhanbad	Jharia	127.0%	Over- exploited	Over- exploited
6	Dhanbad	Topchachi	98.45%	Critical	Critical

- Dynamic Groundwater Resource Assessment, CGWB as per 2013 & 2017.

Table No-6: Cluster-wise Groundwater development scenario

Cluster/ Area	Adminis- trative Blocks/Stage Of GW Develo- pment (SOD)	Total Water demand (Lakh cum/year)				Avg. GW level (bgl in m) 2019		GW level declining trend 2005-2019		Quantity Storage / future use (Lakh Cum/ Year)
		Mine Discharge (GW + Rainwater)	Surface Water Source	Total Use (Domestic + Industrial)	Excess Or other use	Pre- monsoon	Post- monsoon	Pre- monsoon	Post- monsoon	
Cluster-I	Bermo (SOD: Over- exploited)	9.56	NIL	7.42	2.14	4.92	1.92	YES	YES	NIL
Cluster-II	Baghmara (SOD: Critical)	170.17	Jamunia river	22.55	23.83	5.68	1.93	NO	NO	123.75
Cluster-III		58.18	NIL	2.58	12.65	4.68	1.99	NO	NO	42.95
Cluster-IV		68.84	MADA (Damodar river)	18.47	12.31	5.26	1.97	NO	NO	38.06
Cluster-V		127.29	MADA	77.92	31.02	4.01	1.19	YES	YES	18.35
Cluster-VI	Dhanbad (SOD: Over- exploited)	3.86	MADA (Damodar river)	3.69	0.0	7.25	3.07	YES	YES	NIL (loss due to FF)
Cluster-VII		93.33	MADA	27.70	6.87	4.23	2.85	NO	NO	58.76
Cluster-VIII	Jharia (SOD: Over- exploited)	29.27	MADA	24.04	1.18	5.96	3.20	NO	NO	4.05
Cluster-IX		310.34	MADA	160.28	45.05	6.51	3.39	NO	NO	105.01
Cluster-X		59.38	Damodar river	11.47	0.0	5.11	2.75	YES	NO	47.91
Cluster-XI	Dhanbad (SOD: Over- exploited)	249.67	MADA & DVC	19.86	43.92	3.14	1.43	NO	NO	185.89
Cluster-XIII	Baghmara (SOD: Critical)	64.61	Damodar river	10.09	9.86	6.07	2.79	NO	NO	44.66
Cluster-XIV		NA	NA	NA	NA	5.33	2.67	NO	NO	NA
Cluster-XV		5.11	Jamunia river	0.0	5.11	8.25	1.57	NO	NO	0.0
Cluster-XVI	Nirsa (SOD:Safe)	29.78	DVC (Barakar river)	14.60	6.57	5.29	2.10	NO	NO	8.61

7.0 CONSERVATION MEASURES & FUTURE STRATEGY

- BCCL has installed 25 Pressure Filter Plant of total capacity of 4.16 MGD to meet drinking water requirement nearby the area. At present 63 Water Treatment Plants are operational having capacity of 16.16 MGD within Jharia Coalfield area. Further installation of 28 more Pressure Filter Plants with the capacity of 5.84 MGD are in progress.
- BCCL participated in development of low cost technology for drinking water in a CSIR project along with CIMFR, Dhanbad and a pilot plant of 4000 Liters/hour is functional at PB Project site of BCCL. Similar plant has been proposed at other sites of BCCL.
- A scheme entitled 'Scheme for multi-purpose utilization of surplus mine water of Barora Area, Block II and Govindpur Area of BCCL' was prepared with a view to harness the excess water discharge to take care of the persistence problem of water scarcity in the nearby villages. In the scheme, two water reservoirs of capacity 27 MG and 17 MG have been proposed in the non-coal bearing area for storage of 3250 GPM and 2000 GPM surplus mine water which will be fed through pipe line by mine discharge at mines of Barora, Block-II and Govindpur Area.
- Roof-top rainwater harvesting (RWH) will be taken up in the project area using the administrative buildings. 138 no. of quarters having roof-top area of about 14950 sq. m. is already prepared to harvest rainwater and around 13150 cum/annum of water is going to be recharged the nearby groundwater system through RWH structures. Proposal already made to facilitate this kind of RWH structure at suitable locations i.e. Lodna Area, Kusunda Area (Jawahar Nagar, Matkuria, Coal Board Colony), Sijua Area (Nichitpur and Tetulmari Colony) within Jharia Coalfield to augment groundwater recharge.
- After cessation of mining, with plenty rainfall and abundant ground water recharge, the water levels will recoup and attain normalcy. Thus, the impact of mining on groundwater system may be considered as a temporary

phenomenon. The abandoned mine workings (UG) behave as water pool and improves the resources availability in the coalfield area.

- Utilization of treated mine water discharge by both industry and local people in the mine influence area. The excess mine water can be used to recharge groundwater system through connecting pipeline to abandoned dug wells. Utilization of mine water for irrigation use will also enhance the ground water recharge potential through artificial recharge in the area.
- Increase vegetative cover by plantation in the mine area under land amelioration measures. This will contain the surface run-off and increase the groundwater recharge.
- Creation of awareness among workers and local peoples about Rain water harvesting and artificial recharge will be given priority. This aspect is usually covered during the Environmental Week celebrated every year (5 to 12 June).
- Monitoring of water quality of mine water discharge, local River/nala and domestic water source (dug well/hand pump wells) will be continued under routine monitoring (February, May, August & November).

Annexure – I

Location of Hydrograph Stations (Dug Wells)

Well No	Latitude	Longitude	Well No	Latitude	Longitude
A-3	23°47'53.35" N	86°19'55.14" E	B-63	Abandoned due to OCP	
A-12	23°48'20.31" N	86°16'51.64" E	B-64	23°48'43.14" N	86°18'44.25" E
A-16	23°46'57.00" N	86°21'38.57" E	B-65A	23°48'53.65" N	86°18'11.82" E
A-17	23°45'09.44" N	86°22'16.35" E	B-67	23°43'30.70" N	86°14'01.45" E
A-18	23°44'37.65" N	86°22'58.90" E	D-3	23°46'46.31" N	86°24'49.30" E
A-19	23°41'12.86" N	86°23'55.27" E	D-4	23°44'29.37" N	86°24'42.88" E
A-20	23°44'56.64" N	86°19'55.35" E	D-5	23°42'20.05" N	86°24'86.06" E
A-22	23°43'06.65" N	86°14'48.53" E	D-7	23°43'12.08" N	86°27'11.89" E
A-23	23°45'06.38" N	86°15'12.69" E	D-8	23°44'06.13" N	86°27'20.72" E
A-24	23°45'20.44" N	86°13'45.12" E	D-23	23°47'20.89" N	86°20'09.96" E
A-25	23°47'06.20" N	86°15'27.79" E	D-25	23°47'03.28" N	86°23'29.56" E
A-26	23°46'49.24" N	86°18'12.12" E	D-30	23°48'36.10" N	86°21'50.07" E
A-27	23°48'42.55" N	86°20'21.80" E	D-33	23°45'34.62" N	86°23'18.50" E
A-28A	23°47'34.74" N	86°18'04.18" E	D-34	23°45'36.50" N	86°23'02.45" E
A-29	23°47'08.02" N	86°16'02.72" E	D-35	23°40'46.54" N	86°25'46.33" E
A-32	23°44'15.56" N	86°20'43.80" E	D-36	23°40'19.26" N	86°25'18.98" E
A-33	23°44'32.58" N	86°16'58.28" E	D-39	23°43'28.50" N	86°26'0.10" E
A-34	23°42'58.63" N	86°15'19.31" E	D-40A	23°43'20.18" N	86°25'45.70" E
B-1	23°48'48.06" N	86°14'16.87" E	D-41	23°42'40.00" N	86°26'17.20" E
B-14	23°48'00.81" N	86°16'25.88" E	D-43*	NA	NA
B-15	23°46'06.92" N	86°08'59.30" E	D-47	23°45'20.59" N	86°24'34.86" E
B-21A	23°45'10.50" N	86°09'36.38" E	D-49	23°44'08.96" N	86°26'32.71" E
B-23	23°44'13.05" N	86°11'46.56" E	D-51	23°44'20.86" N	86°27'11.37" E
B-24	23°44'26.80" N	86°13'09.38" E	D-55	23°43'58.37" N	86°24'07.45" E
B-25	23°44'44.98" N	86°13'57.80" E	D-74	23°41'33.66" N	86°25'06.10" E
B-32A	23°45'49.18" N	86°13'03.64" E	D-77	23°41'00.74" N	86°22'25.55" E
B-48	23°43'35.09" N	86°16'38.30" E	D-80	23°46'09.46" N	86°24'33.08" E
B-51	23°47'40.20" N	86°09'11.90" E	DB-22	23°43'38.81" N	86°45'09.00" E
B-53	23°45'55.25" N	86°09'35.44" E	DB-23	23°43'44.24" N	86°45'06.39" E
B-53A	DO	DO	DB-24	23°43'53.00" N	86°45'03.88" E
B-59	23°47'59.87" N	86°13'37.97" E	DB-25	23°44'10.75" N	86°44'35.84" E
B-60	23°48'7.87" N	86°15'37.12" E			
B-61A	23°45'59.85" N	86°11'40.80" E			
B-62A	23°45'44.15" N	86°11'27.80" E			

Annexure – IIA

Details of Hydrograph Stations (Dug Wells)

Well No	Location	M.P. (agl) in m	Well Dia in m	Well Depth (m bmp)	R.L. (G.L) (m)	Formation	Owner	Utility
A-3	Sijua	0.53	3.00	5.20	203	Barakar	Govt.	Domestic
A-12	Jamua	0.80	1.90	3.30	202	Barakar	Govt.	Domestic
A-16	Ekra, Kalali More	0.45	3.10	6.50	205	Barakar	Govt.	Domestic
A-17	Kachi Balihari	0.56	1.60	5.30	182	Barakar	Govt.	Domestic
A-18	Bhagabandh	0.61	1.45	3.37	182	Barakar	Govt.	Domestic
A-19	Bhaura	0.54	3.15	11.65	162	Barakar	Govt.	Domestic
A-20	Gorbhudi	0.43	3.30	8.30	181	BM	Govt.	Domestic
A-22	Nagdah, Niche tola	0.00	1.40	9.50	171	Raniganj	Govt	Irrigation
A-23	Machhyara	0.43	1.85	12.40	203	Raniganj	Govt	Domestic
A-24	Pipra Tanr	0.22	1.80	19.55	208	Raniganj	Govt	Domestic
A-25	Sinidih	0.22	2.00	11.30	203	Barakar	Govt	Domestic
A-26	Pasitanr (Malkera)	0.32	1.80	9.65	198	Barakar	Govt	Domestic
A-27	Chandor	0.60	2.50	5.50	221	Barakar	Govt	Domestic
A-28A	Lakarka 6 no.	0.65	1.30	5.25	199	Barakar	BCCL	Domestic
A-29	Aambagan (Gobindpur)	0.10	2.60	9.15	186	Barakar	Govt	Domestic
A-32	Baludih	0.55	2.30	6.85	182	BM	Govt	Domestic
A-33	Mahuda	0.75	2.00	10.80	195	BM	BCCL	Domestic
A-34	Bhatdih	0.55	3.50	24.50	162	Raniganj	BCCL	Domestic
B-1	Muraidih	0.47	1.80	5.35	212	Talchir	Govt	Domestic
B-14	Mathadih	0.76	2.15	3.75	201	Barakar	Govt	Domestic
B-15	Bera Basti	0.55	1.60	2.50	221	Talchir	Dhanu Roy	Domestic
B-21A	Dugdha	0.55	2.10	10.35	220	Metamorphics	Govt	Domestic
B-23	Lohapati	0.26	3.60	10.85	204	Raniganj	Govt	Domestic
B-24	Telmuchu	0.67	4.35	10.83	207	Raniganj	Govt	Domestic
B-25	Mahuda More	0.10	2.45	8.45	205	Raniganj	Govt	Domestic
B-32A	Madhuband	0.80	4.30	8.60	205	Barakar	BCCL	Domestic
B-48	Mahuda	0.65	2.10	11.50	181	Raniganj	Mosque	Domestic
B-51	Taranga	0.00	2.50	5.75	215	Metamorphics	Bisun	Irrigation
B-53	Karmatanr	0.58	2.70	13.25	195	Barakar	Govt	Domestic
B-53A	Karmatanr-Damoda OCP							
B-59	Khodovaly	0.60	2.40	9.30	202	Barakar	BCCL	Domestic
B-60	Bahiyadih	0.77	3.00	15.60	196	Barakar	BCCL	Domestic
B-61A	Kesargora	0.48	2.00	11.20	201	Barakar	BCCL	Domestic
B-62A	Sadariyadih	0.15	3.10	9.50	188	Barakar	Govt	Domestic

Annexure – IIA

Details of Hydrograph Stations (Dug Wells)

Well No	Location	M.P. (agl) in m	Well Dia in m	Well Depth (m bmp)	R.L. (G.L) (m)	Formation	Owner	Utility
B-63	West Mudidih	0.60	1.70	3.35	196	Barakar	BCCL	Domestic
B-64	Keshalpur	0.65	1.10	3.40	195	Barakar	BCCL	Domestic
B-65A	Jhinjipahari	0.95	2.20	12.40	196	Barakar	Shiv Temple	Domestic
B-67	Simatanr	0.55	2.20	11.80	198	Raniganj	Govt	Domestic
D-3	Dhansar	0.60	1.70	8.70	217	Barakar	Govt	Domestic
D-4	Jharia	0.59	1.90	5.73	218	Barakar	Govt	Domestic
D-5	Jiyalgora	0.70	2.80	10.55	183	Barakar	Govt	Domestic
D-7	Golden Pahari	0.67	2.85	10.05	201	Barakar	BCCL	Domestic
D-8	Alokdiha	0.35	1.75	7.57	201	Metamorphics	BCCL	Domestic
D-23	Jogta (Sindra)	0.40	3.10	7.25	205	Barakar	BCCL	Domestic
D-25	Godhar More	0.60	2.75	5.60	219	Barakar	Govt	Domestic
D-30	Borkiboa	0.70	2.00	5.60	221	Talchir	H.Kumbhakar	Domestic
D-33	Kustore-4	0.55	1.85	3.45	196	Barakar	BCCL	Domestic
D-34	Kusunda-7	0.60	1.50	3.45	201	Barakar	BCCL	Domestic
D-35	Patherdih	0.40	2.00	11.20	160	Barakar	BCCL	Domestic
D-36	Sudamdih	0.90	2.00	6.20	141	Barakar	BCCL	Domestic
D-39	Tilabani	0.85	2.00	5.90	178	Barakar	BCCL	Domestic
D-40A	Khapra Dhaora	0.55	1.95	3.70	180	Barakar	Panchayat	Domestic
D-41	Joyrampur	0.50	1.80	4.00	180	Barakar	BCCL	Domestic
D-43	Alagdih	0.45	2.20	8.90	200	Metamorphics	Govt	Domestic
D-47	Parastanr	0.45	3.20	23.80	206	Barakar	BCCL	Domestic
D-49	Goluckdih	0.55	1.80	6.15	192	Barakar	BCCL	Domestic
D-51	Chankuiya	0.55	3.70	11.90	197	Barakar	BCCL	Domestic
D-55	Hariladih	0.48	2.80	11.80	184	Barakar	Govt	Domestic
D-74	Bhulan Barari	0.10	1.60	12.80	173	Barakar	Govt	Domestic
D-77	Rohoniatanr	0.40	3.15	6.70	156	Barakar	Govt	Domestic
D-80	Bastacolla	0.70	2.50	24.95	219	Barakar	Govt	Domestic
DB-22	Nichebasti	0.67	2.40	10.65	121	Barakar	Govt	Domestic
DB-23	Dahibari OC	0.70	2.30	8.00	-	Barakar	BCCL	Domestic
DB-24	Dahibari	0.60	3.60	13.70	125	Barakar	BCCL	Domestic
DB-25	Palasya	0.37	1.55	5.25	127	Barakar	Govt	Domestic

MP: Measuring Point**R.L.: Reduced Level****W.L.: Water Level m: Meter****Abn.: Abandoned****b.g.l.: Below Ground Level****a.g.l.: Above Ground Level****G.L.: Ground Level****bmp: Below Measuring Point****BM: Barren Measure**

Annexure – IIB

Historical Water Level data of Hydrograph Stations

Well No	Water level below ground level (bgl) in meters																
	May, 11	May, 12	Nov 12	May, 13	Nov 13	May, 14	Nov, 14	May 15	Nov 15	May, 16	Nov, 16	May, 17	Nov 17	May, 18	Nov 18	May 19	Nov 19
A-3	4.77	4.25	1.87	4.47	4.45	4.67	2.37	3.70	3.42	4.87	0.47	0.67	0.77	1.27	0.47	3.47	0.47
A-12	2.80	2.80	1.30	3.00	1.17	2.45	1.4	3.00	2.68	2.50	0.70	2.55	0.85	2.80	1.0	2.10	0.45
A-16	5.80	3.53	1.60	3.80	3.35	5.5	2.9	5.55	4.17	5.85	3.15	3.65	2.20	4.30	3.65	5.45	1.95
A-17	2.24	2.52	2.34	2.32	1.54	2.19	1.91	3.79	2.64	2.44	2.69	2.44	2.24	3.34	2.84	2.94	2.24
A-18	2.49	2.59	0.90	2.87	0.91	1.76	1.19	2.84	1.29	1.14	0.89	1.29	0.99	1.24	0.99	2.29	0.69
A-19		9.61	2.46	7.46	4.46	3.00	2.75	3.05	2.75	7.81	4.11	6.37	2.45	5.55	2.45	4.85	3.43
A-20	7.87	7.17	1.57	6.47	0.67	3.97	2.55	4.59	2.93	7.49	3.50	4.27	1.77	4.57	2.57	4.57	1.82
A22A		1.90	1.05	1.79	1.00	1.50	2.0	3.20	1.96	3.25	1.75	4.27	1.77	3.35	1.30	2.60	2.00
A-23	11.92	9.87	4.75	10.57	5.82	8.76	6.82	11.3	9.37	11.87	8.13	6.40	1.50	11.15	7.17	11.97	3.77
A-24	18.28	18.68	5.23	16.01	3.25	16.28	14.98	17.2	14.5	16.62	12.43	11.87	6.97	14.58	6.88	15.88	2.48
A-25	6.83	10.23	4.43	10.23	2.98	7.03	5.28	7.78	5.85	7.43	4.58	6.38	2.88	6.63	3.13	6.08	1.93
A-26	9.18	8.76	4.28	7.56	4.28	7.71	4.58	7.73	3.18	8.93	4.48	5.28	2.53	6.23	3.88	6.58	3.33
A-27	3.00	2.13	1.10	1.62	1.25	1.63	1.55	4.40	3.95	4.85	1.80	2.90	1.25	2.90	1.0	2.40	0.92
A28A	3.90	2.90	2.45	3.35	2.45	3.29	1.91	4.35	3.60	3.35	1.47	4.30	1.55	4.15	2.51	2.45	3.15
A-29	5.50	9.30	1.42	6.95	1.67	3.3	2.35	4.55	4.60	5.92	6.96	4.40	1.30	6.45	2.10	4.85	3.40
A-32	2.30	2.19	1.10	2.45	1.95	3.15	2.45	4.41	2.13	4.75	2.10	3.15	1.55	2.80	0.70	2.75	0.95
A-33	3.07	5.25	1.25	4.13	1.80	4.08	1.57	4.91	1.97	5.75	2.60	6.45	1.55	4.07	2.35	3.65	1.25
A-34	2.90	6.95	2.90	6.21	2.50	4.45	4.45	8.40	4.81	4.75	4.45	12.45	4.45	5.90	3.70	6.35	3.95
B-1	1.78	2.08	1.73	1.53	1.83	2.43	1.81	3.28	2.75	3.58	1.93	2.33	0.85	2.88	2.08	3.18	1.73
B-14	2.49	1.34	1.42	1.74	1.45	3.24	4.44	2.94	2.29	2.44	0.47	2.94	1.84	3.64	2.84	2.24	0.94
B-15	1.37	1.27	0.45	1.20	0.55	0.95	1.45	1.50	0.45	1.85	0.55	4.85	0.15	1.85	0.85	1.90	1.65
B21A	7.60	9.00	5.05	8.01	4.95	9.54	3.7	7.37	4.65	5.55	4.50	8.85	5.65	9.65	2.65	9.45	-
B-23	9.14	3.71	1.74	5.27	1.39	6.57	2.74	7.86	4.29	6.81	2.41	7.74	2.14	6.64	2.14	2.84	1.34
B-24	10.33	-	3.09	8.88	2.83	9.40	2.21	10.0	5.78	10.63	4.28	10.03	4.03	9.28	4.33	4.58	2.33
B-25	8.35	8.35	2.60	7.08	2.15	5.82	5.15	6.88	-	7.05	1.70	6.70	1.40	5.90	3.70	4.80	1.40
B32A	7.80	7.75	3.22	6.25	2.68	8.33	2.05	7.55	3.32	6.95	3.07	6.95	2.80	6.75	3.90	5.55	1.70
B-48	5.75	5.43	3.85	4.69	3.20	6.38	4.35	7.90	5.42	9.35	4.60	7.70	4.15	7.33	3.97	7.05	4.35
B-51	3.95	3.60	2.05	3.35	2.49	2.09	1.98	4.65	3.40	4.90	3.18	4.98	2.55	5.02	2.42	5.10	2.70
B-53	1.67	6.97	1.42	4.15	1.12	3.39	-	5.58	2.82	4.70	1.45	4.02	1.92	3.92	1.42	3.22	1.42
B-59	8.25	6.90	0.60	7.56	0.30	2.65	1.0	4.12	1.60	4.40	0.50	5.40	0.60	5.47	1.10	6.20	0.90
B-60	11.44	10.18	5.13	11.29	5.23	9.82	4.59	9.21	5.28	10.33	5.03	13.23	3.18	13.68	4.23	8.13	3.23
B61A	10.72	5.42	2.40	8.17	2.02	6.93	3.57	6.15	4.52	6.58	3.87	2.57	0.82	2.57	2.02	3.32	0.52
B62A	8.85	7.85	4.90	7.73	4.63	8.83	5.85	9.10	5.21	9.30	4.95	8.15	4.35	8.27	4.78	7.55	3.25



Annexure – IIB

Historical Water Level data of Hydrograph Stations

Well No	Water level below ground level (bgl) in meters																
	May, 11	May, 12	Nov, 12	May, 13	Nov, 13	May, 14	Nov, 14	May, 15	Nov, 15	May, 16	Nov, 16	May, 17	Nov, 17	May, 18	Nov, 18	May 19	Nov 19
B-64	0.85	1.05	1.00	1.35	0.85	0.7	1.15	1.38	0.95	2.35	0.55	1.25	0.85	2.15	1.85	0.95	0.45
B65A	9.65	11.45	1.73	10.11	1.82	10.45	2.4	7.82	5.87	7.15	2.68	9.05	1.25	10.03	2.40	11.05	0.95
B-67	11.25	8.55	6.50	9.73	5.31	9.80	3.72	9.23	5.53	9.53	4.30	10.00	2.15	9.55	4.0	8.57	4.35
D-3	2.55	2.93	1.80	3.45	1.68	2.54	2.11	4.25	2.25	2.35	1.90	2.15	2.30	3.43	2.45	1.75	1.30
D-4	1.51	1.94	0.91	2.41	0.98	1.23	0.91	2.41	1.27	1.21	1.36	1.21	1.46	1.91	1.56	2.81	1.71
D-5	9.05	9.50	6.45	9.32	4.59	9.0	7.8	9.37	8.33	9.40	6.40	7.90	5.20	7.80	5.30	8.25	4.85
D-7	9.33	6.08	5.83	7.19	4.63	5.28	5.53	8.25	5.61	7.53	4.03	7.33	2.88	7.53	2.83	8.23	3.28
D-8	7.75	6.15	3.75	6.65	2.85	7.73	-	6.24	4.38	8.00	3.43	5.15	1.85	5.65	1.85	4.80	2.85
D-23	6.80	6.00	3.30	6.60	1.20	6.38	2.4	6.55	3.48	5.70	1.63	2.80	2.98	4.40	3.40	4.70	1.40
D-25	4.70	5.20	3.65	4.26	3.45	4.42	2.9	4.48	2.45	2.40	1.90	2.40	1.20	2.60	2.40	*9.90	*5.38
D-30	5.10	3.88	1.80	4.38	3.08	4.17	3.3	4.55	3.15	4.45	3.20	4.40	1.25	4.58	1.10	4.60	0.75
D-33	0.95	2.85	0.35	1.80	0.45	1.72	0.35	2.25	1.10	2.50	1.95	0.75	0.75	2.85	0.95	2.35	1.65
D-34	2.85	2.35	2.50	2.50	2.13	2.80	0.30	2.55	1.45	2.30	0.30	0.80	0.55	2.80	0.45	4.75	2.40
D-35	8.20	8.05	5.55	7.70	4.10	6.94	6.15	9.80	7.90	9.52	6.45	8.80	3.60	8.40	4.45	8.00	3.80
D-36	1.95	1.55	0.15	1.28	0.80	1.82	0.75	1.66	1.13	0.78	0.95	1.30	0.70	1.20	0.60	1.20	0.55
D-39	5.05	5.05	3.65	3.98	2.50	5.03	2.25	5.00	2.61	2.18	2.65	6.17	4.75	4.95	4.35	*12.60	*5.95
D40A	1.95	2.45	1.70		2.25	2.35	2.45	3.07	2.45	1.40	0.85	1.45	1.35	2.10	1.40	1.85	1.45
D-41	1.55	1.50	1.50	1.72	1.35	3.20	1.35	2.65	2.32	1.30	1.52	1.40	1.20	1.59	1.32	2.30	1.25
D-43	7.65	7.05	4.00	6.23	4.05	6.0	4.75	6.61	5.05	8.20	3.35	7.50	3.60	7.15	3.45	7.35	2.70
D-47	4.35	1.95	2.12	2.60	2.97	8.0	2.37	9.60	3.60	3.18	2.95	3.15	2.85	5.33	2.55	4.55	4.35
D-49	1.55	1.60	1.65	1.30	1.45	2.51	1.65	3.55	2.35	2.45	1.72	2.70	2.05	3.45	2.45	1.75	1.50
D-51	10.85	10.00	7.85	8.94	8.35	9.60	9.05	10.48	9.15	11.15	6.45	10.45	5.43	10.93	7.10	9.95	5.75
D-55	5.97	1.93	1.82	3.90	1.45	1.95	2.07	6.15	1.57	2.52	3.62	6.42	2.37	8.42	1.57	8.42	5.47
D-74	4.05	4.95	3.60	4.55	3.41	5.0	4.0	10.05	7.20	7.73	5.00	9.25	3.85	8.60	4.80	5.80	3.57
D-77	6.30	6.50	4.75	4.79	5.10	6.23	6.0	6.44	5.60	4.60	2.90	6.50	4.90	6.30	5.20	6.40	3.20
D-80	17.45	14.20	3.35	15.25	3.32	13.3	3.15	10.97	3.35	6.55	4.15	8.65	3.70	9.35	4.20	5.00	3.05
RCF (part)		May, 12	Nov, 12	May, 13	Nov, 13	May, 14	Nov, 14	May, 15	Nov, 15	May, 16	Nov, 16	May, 17	Nov, 17	May, 18	Nov, 18	May 19	Nov 19
DB22		2.43	2.38	8.18	2.64	6.48	3.03	4.59	3.53	5.38	3.33	1.93	1.63	2.34	1.93	4.93	1.63
DB23		2.90	2.33	5.05	3.10	3.95	2.13	3.38	6.04	5.30	0.90	2.05	1.90	2.85	1.75	1.60	0.80
DB24		-	-	-	8.25	-	8.45	9.52	8.20	10.65	6.50	5.80	3.78	8.25	5.70	9.35	3.88
DB25		3.96	1.18	1.33	2.53	3.27	2.73	3.83	2.68	3.61	1.98	3.23	2.58	3.93	1.63	-	-



Annexure – III

HYDROGRAPHS OF CGWB PERMANENT OBSERVATION STATIONS



Annexure – III

HYDROGRAPHS OF CGWB PERMANENT OBSERVATION STATIONS



Annexure – IV**GROUNDWATER SAMPLE LOCATION DETAILS****Sampling month:** May month of the assessment year of 2019

SI No	Name of Cluster	Ground Water Sample	Dug well (CMPDI)	Location	Sampling Date
					May'2019
1	CLUSTER-I	GW-1	B-15	BERA VILLAGE	28.05.2019
2	CLUSTER-II	GW-2	B-59	KHODOVALY VILLAGE	28.05.2019
3	CLUSTER-III	GW-3	A-29	GOVINDPUR,AMBAGAN VILLAGE	28.05.2019
4	CLUSTER-IV	GW-4	B-63	KESHALPUR, BATIGHAR	28.05.2019
5	CLUSTER-V	GW-5	D-30	BORKIBOA VILLAGE	28.05.2019
6	CLUSTER-VI	GW-6	D-25	GODHUR MORE	28.05.2019
7	CLUSTER-VII	GW-7	D-80	DHANSAR MINE RESCUE STN.	29.05.2019
8	CLUSTER-VIII	GW-8	D-49	NEAR GHANOODIH OC	29.05.2019
9	CLUSTER-IX	GW-9	D-5	JEALGORA, NEAR P.O.	29.05.2019
10	CLUSTER-X	GW-10	D-35	PATHERDIH RLY. COLONY	29.05.2019
11	CLUSTER-XI	GW-11	A-32	MONNIDIH BAZAR	29.05.2019
12	CLUSTER-XIII	GW-13	A-23	MACHHAYARA	28.05.2019
13	CLUSTER-XIV	GW-14	B-23	LOHAPATTI VILLAGE	28.05.2019
14	CLUSTER-XV	GW-15	B-32A	MADHUBAND VILLAGE	28.05.2019
15	CLUSTER-XVI	GW-16	DB-22	DAHIBARI,NICHE BASTI	28.05.2019

Annexure – V**GROUNDWATER QUALITY DATA (DUG WELLS)**

Month: May 2019

Sampling details is given in Annexure-IV.

Sl. No	Parameter	Sampling Stations			Detection Limit	IS:10500 Drinking Water Standards	Standard / Test Method
		GW 1 28.05.19	GW-2 28.05.19	GW-3 28.05.19			
1	Boron (as B), mg/l, Max	<0.2	<0.2	<0.2	0.2	0.5	APHA, 23rd Edition ,Carminc
2	Colour,in Hazen Units	3	2	4	1	5	APHA, 23rd Edition ,Pt.-Co. Method
3	Calcium (as Ca), mg/l, Max	40	64	76	1.6	75	IS-3025/40:1991, EDTA
4	Chloride (as Cl), mg/l, Max	24	28	18	2	250	IS-3025/32:1988, R-2007, Argentometric
5	Copper (as Cu), mg/l, Max	<0.03	0.03	<0.03	0.03	0.05	IS 3025/42 : 1992 R : 2009, AAS-Flame
6	Fluoride (as F) mg/l, Max	0.64	0.49	0.52	0.02	1.0	APHA, 23rd Edition , SPADNS
7	Free Residual Chlorine, mg/l, Min	<0.02	<0.02	<0.02	0.02	0.2	APHA, 23rd Edition , DPD
8	Iron (as Fe), mg/l, Max	0.15	0.12	0.06	0.06	1.0	IS 3025 /53 : 2003, R : 2009 , AAS-Flame
9	Lead (as Pb), mg/l, Max	<0.005	<0.005	<0.005	0.005	0.01	APHA, 23rd Edition ,AAS-GTA
10	Manganese (as Mn), mg/l, Max	<0.02	<0.02	<0.02	0.02	0.1	IS-3025/59:2006, AAS-Flame
11	Nitrate (as NO ₃), mg/l, Max	9.62	15.33	12.82	0.5	45	APHA, 23rd Edition., UV-Spectrophotometric
12	Odour	Agreeable	Agreeable	Agreeable	Qualitative	Agreeable	IS 3025 /05:1983, R-2012, Qualitative
13	pH value	7.83	8.03	7.98	2.5	6.5 to 8.5	IS-3025/11:1983, R-1996, Electrometric
14	Phenolic compounds (as C ₆ H ₅ OH), mg/l, Max	<0.001	<0.001	<0.001	0.001	0.001	APHA, 23rd Edition.,4-Amino Antipyrine
15	Selenium (as Se), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 56:2003, AAS-VGA
16	Sulphate (as SO ₄) mg/l, Max	98	112	136	2.00	200	APHA, 23rd Edition.
17	Taste	Acceptable	Acceptable	Acceptable	Qualitative	Acceptable	APHA, 23rd Edition. Taste
18	Total Alkalinity (CaCO ₃), mg/l, Max	102	94	116	4.00	200	IS-3025/23:1986, Titration
19	Total Arsenic (as As), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 37:1988 R : 2003, AAS-VGA
20	Total Chromium (as Cr), mg/l, Max	<0.04	<0.04	<0.04	0.04	0.05	IS-3025/52:2003, AAS-Flame
21	Total Dissolved Solids, mg/l, Max	462	536	642	25.00	500	IS 3025 /16:1984 R : 2006, Gravimetric
22	Total Hardness (CaCO ₃), mg/l, Max	210	360	420	4.00	200	IS-3025/21:1983, R-2002, EDTA
23	Turbidity, NTU, Max	2	1	2	1.0	5.0	IS-3025/10:1984 R-1996, Nephelometric
24	Zinc (as Zn), mg/l, Max	0.06	0.14	0.03	0.01	5.0	IS 3025/ 49 : 1994, R : 2009, AAS-Flame
25	Nickel as Ni, mg/l Max	<0.01	<0.01	<0.01	0.01	0.02	IS 3025/ 54 : 2003, AAS-Flame

Sl. No	Parameter	Sampling Stations			Detection Limit	IS:10500 Drinking Water Standards	Standard / Test Method
		GW 4 28.05.19	GW-5 28.05.19	GW-6 28.05.19			
1	Boron (as B), mg/l, Max	<0.2	<0.2	<0.2	0.2	0.5	APHA, 23rd Edition ,Carmin
2	Colour,in Hazen Units	2	2	1	1	5	APHA, 23rd Edition ,Pt.-Co. Method
3	Calcium (as Ca), mg/l, Max	72	56	84	1.6	75	IS-3025/40:1991, EDTA
4	Chloride (as Cl), mg/l, Max	32	22	28	2	250	IS-3025/32:1988, R-2007, Argentometric
5	Copper (as Cu), mg/l, Max	<0.03	<0.03	<0.03	0.03	0.05	IS 3025/42 : 1992 R : 2009, AAS-Flame
6	Fluoride (as F) mg/l, Max	0.44	0.48	0.69	0.02	1.0	APHA, 23rd Edition , SPADNS
7	Free Residual Chlorine, mg/l, Min	<0.02	<0.02	<0.02	0.02	0.2	APHA, 23rd Edition , DPD
8	Iron (as Fe), mg/l, Max	0.09	0.06	0.12	0.06	1.0	IS 3025 /53 : 2003, R : 2009 , AAS-Flame
9	Lead (as Pb), mg/l, Max	<0.005	<0.005	<0.005	0.005	0.01	APHA, 23rd Edition ,AAS-GTA
10	Manganese (as Mn), mg/l, Max	<0.02	<0.02	<0.02	0.02	0.1	IS-3025/59:2006, AAS-Flame
11	Nitrate (as NO ₃), mg/l, Max	11.27	15.18	13.03	0.5	45	APHA, 23rd Edition., UV-Spectrophotometric
12	Odour	Agreeable	Agreeable	Agreeable	Qualitative	Agreeable	IS 3025 /05:1983, R-2012, Qualitative
13	pH value	8.07	7.99	7.64	2.5	6.5 to 8.5	IS-3025/11:1983, R-1996, Electrometric
14	Phenolic compounds (as C ₆ H ₅ OH), mg/l, Max	<0.001	<0.001	<0.001	0.001	0.001	APHA, 23rd Edition.,4-Amino Antipyrine
15	Selenium (as Se), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 56:2003, AAS-VGA
16	Sulphate (as SO ₄) mg/l, Max	108	82	90	2.00	200	APHA, 23rd Edition.
17	Taste	Acceptable	Acceptable	Acceptable	Qualitative	Acceptable	APHA, 23rd Edition. Taste
18	Total Alkalinity (CaCO ₃), mg/l, Max	104	96	72	4.00	200	IS-3025/23:1986, Titration
19	Total Arsenic (as As), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 37:1988 R : 2003, AAS-VGA
20	Total Chromium (as Cr), mg/l, Max	<0.04	<0.04	<0.04	0.04	0.05	IS-3025/52:2003, AAS-Flame
21	Total Dissolved Solids, mg/l, Max	428	366	796	25.00	500	IS 3025 /16:1984 R : 2006, Gravimetric
22	Total Hardness (CaCO ₃), mg/l, Max	330	290	400	4.00	200	IS-3025/21:1983, R-2002, EDTA
23	Turbidity, NTU, Max	4	3	1	1.0	5.0	IS-3025/10:1984 R-1996, Nephelometric
24	Zinc (as Zn), mg/l, Max	0.06	0.27	0.05	0.01	5.0	IS 3025/ 49 : 1994, R : 2009, AAS-Flame
25	Nickel as Ni, mg/l Max	<0.01	<0.01	<0.01	0.01	0.02	IS 3025/ 54 : 2003, AAS-Flame



Sl. No	Parameter	Sampling Stations			Detection Limit	IS:10500 Drinking Water Standards	Standard / Test Method
		GW 7 29.05.19	GW-8 29.05.19	GW-9 29.05.19			
1	Boron (as B), mg/l, Max	<0.2	<0.2	<0.2	0.2	0.5	APHA, 23rd Edition ,Carmine
2	Colour,in Hazen Units	3	2	2	1	5	APHA, 23rd Edition ,Pt.-Co. Method
3	Calcium (as Ca), mg/l, Max	32	68	80	1.6	75	IS-3025/40:1991, EDTA
4	Chloride (as Cl), mg/l, Max	34	36	24	2	250	IS-3025/32:1988, R-2007, Argentometric
5	Copper (as Cu), mg/l, Max	<0.03	<0.03	<0.03	0.03	0.05	IS 3025/42 : 1992, R : 2009, AAS-Flame
6	Fluoride (as F) mg/l, Max	0.70	0.62	0.67	0.02	1.0	APHA, 23rd Edition , SPADNS
7	Free Residual Chlorine, mg/l, Min	<0.02	<0.02	<0.02	0.02	0.2	APHA, 23rd Edition ,DPD
8	Iron (as Fe), mg/l, Max	0.24	0.08	0.06	0.06	1.0	IS 3025 /53 : 2003,R : 2009 , AAS-Flame
9	Lead (as Pb), mg/l, Max	<0.005	<0.005	<0.005	0.005	0.01	APHA, 23rd Edition ,AAS-GTA
10	Manganese (as Mn), mg/l, Max	<0.02	<0.02	<0.02	0.02	0.1	IS-3025/59:2006,AAS-Flame
11	Nitrate (as NO ₃), mg/l, Max	16.22	15.64	11.20	0.5	45	APHA, 23rd Edition.,UV-Spectrophotometric
12	Odour	Agreeable	Agreeable	Agreeable	Qualitative	Agreeable	IS 3025 /05:1983, R-2012, Qualitative
13	pH value	8.14	7.81	8.01	2.5	6.5 to 8.5	IS-3025/11:1983, R-1996, Electrometric
14	Phenolic compounds (as C ₆ H ₅ OH), mg/l, Max	<0.001	<0.001	<0.001	0.001	0.001	APHA, 23rd Edition.,4-Amino Antipyrine
15	Selenium (as Se), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 56:2003, AAS-VGA
16	Sulphate (as SO ₄) mg/l, Max	126	106	114	2.00	200	APHA, 23rd Edition.
17	Taste	Acceptable	Acceptable	Acceptable	Qualitative	Acceptable	APHA, 23rd Edition. Taste
18	Total Alkalinity (CaCO ₃), mg/l, Max	124	86	112	4.00	200	IS-3025/23:1986,Titration
19	Total Arsenic (as As), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 37:1988R : 2003, AAS-VGA
20	Total Chromium (as Cr), mg/l, Max	<0.04	<0.04	<0.04	0.04	0.05	IS-3025/52:2003, AAS-Flame
21	Total Dissolved Solids, mg/l, Max	388	544	612	25.00	500	IS 3025 /16:1984, R : 2006, Gravimetric
22	Total Hardness (CaCO ₃), mg/l, Max	190	320	410	4.00	200	IS-3025/21:1983,R-2002, EDTA
23	Turbidity, NTU, Max	4	2	3	1.0	5.0	IS-3025/10:1984 R-1996,Nephelometric
24	Zinc (as Zn), mg/l, Max	0.04	0.02	0.08	0.01	5.0	IS 3025/ 49 : 1994, R : 2009, AAS-Flame
25	Nickel as Ni, mg/l Max	<0.01	<0.01	<0.01	0.01	0.02	IS 3025/ 54 : 2003, AAS-Flame

Sl. No	Parameter	Sampling Stations			Detection Limit	IS:10500 Drinking Water Standards	Standard / Test Method
		GW 10 29.05.19	GW-11 29.05.19	GW-13 28.05.19			
1	Boron (as B), mg/l, Max	<0.2	<0.2	<0.2	0.2	0.5	APHA, 23rd Edition ,Carmin
2	Colour,in Hazen Units	3	2	2	1	5	APHA, 23rd Edition ,Pt.-Co. Method
3	Calcium (as Ca), mg/l, Max	76	48	52	1.6	75	IS-3025/40:1991, EDTA
4	Chloride (as Cl), mg/l, Max	26	20	16	2	250	IS-3025/32:1988, R-2007, Argentometric
5	Copper (as Cu), mg/l, Max	<0.03	<0.03	<0.03	0.03	0.05	IS 3025/42 : 1992 R : 2009, AAS-Flame
6	Fluoride (as F) mg/l, Max	0.55	0.68	0.78	0.02	1.0	APHA, 23rd Edition , SPADNS
7	Free Residual Chlorine, mg/l, Min	<0.02	<0.02	<0.02	0.02	0.2	APHA, 23rd Edition , DPD
8	Iron (as Fe), mg/l, Max	0.18	0.06	0.09	0.06	1.0	IS 3025 /53 : 2003, R : 2009 , AAS-Flame
9	Lead (as Pb), mg/l, Max	<0.005	<0.005	<0.005	0.005	0.01	APHA, 23rd Edition ,AAS-GTA
10	Manganese (as Mn), mg/l, Max	<0.02	<0.02	<0.02	0.02	0.1	IS-3025/59:2006, AAS-Flame
11	Nitrate (as NO ₃), mg/l, Max	14.62	13.11	10.37	0.5	45	APHA, 23rd Edition., UV-Spectrophotometric
12	Odour	Agreeable	Agreeable	Agreeable	Qualitative	Agreeable	IS 3025 /05:1983, R-2012, Qualitative
13	pH value	8.10	7.85	7.77	2.5	6.5 to 8.5	IS-3025/11:1983, R-1996, Electrometric
14	Phenolic compounds (as C ₆ H ₅ OH), mg/l, Max	<0.001	<0.001	<0.001	0.001	0.001	APHA, 23rd Edition.,4-Amino Antipyrine
15	Selenium (as Se), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 56:2003, AAS-VGA
16	Sulphate (as SO ₄) mg/l, Max	82	104	132	2.00	200	APHA, 23rd Edition.
17	Taste	Acceptable	Acceptable	Acceptable	Qualitative	Acceptable	APHA, 23rd Edition. Taste
18	Total Alkalinity (CaCO ₃), mg/l, Max	106	66	94	4.00	200	IS-3025/23:1986, Titration
19	Total Arsenic (as As), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 37:1988 R : 2003, AAS-VGA
20	Total Chromium (as Cr), mg/l, Max	<0.04	<0.04	<0.04	0.04	0.05	IS-3025/52:2003, AAS-Flame
21	Total Dissolved Solids, mg/l, Max	604	484	462	25.00	500	IS 3025 /16:1984 R : 2006, Gravimetric
22	Total Hardness (CaCO ₃), mg/l, Max	370	230	270	4.00	200	IS-3025/21:1983, R-2002, EDTA
23	Turbidity, NTU, Max	1	1	1	1.0	5.0	IS-3025/10:1984 R-1996, Nephelometric
24	Zinc (as Zn), mg/l, Max	0.14	0.02	0.08	0.01	5.0	IS 3025/ 49 : 1994, R : 2009, AAS-Flame
25	Nickel as Ni, mg/l Max	<0.01	<0.01	<0.01	0.01	0.02	IS 3025/ 54 : 2003, AAS-Flame

Sl. No	Parameter	Sampling Stations			Detection Limit	IS:10500 Drinking Water Standards	Standard / Test Method
		GW-14 28.05.19	GW-15 28.05.19	GW-16 28.05.19			
1	Boron (as B), mg/l, Max	<0.20	<0.20	<0.2	0.2	0.5	APHA, 23rd Edition, Cammine
2	Colour, in Hazen Units	1	2	1	1	5	APHA, 23rd Edition, Pt.-Co. Method
3	Calcium (as Ca), mg/l, Max	60	44	28	1.6	75	IS-3025/40:1991, EDTA
4	Chloride (as Cl), mg/l, Max	42	30	18	2	250	IS-3025/32:1988, R-2007, Argentometric
5	Copper (as Cu), mg/l, Max	<0.03	<0.03	<0.03	0.03	0.05	IS 3025/42 : 1992 R : 2009, AAS-Flame
6	Fluoride (as F) mg/l, Max	0.53	0.46	0.51	0.02	1.0	APHA, 23rd Edition, SPADNS
7	Free Residual Chlorine, mg/l, Min	<0.02	<0.02	<0.02	0.02	0.2	APHA, 23rd Edition, DPD
8	Iron (as Fe), mg/l, Max	0.12	0.06	0.15	0.06	1.0	IS 3025 /53 : 2003, R : 2009, AAS-Flame
9	Lead (as Pb), mg/l, Max	<0.005	<0.005	<0.005	0.005	0.01	APHA, 23rd Edition, AAS-GTA
10	Manganese (as Mn), mg/l, Max	<0.02	<0.02	<0.02	0.02	0.1	IS-3025/59:2006, AAS-Flame
11	Nitrate (as NO ₃), mg/l, Max	12.32	14.10	10.97	0.5	45	APHA, 23rd Edition, UV-Spectrophotometric
12	Odour	Agreeable	Agreeable	Agreeable	Qualitative	Agreeable	IS 3025 /05:1983, R-2012, Qualitative
13	pH value	8.07	7.82	8.04	2.5	6.5 to 8.5	IS-3025/11:1983, R-1996, Electrometric
14	Phenolic compounds (as C ₆ H ₅ OH), mg/l, Max	<0.001	<0.001	<0.001	0.001	0.001	APHA, 23rd Edition, 4-Amino Antipyrine
15	Selenium (as Se), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 56:2003, AAS-VGA
16	Sulphate (as SO ₄) mg/l, Max	68	118	122	2.00	200	APHA, 23rd Edition.
17	Taste	Acceptable	Acceptable	Acceptable	Qualitative	Acceptable	APHA, 23rd Edition. Taste
18	Total Alkalinity (CaCO ₃), mg/l, Max	100	92	76	4.00	200	IS-3025/23:1986, Titration
19	Total Arsenic (as As), mg/l, Max	<0.002	<0.002	<0.002	0.002	0.01	IS 3025/ 37:1988 R : 2003, AAS-VGA
20	Total Chromium (as Cr), mg/l, Max	<0.04	<0.04	<0.04	0.04	0.05	IS-3025/52:2003, AAS-Flame
21	Total Dissolved Solids, mg/l, Max	538	468	398	25.00	500	IS 3025 /16:1984 R : 2006, Gravimetric
22	Total Hardness (CaCO ₃), mg/l, Max	340	280	170	4.00	200	IS-3025/21:1983, R-2002, EDTA
23	Turbidity, NTU, Max	2	2	1	1.0	5.0	IS-3025/10:1984 R-1996, Nephelometric
24	Zinc (as Zn), mg/l, Max	0.06	0.18	0.03	0.01	5.0	IS 3025/ 49 : 1994, R : 2009, AAS-Flame
25	Nickel as Ni, mg/l Max	<0.01	<0.01	<0.01	0.01	0.02	IS 3025/ 54 : 2003, AAS-Flame - Flame



Annexure – VI

HYDROGRAPHS OF CLUSTER-I





Annexure – VI

HYDROGRAPHS OF CLUSTER-II





Annexure – VI

HYDROGRAPHS OF CLUSTER-III





Annexure – VI

HYDROGRAPHS OF CLUSTER-IV





Annexure – VI

HYDROGRAPHS OF CLUSTER-V





Annexure – VI

HYDROGRAPHS OF CLUSTER-VI





Annexure – VI

HYDROGRAPHS OF CLUSTER-VII





Annexure – VI

HYDROGRAPHS OF CLUSTER-VIII





Annexure – VI

HYDROGRAPHS OF CLUSTER-IX





Annexure – VI

HYDROGRAPHS OF CLUSTER-X





Annexure – VI

HYDROGRAPHS OF CLUSTER-XI





Annexure – VI

HYDROGRAPHS OF CLUSTER-XIII





Annexure – VI

HYDROGRAPHS OF CLUSTER-XIV





Annexure – VI

HYDROGRAPHS OF CLUSTER-XV



Annexure – VI

HYDROGRAPHS OF CLUSTER-XVI

**Abbreviations**

AMSL: Above mean sea level

Avg.: Average

APT: Aquifer Pumping Test

BCCL: Bharat Coking Coal Ltd.

bgl: Below Ground Level

Buffer zone: periphery of the 10 km radius from the project boundary

Core zone: Project / mine / colliery boundary (leasehold area)

CMPDI: Central Mine Plan & Design Institute

DVC: Damodar Valley Corporation

DTW: Depth to water level

GW: Groundwater

IMD: Indian Meteorological Division

JCF: Jharia Coalfield

RCF: Raniganj Coalfield

MADA: Mineral Area Development Authority

MCM: Million Cubic Meter

MGD: Million Gallon per day

NTU: Nephelometric Turbidity unit

OC / UG: Opencast / Underground


OCP / UGP: Opencast Project / Underground Project

RL: Reduced Level


RWH: Rainwater Harvesting

FF: Fire Fighting


GROUNDWATER MONITORING STATION LOCATION MAP




GROUNDWATER QUALITY MONITORING STATION LOCATION MAP



PROPOSED PIEZOMETER LOCATION MAP, JCF & RCF (part)



WATER TABLE CONTOUR MAP OF PRE-MONSOON 2019



STRICTLY RESTRICTED**FOR COMPANY USE ONLY RESTRICTED**

The information given in this report is not to be communicated either directly or indirectly to the press or to any person not holding an official position in the CIL /GOVERNMENT.

**ENVIRONMENTAL MONITORING REPORT
OF
BHARAT COKING COAL LIMITED,
CLUSTER – XIII**

(FOR THE MONTH OCTOBER, 2019)

E. C. no. J-11015/11/2010-IA.II (M) dated 06.06.2013-



CMPDI

ISO 9001 Company
**Regional Institute-II
Dhanbad, Jharkhand**

CONTENTS

SL. NO.	CHAPTER	PARTICULARS	PAGE NO.
1.	CHAPTER - I	EXECUTIVE SUMMARY	3-5
2.	CHAPTER-II	INTRODUCTION	6
3.	CHAPTER-III	RESULTS	7-11
4.	CHAPTER-IV	STANDARDS AND PLANS	12-15

EXECUTIVE SUMMARY

1.0 Introduction

The purpose of environmental monitoring is to assess the quality of various attributes that affects the fauna and flora. In accordance with the quality of these attributes appropriate strategy is to be developed to control the pollution level within the permissible limits. The three major attributes are air, water and noise level.

Bharat Coking Coal Limited (BCCL), a Subsidiary company of Coal India Limited is operating Underground and Opencast Mines in Jharia Coalfield (JCF) is a part of Gondwana Coalfields located in Dhanbad district of Jharkhand, the JCF is bounded by 23°37' N to 23°52' N latitudes and 86°09' E to 86°30' E longitude occupying an area of 450 Sq.km. BCCL has awarded Environmental monitoring work of Jharia Coalfield (JCF) to Central Mine Planning & Design Institute Limited (CMPDIL). The environmental monitoring has been carried out as per the conditions laid down by the MoEF&CC while granting environmental clearance of project, consent letter issued by the respective SPCB, and other statutory requirements.

2.0 Sampling location and rationale

2.1 Ambient air sampling locations

The ambient air quality monitoring stations were selected to represent core, buffer zone area. The rationale has been based on the guidelines stipulated by MoEF&CC, consent letter of SPCB, as well as other statutory requirements.

2.2 Water sampling stations

The Water sampling stations were selected for mine discharge water.

2.3 Noise level monitoring locations

Noise levels vary depending on the various activities in mining areas. The monitoring of noise level in different locations will be helpful to take appropriate mitigating measures. The rationale has been based on the guidelines stipulated by MoEF&CC, consent letter of SPCB, as well as other statutory requirements.

3.0 Methodology of sampling and analysis

3.1 Ambient air quality

Parameters chosen for assessment of ambient air quality were Particulate Matter (PM₁₀), Fine Particulate Matter (PM_{2.5}), Sulphur Di-oxide

(SO₂) and Nitrogen Oxides (NO_x). Respirable Dust Samplers (RDS) were used for sampling of PM₁₀, SO₂, & NO_x and Fine Dust Sampler (PM_{2.5} sampler) were used for sampling of PM_{2.5} at 24 hours interval once in a fortnight and the same for the gaseous pollutants. The samples were analyzed in Environmental Laboratory of CMPDI, RI-II, Dhanbad.

3.2 Water quality

Water samples were collected as per standard practice. The Mine effluent samples were collected and analysed for four parameters on fortnightly basis. Thereafter the samples were preserved and analysed at the Environmental Laboratory of CMPDI, RI- II, Dhanbad.

3.3 Noise level monitoring

Noise level measurements in form of 'L_{EQ}' were taken using Integrated Data Logging Sound Level Meter. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB(A).

4.0 Results and interpretations

4.1 Air quality

It has been seen from the analysis results that the 24 hours average concentration parameters like PM₁₀, PM_{2.5}, SO₂ and NO_x are mostly within the permissible limits in all sampling locations as per MoEF&CC Gazette Notification No. GSR 742(E) dt 25.09.2000 Standards for Coal Mines and National Ambient Air Quality Standard -2009. Sometimes the concentration of PM₁₀& PM_{2.5} exceeds the limits due to heavy public traffic, poor road condition, coke oven plants, burning of coal by surrounding habitants, brick making, municipal waste dumps and industries like Steel Plant, thermal Plants including their fly ash etc.

The following preventive and suppressive mitigative measures can be undertaken to contain the pollution level within prescribed level:-

- Wet drilling and controlled blasting should be practice.
- Explosive used should be optimised to restrict the dust generation.
- Transportation roads should be permanently asphalted free of ruts, potholes etc.
- Water should be sprayed on coal transportation road, service road more frequently and at regular interval.
- Dust from roads should be removed physically or mechanically.
- Greenbelts around industrial sites, service building area besides Avenue plantation along roads should be created.
- Coal dust should be suppressed by using fixed sprinklers.
- Regular maintenance of plant and machinery should be undertaken.

4.2 Water quality

The test results indicate that the major parameters compared with MoEF&CC Gazette Notification No. GSR 742(E) dt 25.09.2000 Standards for Coal Mines, are within permissible limits.

4.3 Noise Level

During the noise level survey it has been observed that the noise level in the sampling locations is within the permissible limits prescribed as per MoEF&CC Gazette Notification No. GSR 742(E) dt 25.09.2000 Standards for Coal Mines for Industrial Area and Noise pollution (Regulation and Control) Rules, 2000.

INTRODUCTION

- 1.0 Any industry and development activities including coal mining is bound to affect environmental attributes. There are positive as well as negative impacts of such operations. For controlling the adverse impacts a regular monitoring is essential. The environmental monitoring is being done as per the guide-lines stipulated by Ministry of Environment, Forest and Climate Change (MoEF&CC), Govt. of India.

Bharat Coking Coal has awarded Environmental Monitoring work of all Projects, Cluster wise, to Central Mine Planning & Design Institute Limited (CMPDIL). The environmental monitoring has been carried out as per conditions laid down by MoEF&CC while granting environmental clearance to different projects. CMPDI has trained manpower and well equipped laboratory to carry out monitoring, analysis and R&D work in the field of environment.

- 1.1 The Cluster-XIII is in the Northern part of the Jharia coalfield. It includes a group of 7 Mines (viz. Murlidih, Bhurungiya, Mucharadih, Hantoodih, Padugora, Murlidih 20/21 Pits & Bhatdih. The Cluster – XIII is situated about 25 - 30 kms from Dhanbad Railway Station. The mines of this Cluster – XIII are operating since pre nationalization period (prior to 1972-73). It is connected by both Railway and Road. The drainage of the area is governed by Katri River & Damodar River..

- 1.2 The Cluster-XIII is designed to produce 0.18 MTPA (normative) and 2.34 MTPA (peak) capacity of coal.

The Project has Environmental Clearance from Ministry of Environment, Forests and Climate Change (MoEF&CC) for a rated capacity 0.18 MTPA (normative) and 2.34 MTPA (peak) capacity of coal production vide letter no. J-11015/11/2010-IA.II (M) dated 06th June, 2013.

Ministry of Environment, Forests and Climate Change while granting environmental clearance has given one of the General conditions that “ Four ambient air quality monitoring stations should be established in the core zone as well as in the buffer zone for PM₁₀, PM_{2.5}, SO₂, NO_x monitoring. Location of the stations should be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets in consultation with the State Pollution Control Board.” And other conditions regarding water / effluent and noise level monitoring.

In compliance of these conditions the Environmental Monitoring has been carried out & report prepared for submission to MoEF&CC& SPCB and other statutory authorities.

AMBIENT AIR QUALITY MONITORING

2.1 Location of sampling station and their rationale:

(As per G.S.R. 742 (E) dt. 25th December, 2000)

2.1.1 Ambient Air Quality Sampling Locations

I. CORE ZONE Monitoring Location

i) Murlidih 20/21 (A19): Industrial Area

The location of the sampling station is 23°43' 51.82" N & 86° 16' 21.17" E. The sampler was placed at a height of approx. 1.5m above ground level at Project Office.

II. BUFFER ZONE Monitoring Location

i) Lohapatti (A20)

The location of the sampling station is 23°44'29.42" N & 86°16'49.96" E. The sampler was placed at a height of approx. 1.5m above ground level at Safety Office.

ii) Kharkharee CISF Office (A21)


The location of the sampling station is 23°46' 29.00" N 86° 14' 37.08"E. The sampler was placed at a height of approx. 1.5m above ground level at Project Office.

ii) Dumarda (A31)


The location of the sampling station is 23° 42' 50.00" N 86° 15' 4.00"E. The location was selected for studying the impact of the mining activity on the Dumarda village as it lies in the buffer zone for the Cluster XIII.

AMBIENT AIR QUALITY DATA**Cluster –XIII, Bharat Coking Coal limited****Month: OCT. ,2019****Year : 2019-20.**

Station Name: A19 – Murlidih 20/21		Zone: Core		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	15.10.19	71	38	11.94	22.86
2	22.10.19	67	36	11.52	21.35
	NAAQ Standards	100	60	80	80



Station Name: A20, Lohapatti		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	15.10.19	75	41	11.61	21.31
2	23.10.19	78	42	12.33	22.60
	NAAQ Standard	100	60	80	80




अमान उद्ध रावत
Analysed By
JSA/SA/SSA


Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

Station Name: A21 Kharkharee		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	01.10.19	76	39	11.13	22.06
2	18.10.19	69	37	12.54	21.06
	NAAQ Standards	100	60	80	80



Station Name: A31 Dumarda		Zone: Buffer		Category: Residential	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	15.10.19	81	45	9.55	19.65
2	22.10.19	82	47	9.25	18.32
	NAAQ Standards	100	60	80	80



- All values are expressed in microgram per cubic meter.
- 24 hours duration

अनिल उद्ध रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

WATER quality monitoring

3.1 Location of sampling sites

(Refer **Plate No. – II**)

i) **Mine Discharge of Murlidih 20/21 (MW13)**

A sampling point is fixed to assess the effluent quality of Mine discharge. This location is selected to monitor effluent discharge in to Jamunia.

3.2 Methodology of sampling and analysis

Water samples were collected as per standard practice. The effluent samples were collected and analyzed for four parameters on fortnightly basis at the Environmental Laboratory of CMPDI RI-II, Dhanbad.


3.3 Results & Interpretations

The results are given in tabular form along with the applicable standards. Results are compared with Schedule - VI, effluent prescribed by MoEF&CC. Results show that most of the parameters are within the permissible limits.

WATER QUALITY DATA (EFFLUENT WATER- FOUR PARAMETERS)

Name of the Cluster: Cluster -XIII		Month: OCT, 2019	Name of the Station: Mine Discharge of Murlidih 20/21	
Sl. No.	Parameters	MW13 First Fortnight	MW13 Second Fortnight	As per MOEF General Standards for schedule VI
		07.10.2019	23.10.2019	
1	Total Suspended Solids	32	70	100 (Max)
2	pH	8.14	8.19	5.5 - 9.0
3	Oil & Grease	<2.0	<2.0	10 (Max)
4	COD	44	36	250 (Max)

All values are expressed in mg/lit unless specified.


 Analysed By
 JSA/SA/SSA


 Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad


 Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

NOISE LEVEL QUALITY MONITORING

4.1 Location of sampling sites

- i) Murlidih (N19)
- ii) Lohapatti (N20)
- iii) Kharkharee CISF Office (N21)
- iv) Dumarda (N31)

4.2 Methodology of sampling and analysis

Noise level measurements in form of 'L_{EQ}' were taken using Integrated Data Logging Sound Level Meter (NL-52 OF RION CO. Ltd. Make) during day time. Noise levels were measured for about one hour time in day time. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB (A).

4.3 Results & Interpretations

Ambient noise levels were recorded during day time and the observed values were compared with standards prescribed by MoEFCC. The results of Noise levels recorded during day time on fortnightly basis are presented in tabular form along with the applicable standard permissible limits. The observed values in terms of L_{EQ} are presented. The observed values at all the monitoring locations are found to be within permissible limits.

NOISE LEVEL DATA

Name of the Project: Cluster -XIII			Month: OCT. , 2019		
Sl. No.	Station Name/Code	Category of area	Date	Noise level dB(A)LEQ	*Permissible Limit of Noise level in dB(A)
1	Murlidih 20/21 (N19)	Industrial area	15.10.19	58.1	75
2	Murlidih 20/21	Industrial area	22.10.19	51.2	75
3	Lohapatti (N20)	Industrial area	15.10.19	63.3	75
4	Lohapatti	Industrial area	23.10.19	64.5	75
5	Kharkharee (N21)	Industrial area	01.10.19	55.6	75
6	Kharkharee	Industrial area	18.10.19	56.3	75
7	Dumarda (N31)	Residential area	15.10.19	48.2	55
8	Dumarda	Residential area	22.10.19	49.1	55

*Permissible limits of Noise Level as per MOEF Gazette Notification No. GSR 742(E) dt. 25.09.2000 Standards for Coal Mines and Noise Pollution (Regulation and Control) Rules, 2000.

* Day Time: 6.00 AM to 10.00 PM,

अनुमन उद्ध रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अतिर
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

Ambient Air Quality Standards for Jharia Coal Field
As per the Environment (Protection) Amendment Rules, 2000 notified vide
notification G.S.R. 742(E), dated 25.9.2000.

Category	Pollutant	Time weighted average	Concentration in Ambient Air	Method of Measurement
1	2	3	4	5
III Coal mines located in the coal fields of <ul style="list-style-type: none"> • Jharia • Raniganj • Bokaro 	Suspended Particulate Matter (SPM)	Annual Average * 24 hours **	500 $\mu\text{g}/\text{m}^3$ 700 $\mu\text{g}/\text{m}^3$	- High Volume Sampling (Average flow rate not less than 1.1
	Respirable Particulate Matter (size less than 10 μm) (RPM)	Annual Average * 24 hours **	250 $\mu\text{g}/\text{m}^3$ 300 $\mu\text{g}/\text{m}^3$	Respirable Particulate Matter sampling and analysis
	Sulphur Dioxide (SO_2)	Annual Average * 24 hours **	80 $\mu\text{g}/\text{m}^3$ 120 $\mu\text{g}/\text{m}^3$	1.Improvedwest and Gaeke method 2.Ultraviolet fluorescene
	Oxide of Nitrogen as NO_2	Annual Average * 24 hours **	80 $\mu\text{g}/\text{m}^3$ 120 $\mu\text{g}/\text{m}^3$	1. Jacob &Hochheiser Modified (Na-Arsenic) Method 2. Gas phase Chemilumine-scence

Note:

* Annual Arithmetic mean for the measurements taken in a year, following the guidelines for frequency of sampling laid down in clause 2.

** 24hourly/8hourly values shall be met 92% of the time in a year. However, 8% of the time it may exceed but not on two consecutive days.

NATIONAL AMBIENT AIR QUALITY STANDARDS

New Delhi the 18th JANUARY 2009

In exercise of the powers conferred by Sub-section (2) (h) of section 16 of the Air (Prevention and Control of Pollution) Act, 1981 (Act No. 14 of 1981), and in supersession of the notification No(s).S.O.384(E), dated 11th AUGUST 1994 and S.O.935(E), dated 14th October 1998, the Central Pollution Control Board hereby notify the National Ambient Air Quality Standards with immediate effect.

Pollutant	Time Weighted Average	Concentration in Ambient Air		Methods of Measurement
		Industrial, Residential, Rural and other Areas	Ecologically Sensitive Area (Notified by Central Government)	
Sulphur Dioxide (SO₂), µg/m³	Annual * 24 Hours **	50 80	20 80	-Improved West and Gaeke Method -Ultraviolet Fluorescence
Nitrogen dioxide (NO₂), µg/m³	Annual * 24 Hours **	40 80	30 80	-Jacob & Hochheiser modified (NaOH-NaAsO ₂) Method -Gas Phase Chemiluminescence
Particulate Matter (Size less than 10µm) or PM₁₀, µg/m³	Annual * 24 Hours **	60 100	60 100	-Gravimetric -TEOM -Beta attenuation
Particulate Matter (Size less than 2.5µm) or PM_{2.5}, µg/m³	Annual * 24 Hours **	40 60	40 60	-Gravimetric -TEOM -Beta attenuation
Ozone (O₃) , µg/m³	8 Hours * 1 Hour **	100 180	100 180	-UV Photometric -Chemiluminescence -Chemical Method
Lead (Pb) , µg/m³	Annual * 24 Hours **	0.50 1.0	0.50 1.0	-AAS/ICP Method after sampling on EPM 2000 or equivalent filter paper -ED-XRF using Teflon filter
Carbon Monoxide (CO), mg/m³	8 Hours ** 1 Hour **	02 04	02 04	-Non dispersive Infrared (NDIR) Spectroscopy
Ammonia (NH₃), µg/m³	Annual * 24 Hours **	100 400	100 400	-Chemiluminescence -Indophenol blue method
Benzene (C₆H₆), µg/m³	Annual *	05	05	-Gas Chromatography (GC) based continuous analyzer -Adsorption and desorption followed by GC analysis
Benzo(a)Pyrene (BaP) Particulate phase only, ng/m³	Annual *	01	01	-Solvent extraction followed by HPLC/GC analysis
Arsenic (As), ng/m³	Annual *	06	06	-AAS/ICP Method after sampling on EPM 2000 or equivalent filter paper
Nickel (Ni), ng/m³	Annual *	20	20	-AAS/ICP Method after sampling on EPM 2000 or equivalent filter paper

* Annual Arithmetic mean of minimum 104 measurements in a year at a particular site taken twice a week 24 hourly at uniform intervals.

** 24 hourly or 8 hourly or 1 hourly monitored values, as applicable, shall be complied with 98% of the time in a year. 2% of the time, they AUGUST exceed the limits but not on two consecutive days of monitoring.

NOTE: Whenever and wherever monitoring results on two consecutive days of monitoring exceed the limits specified above for the respective category, it shall be considered adequate reason to institute regular or continuous monitoring and further investigations.

STRICTLY RESTRICTED**FOR COMPANY USE ONLY RESTRICTED**

The information given in this report is not to be communicated either directly or indirectly to the press or to any person not holding an official position in the CIL /GOVERNMENT.

ENVIRONMENTAL MONITORING REPORT OF BHARAT COKING COAL LIMITED, CLUSTER – XIII

(FOR THE MONTH NOVEMBER, 2019)

E. C. no. J-11015/11/2010-IA.II (M) dated 06.06.2013-




CMPDI

ISO 9001 Company
Regional Institute-II
Dhanbad, Jharkhand


AMBIENT AIR QUALITY DATA

Cluster –XIII, Bharat Coking Coal limited
Month: NOV. ,2019
Year : 2019-20.

Station Name: A19 – Murlidih 20/21		Zone: Core		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	14.11.19	97	56	13.40	23.69
2	29.11.19	91	53	11.92	21.53
	NAAQ Standards	100	60	80	80



Station Name: A20, Lohapatti		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	13.11.19	95	58	11.77	22.02
2	28.11.19	97	59	13.36	24.55
	NAAQ Standard	100	60	80	80




Analysed By
 JSA/SA/SSA


Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad

Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

Station Name: A21 Kharkharee		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	06.11.19	95	54	11.44	22.54
2	21.11.19	92	50	14.14	22.86
	NAAQ Standards	100	60	80	80



Station Name: A31 Dumarda		Zone: Buffer		Category: Residential	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	14.11.19	96	57	9.05	18.32
2	29.11.19	92	48	9.09	17.56
	NAAQ Standards	100	60	80	80



- All values are expressed in microgram per cubic meter.
- 24 hours duration

अनिल कुमार रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

WATER quality monitoring

3.1 Location of sampling sites

(Refer **Plate No. – II**)

i) **Mine Discharge of Murlidih 20/21 (MW13)**

A sampling point is fixed to assess the effluent quality of Mine discharge. This location is selected to monitor effluent discharge in to Jamunia.

3.2 Methodology of sampling and analysis

Water samples were collected as per standard practice. The effluent samples were collected and analyzed for four parameters on fortnightly basis at the Environmental Laboratory of CMPDI RI-II, Dhanbad.


3.3 Results & Interpretations

The results are given in tabular form along with the applicable standards. Results are compared with Schedule - VI, effluent prescribed by MoEF&CC. Results show that most of the parameters are within the permissible limits.

WATER QUALITY DATA **(EFFLUENT WATER- FOUR PARAMETERS)**

Name of the Cluster: Cluster -XIII		Month: NOV, 2019	Name of the Station: Mine Discharge of Murlidih 20/21	
Sl. No.	Parameters	MW13 First Fortnight	MW13 Second Fortnight	As per MOEF General Standards for schedule VI
		01.11.2019	29.11.2019	
1	Total Suspended Solids	38	43	100 (Max)
2	pH	8.13	8.21	5.5 - 9.0
3	Oil & Grease	<2.0	<2.0	10 (Max)
4	COD	52	44	250 (Max)

All values are expressed in mg/lit unless specified.


 Analysed By
 JSA/SA/SSA


 Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad


 Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

NOISE LEVEL QUALITY MONITORING

4.1 Location of sampling sites

- i) Murlidih (N19)
- ii) Lohapatti (N20)
- iii) Kharkharee CISF Office (N21)
- iv) Dumarda (N31)

4.2 Methodology of sampling and analysis

Noise level measurements in form of 'L_{EQ}' were taken using Integrated Data Logging Sound Level Meter (NL-52 OF RION CO. Ltd. Make) during day time. Noise levels were measured for about one hour time in day time. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB (A).

4.3 Results & Interpretations

Ambient noise levels were recorded during day time and the observed values were compared with standards prescribed by MoEFCC. The results of Noise levels recorded during day time on fortnightly basis are presented in tabular form along with the applicable standard permissible limits. The observed values in terms of L_{EQ} are presented. The observed values at all the monitoring locations are found to be within permissible limits.

NOISE LEVEL DATA

Name of the Project: Cluster -XIII			Month: NOV. , 2019		
Sl. No.	Station Name/Code	Category of area	Date	Noise level dB(A)LEQ	*Permissible Limit of Noise level in dB(A)
1	Murlidih 20/21 (N19)	Industrial area	14.11.19	59.2	75
2	Murlidih 20/21	Industrial area	29.11.19	56.3	75
3	Lohapatti (N20)	Industrial area	13.11.19	61.2	75
4	Lohapatti	Industrial area	28.11.19	61.2	75
5	Kharkharee (N21)	Industrial area	06.11.19	57.4	75
6	Kharkharee	Industrial area	21.11.19	57.3	75
7	Dumarda (N31)	Residential area	14.11.19	49.3	55
8	Dumarda	Residential area	29.11.19	49.1	55

*Permissible limits of Noise Level as per MOEF Gazette Notification No. GSR 742(E) dt. 25.09.2000 Standards for Coal Mines and Noise Pollution (Regulation and Control) Rules, 2000.

* Day Time: 6.00 AM to 10.00 PM,

अनुमन उद्ध रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अतिर
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

Ambient Air Quality Standards for Jharia Coal Field
As per the Environment (Protection) Amendment Rules, 2000 notified vide
notification G.S.R. 742(E), dated 25.9.2000.

Category	Pollutant	Time weighted average	Concentration in Ambient Air	Method of Measurement
1	2	3	4	5
III Coal mines located in the coal fields of <ul style="list-style-type: none"> • Jharia • Raniganj • Bokaro 	Suspended Particulate Matter (SPM)	Annual Average * 24 hours **	500 $\mu\text{g}/\text{m}^3$ 700 $\mu\text{g}/\text{m}^3$	- High Volume Sampling (Average flow rate not less than 1.1
	Respirable Particulate Matter (size less than 10 μm) (RPM)	Annual Average * 24 hours **	250 $\mu\text{g}/\text{m}^3$ 300 $\mu\text{g}/\text{m}^3$	Respirable Particulate Matter sampling and analysis
	Sulphur Dioxide (SO_2)	Annual Average * 24 hours **	80 $\mu\text{g}/\text{m}^3$ 120 $\mu\text{g}/\text{m}^3$	1.Improvedwest and Gaeke method 2.Ultraviolet fluorescene
	Oxide of Nitrogen as NO_2	Annual Average * 24 hours **	80 $\mu\text{g}/\text{m}^3$ 120 $\mu\text{g}/\text{m}^3$	1. Jacob &Hochheiser Modified (Na-Arsenic) Method 2. Gas phase Chemilumine-scence

Note:

* Annual Arithmetic mean for the measurements taken in a year, following the guidelines for frequency of sampling laid down in clause2.

** 24hourly/8hourlyvalueshallbemmet92%ofthetimeinayear.However,8% of the time it AUGUST exceed but not on two consecutivedays.

STRICTLY RESTRICTED**FOR COMPANY USE ONLY RESTRICTED**

The information given in this report is not to be communicated either directly or indirectly to the press or to any person not holding an official position in the CIL /GOVERNMENT.

**ENVIRONMENTAL MONITORING REPORT
OF
BHARAT COKING COAL LIMITED,
CLUSTER – XIII**

(FOR THE MONTH DECEMBER, 2019)

E. C. no. J-11015/11/2010-IA.II (M) dated 06.06.2013-




CMPDI

ISO 9001 Company
**Regional Institute-II
Dhanbad, Jharkhand**


AMBIENT AIR QUALITY DATA

Cluster –XIII, Bharat Coking Coal limited
Month: DEC. 2019
Year : 2019-20.

Station Name: A19 – Murlidih 20/21		Zone: Core		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	12.12.19	96	54	12.37	23.56
2	30.12.19	104	58	11.31	22.52
	NAAQ Standards	100	60	80	80



Station Name: A20, Lohapatti		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	13.12.19	98	56	11.16	21.99
2	27.12.19	94	51	12.94	23.35
	NAAQ Standard	100	60	80	80




Analysed By
 JSA/SA/SSA


Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad

Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

Station Name: A21 Kharkharee		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	03.12.19	90	49	12.08	21.73
2	25.12.19	88	45	11.66	22.63
	NAAQ Standards	100	60	80	80



Station Name: A31 Dumarda		Zone: Buffer		Category: Residential	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	12.12.19	92	51	8.72	19.56
2	30.12.19	97	53	9.50	20.40
	NAAQ Standards	100	60	80	80



- All values are expressed in microgram per cubic meter.
- 24 hours duration

अनिल कुमार रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

WATER quality monitoring

3.1 Location of sampling sites

(Refer **Plate No. – II**)

i) **Mine Discharge of Murlidih 20/21 (MW13)**

A sampling point is fixed to assess the effluent quality of Mine discharge. This location is selected to monitor effluent discharge in to Jamunia.

3.2 Methodology of sampling and analysis

Water samples were collected as per standard practice. The effluent samples were collected and analyzed for four parameters on fortnightly basis at the Environmental Laboratory of CMPDI RI-II, Dhanbad.


3.3 Results & Interpretations

The results are given in tabular form along with the applicable standards. Results are compared with Schedule - VI, effluent prescribed by MoEF&CC. Results show that most of the parameters are within the permissible limits.

WATER QUALITY DATA **(EFFLUENT WATER- FOUR PARAMETERS)**

Name of the Cluster: Cluster -XIII		Month: DEC, 2019	Name of the Station: Mine Discharge of Murlidih 20/21	
Sl. No.	Parameters	MW13 First Fortnight	MW13 Second Fortnight	As per MOEF General Standards for schedule VI
		11.12.19	30.12.19	
1	Total Suspended Solids	31	36	100 (Max)
2	pH	8.11	8.06	5.5 - 9.0
3	Oil & Grease	<2.0	<2.0	10 (Max)
4	COD	60	48	250 (Max)

All values are expressed in mg/lit unless specified.


 Analysed By
 JSA/SA/SSA


 Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad


 Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

NOISE LEVEL QUALITY MONITORING

4.1 Location of sampling sites

- i) Murlidih (N19)
- ii) Lohapatti (N20)
- iii) Kharkharee CISF Office (N21)
- iv) Dumarda (N31)

4.2 Methodology of sampling and analysis

Noise level measurements in form of 'L_{EQ}' were taken using Integrated Data Logging Sound Level Meter (NL-52 OF RION CO. Ltd. Make) during day time. Noise levels were measured for about one hour time in day time. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB (A).

4.3 Results & Interpretations

Ambient noise levels were recorded during day time and the observed values were compared with standards prescribed by MoEFCC. The results of Noise levels recorded during day time on fortnightly basis are presented in tabular form along with the applicable standard permissible limits. The observed values in terms of L_{EQ} are presented. The observed values at all the monitoring locations are found to be within permissible limits.

NOISE LEVEL DATA

Name of the Project: Cluster -XIII			Month: DEC. , 2019		
Sl. No.	Station Name/Code	Category of area	Date	Noise level dB(A)LEQ	*Permissible Limit of Noise level in dB(A)
1	Murlidih 20/21 (N19)	Industrial area	12.12.19	57.6	75
2	Murlidih 20/21	Industrial area	30.12.19	56.4	75
3	Lohapatti (N20)	Industrial area	13.12.19	65.4	75
4	Lohapatti	Industrial area	27.12.19	63.7	75
5	Kharkharee (N21)	Industrial area	03.12.19	54.1	75
6	Kharkharee	Industrial area	25.12.19	53.4	75
7	Dumarda (N31)	Residential area	12.12.19	53.4	55
8	Dumarda	Residential area	30.12.19	49.1	55

**Permissible limits of Noise Level as per MOEF Gazette Notification No. GSR 742(E) dt. 25.09.2000 Standards for Coal Mines and Noise Pollution (Regulation and Control) Rules, 2000.*

** Day Time: 6.00 AM to 10.00 PM,*

अनुमन उद्ग रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

STRICTLY RESTRICTED**FOR COMPANY USE ONLY RESTRICTED**

The information given in this report is not to be communicated either directly or indirectly to the press or to any person not holding an official position in the CIL /GOVERNMENT.

ENVIRONMENTAL MONITORING REPORT OF BHARAT COKING COAL LIMITED, CLUSTER – XIII

(FOR THE MONTH JANUARY, 2020)

E. C. no. J-11015/11/2010-IA.II (M) dated 06.06.2013-




CMPDI


ISO 9001 Company
Regional Institute-II
Dhanbad, Jharkhand

AMBIENT AIR QUALITY DATA**Cluster –XIII, Bharat Coking Coal limited****Month: JAN. 2020****Year : 2019-20.**

Station Name: A19 – Murlidih 20/21		Zone: Core		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	14.01.2020	95	56	12	22
2	29.01.2020	92	51	11	20
	NAAQ Standards	100	60	80	80



Station Name: A20, Lohapatti		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	15.01.2020	94	55	11	22
2	22.01.2020	89	52	11	20
	NAAQ Standard	100	60	80	80




अमान उद्ग रावुन
Analysed By
JSA/SA/SSA


Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

Station Name: A21 Kharkharee		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	07.01.2020	96	57	13	22
2	23.01.2020	94	52	11	22
	NAAQ Standards	100	60	80	80



Station Name: A31 Dumarda		Zone: Buffer		Category: Residential	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	14.01.2020	94	53	9	18
2	29.01.2020	96	54	9	19
	NAAQ Standards	100	60	80	80



- All values are expressed in microgram per cubic meter.
- 24 hours duration

अनिल कुमार रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

WATER quality monitoring

3.1 Location of sampling sites

(Refer **Plate No. – II**)

i) **Mine Discharge of Murlidih 20/21 (MW13)**

A sampling point is fixed to assess the effluent quality of Mine discharge. This location is selected to monitor effluent discharge in to Jamunia.

3.2 Methodology of sampling and analysis

Water samples were collected as per standard practice. The effluent samples were collected and analyzed for four parameters on fortnightly basis at the Environmental Laboratory of CMPDI RI-II, Dhanbad.


3.3 Results & Interpretations

The results are given in tabular form along with the applicable standards. Results are compared with Schedule - VI, effluent prescribed by MoEF&CC. Results show that most of the parameters are within the permissible limits.

WATER QUALITY DATA **(EFFLUENT WATER- FOUR PARAMETERS)**

Name of the Cluster: Cluster -XIII		Month: JAN, 2020	Name of the Station: Mine Discharge of Murlidih 20/21	
Sl. No.	Parameters	MW13 First Fortnight	MW13 Second Fortnight	As per MOEF General Standards for schedule VI
		14.01.2020	29.01.2020	
1	Total Suspended Solids	32	30	100 (Max)
2	pH	8.16	8.02	5.5 - 9.0
3	Oil & Grease	<2.0	<2.0	10 (Max)
4	COD	60	56	250 (Max)

All values are expressed in mg/lit unless specified.


 Analysed By
 JSA/SA/SSA


 Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad


 Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

NOISE LEVEL QUALITY MONITORING

4.1 Location of sampling sites

- i) Murlidih (N19)
- ii) Lohapatti (N20)
- iii) Kharkharee CISF Office (N21)
- iv) Dumarda (N31)

4.2 Methodology of sampling and analysis

Noise level measurements in form of 'L_{EQ}' were taken using Integrated Data Logging Sound Level Meter (NL-52 OF RION CO. Ltd. Make) during day time. Noise levels were measured for about one hour time in day time. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB (A).

4.3 Results & Interpretations

Ambient noise levels were recorded during day time and the observed values were compared with standards prescribed by MoEFCC. The results of Noise levels recorded during day time on fortnightly basis are presented in tabular form along with the applicable standard permissible limits. The observed values in terms of L_{EQ} are presented. The observed values at all the monitoring locations are found to be within permissible limits.

NOISE LEVEL DATA

Name of the Project: Cluster -XIII			Month: JAN, 2020		
Sl. No.	Station Name/Code	Category of area	Date	Noise level dB(A)LEQ	*Permissible Limit of Noise level in dB(A)
1	Murlidih 20/21 (N19)	Industrial area	14.01.2020	52.3	75
2	Murlidih 20/21	Industrial area	29.01.2020	57.3	75
3	Lohapatti (N20)	Industrial area	15.01.2020	60.2	75
4	Lohapatti	Industrial area	22.01.2020	65.8	75
5	Kharkharee (N21)	Industrial area	07.01.2020	53.2	75
6	Kharkharee	Industrial area	23.01.2020	54.6	75
7	Dumarda (N31)	Residential area	14.01.2020	51.6	55
8	Dumarda	Residential area	29.01.2020	47.1	55

**Permissible limits of Noise Level as per MOEF Gazette Notification No. GSR 742(E) dt. 25.09.2000 Standards for Coal Mines and Noise Pollution (Regulation and Control) Rules, 2000.*

** Day Time: 6.00 AM to 10.00 PM,*

अनुमन उद्ग रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

STRICTLY RESTRICTED**FOR COMPANY USE ONLY RESTRICTED**

The information given in this report is not to be communicated either directly or indirectly to the press or to any person not holding an official position in the CIL /GOVERNMENT.

ENVIRONMENTAL MONITORING REPORT OF BHARAT COKING COAL LIMITED, CLUSTER – XIII

(FOR THE MONTH FEBRUARY, 2020)

E. C. no. J-11015/11/2010-IA.II (M) dated 06.06.2013-



CMPDI

ISO 9001 Company
Regional Institute-II
Dhanbad, Jharkhand


AMBIENT AIR QUALITY DATA

Cluster –XIII, Bharat Coking Coal limited


Month: FEB. 2020

Year : 2019-20.

Station Name: A19 – Murlidih 20/21		Zone: Core		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	12.02.2020	94	52	11	22
2	21.02.2020	91	49	13	21
	NAAQ Standards	100	60	80	80



Station Name: A20, Lohapatti		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	07.02.2020	92	51	11	21
2	20.02.2020	96	53	12	23
	NAAQ Standard	100	60	80	80




अनुमन उद्ग रावत
Analysed By
JSA/SA/SSA


Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

Station Name: A21 Kharkharee		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	13.02.2020	98	57	11	23
2	19.02.2020	117	66	11	22
	NAAQ Standards	100	60	80	80



Station Name: A31 Dumarda		Zone: Buffer		Category: Residential	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	12.02.2020	91	49	7	18
2	21.02.2020	97	53	9	19
	NAAQ Standards	100	60	80	80



- All values are expressed in microgram per cubic meter.
- 24 hours duration

अनिल कुमार रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

WATER quality monitoring

3.1 Location of sampling sites

(Refer **Plate No. – II**)

i) **Mine Discharge of Murlidih 20/21 (MW13)**

A sampling point is fixed to assess the effluent quality of Mine discharge. This location is selected to monitor effluent discharge in to Jamunia.

3.2 Methodology of sampling and analysis

Water samples were collected as per standard practice. The effluent samples were collected and analyzed for four parameters on fortnightly basis at the Environmental Laboratory of CMPDI RI-II, Dhanbad.


3.3 Results & Interpretations

The results are given in tabular form along with the applicable standards. Results are compared with Schedule - VI, effluent prescribed by MoEF&CC. Results show that most of the parameters are within the permissible limits.

WATER QUALITY DATA **(EFFLUENT WATER- FOUR PARAMETERS)**

Name of the Cluster: Cluster -XIII		Month: FEB, 2020	Name of the Station: Mine Discharge of Murlidih 20/21	
Sl. No.	Parameters	MW13 First Fortnight	MW13 Second Fortnight	As per MOEF General Standards for schedule VI
		12.02.2020	22.02.2020	
1	Total Suspended Solids	31	34	100 (Max)
2	pH	8.07	8.12	5.5 - 9.0
3	Oil & Grease	<2.0	<2.0	10 (Max)
4	COD	44	40	250 (Max)

All values are expressed in mg/lit unless specified.


 Analysed By
 JSA/SA/SSA


 Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad


 Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

NOISE LEVEL QUALITY MONITORING

4.1 Location of sampling sites

- i) Murlidih (N19)
- ii) Lohapatti (N20)
- iii) Kharkharee CISF Office (N21)
- iv) Dumarda (N31)

4.2 Methodology of sampling and analysis

Noise level measurements in form of 'L_{EQ}' were taken using Integrated Data Logging Sound Level Meter (NL-52 OF RION CO. Ltd. Make) during day time. Noise levels were measured for about one hour time in day time. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB (A).

4.3 Results & Interpretations

Ambient noise levels were recorded during day time and the observed values were compared with standards prescribed by MoEFCC. The results of Noise levels recorded during day time on fortnightly basis are presented in tabular form along with the applicable standard permissible limits. The observed values in terms of L_{EQ} are presented. The observed values at all the monitoring locations are found to be within permissible limits.

NOISE LEVEL DATA

Name of the Project: Cluster -XIII			Month: FEB , 2020		
Sl. No.	Station Name/Code	Category of area	Date	Noise level dB(A)LEQ	*Permissible Limit of Noise level in dB(A)
1	Murlidih 20/21 (N19)	Industrial area	12.02.2020	52.6	75
2	Murlidih 20/21	Industrial area	21.02.2020	58.4	75
3	Lohapatti (N20)	Industrial area	07.02.2020	60.2	75
4	Lohapatti	Industrial area	20.02.2020	61.8	75
5	Kharkharee (N21)	Industrial area	13.02.2020	51.7	75
6	Kharkharee	Industrial area	19.02.2020	54.2	75
7	Dumarda (N31)	Residential area	12.02.2020	50.6	55
8	Dumarda	Residential area	21.02.2020	50.7	55

**Permissible limits of Noise Level as per MOEF Gazette Notification No. GSR 742(E) dt. 25.09.2000 Standards for Coal Mines and Noise Pollution (Regulation and Control) Rules, 2000.*

** Day Time: 6.00 AM to 10.00 PM,*

अनुमन उद्ग रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

STRICTLY RESTRICTED**FOR COMPANY USE ONLY RESTRICTED**

The information given in this report is not to be communicated either directly or indirectly to the press or to any person not holding an official position in the CIL /GOVERNMENT.

**ENVIRONMENTAL MONITORING REPORT
OF
BHARAT COKING COAL LIMITED,
CLUSTER – XIII**

(FOR THE MONTH MARCH, 2020)

E. C. no. J-11015/11/2010-IA.II (M) dated 06.06.2013-



CMPDI

ISO 9001 Company
**Regional Institute-II
Dhanbad, Jharkhand**


AMBIENT AIR QUALITY DATA

Cluster –XIII, Bharat Coking Coal limited


Month: MAR. 2020

Year : 2019-20.

Station Name: A19 – Murlidih 20/21		Zone: Core		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	04.03.2020	92	50	12	22
2	18.03.2020	96	52	11	20
	NAAQ Standards	100	60	80	80



Station Name: A20, Lohapatti		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO ₂	NO _x
1	13.03.2020	109	63	11	21
2	20.03.2020	92	54	11	21
	NAAQ Standard	100	60	80	80




अनुमन उद्ध रावत
Analysed By
JSA/SA/SSA


Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

Station Name: A21 Kharkharee		Zone: Buffer		Category: Industrial	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	04.03.2020	119	69	11	22
N/A –Due to Nationwide Lockdown					
	NAAQ Standards	100	60	80	80



Station Name: A31 Dumarda		Zone: Buffer		Category: Residential	
Sl. No.	Dates of sampling	PM 10	PM 2.5	SO2	NOx
1	13.03.2020	79	41	8	19
2	18.03.2020	83	45	9	19
	NAAQ Standards	100	60	80	80



- All values are expressed in microgram per cubic meter.
- 24 hours duration

अनुराग रावत
Analysed By
JSA/SA/SSA

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad

अमित
Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

WATER quality monitoring

3.1 Location of sampling sites

(Refer **Plate No. – II**)

i) **Mine Discharge of Murlidih 20/21 (MW13)**

A sampling point is fixed to assess the effluent quality of Mine discharge. This location is selected to monitor effluent discharge in to Jamunia.

3.2 Methodology of sampling and analysis

Water samples were collected as per standard practice. The effluent samples were collected and analyzed for four parameters on fortnightly basis at the Environmental Laboratory of CMPDI RI-II, Dhanbad.


3.3 Results & Interpretations

The results are given in tabular form along with the applicable standards. Results are compared with Schedule - VI, effluent prescribed by MoEF&CC. Results show that most of the parameters are within the permissible limits.

WATER QUALITY DATA **(EFFLUENT WATER- FOUR PARAMETERS)**

Name of the Cluster: Cluster -XIII		Month: MAR, 2020	Name of the Station: Mine Discharge of Murlidih 20/21	
Sl. No.	Parameters	MW13 First Fortnight 13.03.2020	MW13 Second Fortnight 19.03.2020	As per MOEF General Standards for schedule VI
1	Total Suspended Solids	34	38	100 (Max)
2	pH	8.13	7.99	5.5 - 9.0
3	Oil & Grease	<2.0	<2.0	10 (Max)
4	COD	52	48	250 (Max)

All values are expressed in mg/lit unless specified.


 Analysed By
 JSA/SA/SSA


 Checked By
 Lab In Charge
 RI-2, CMPDI, Dhanbad


 Approved By
 HOD(In-charge) Environment
 RI-2, CMPDI, Dhanbad

NOISE LEVEL QUALITY MONITORING

4.1 Location of sampling sites

- i) Murlidih (N19)
- ii) Lohapatti (N20)
- iii) Kharkharee CISF Office (N21)
- iv) Dumarda (N31)

4.2 Methodology of sampling and analysis

Noise level measurements in form of 'L_{EQ}' were taken using Integrated Data Logging Sound Level Meter (NL-52 OF RION CO. Ltd. Make) during day time. Noise levels were measured for about one hour time in day time. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB (A).

4.3 Results & Interpretations

Ambient noise levels were recorded during day time and the observed values were compared with standards prescribed by MoEFCC. The results of Noise levels recorded during day time on fortnightly basis are presented in tabular form along with the applicable standard permissible limits. The observed values in terms of L_{EQ} are presented. The observed values at all the monitoring locations are found to be within permissible limits.

NOISE LEVEL DATA

Name of the Project: Cluster -XIII			Month: MAR, 2020		
Sl. No.	Station Name/Code	Category of area	Date	Noise level dB(A)LEQ	*Permissible Limit of Noise level in dB(A)
1	Murlidih 20/21 (N19)	Industrial area	04.03.2020	54.6	75
2	Murlidih 20/21	Industrial area	18.03.2020	55.8	75
3	Lohapatti (N20)	Industrial area	13.03.2020	64.8	75
4	Lohapatti	Industrial area	20.03.2020	67.1	75
5	Kharkharee (N21)	Industrial area	04.03.2020	53.1	75
6	Kharkharee	Industrial area	N/A –Due to Nationwide Lockdown		
7	Dumarda (N31)	Residential area	13.03.2020	51.9	55
8	Dumarda	Residential area	18.03.2020	53.5	55

**Permissible limits of Noise Level as per MOEF Gazette Notification No. GSR 742(E) dt. 25.09.2000 Standards for Coal Mines and Noise Pollution (Regulation and Control) Rules, 2000.*

** Day Time: 6.00 AM to 10.00 PM,*

अनिल कुमार राय

Analysed By
JSA/SA/SSA


✓

Checked By
Lab In Charge
RI-2, CMPDI, Dhanbad


अमित

Approved By
HOD(In-charge) Environment
RI-2, CMPDI, Dhanbad

Location of Air & Noise Monitoring Stations in BCCL



Water Sampling Locations in BCCL



INDEX

Cluster	Surface Water (US, DS)	Name of River Nala / Jore	Mine/ Effluent Water	Sampling Location	Ground Water	Sampling Location
I	SW1, SW2	Jamunia River	MW1	Damoda Area	GW1	Chitway Village
II	SW3, SW4	Khudra Nala	MW2	Block II OCP	GW2	Joyrampur Village
III	SW4, SW5, SW6, SW7	Khudra Nala, Bagdigi Nala	MW3	Govindpur Colliery	GW3	Jogdih Village
IV	SW8, SW11, SW9, SW10	Kanti River, Kurnai Jore	MW4	Chotudih	GW4	Kankanee Village
V	SW12, SW13, SW15	Jarian Nala, Ekra Nala	MW5	Muddih	GW5	Nichitpur
VI	SW14, SW15	Ekra Nala	MW6	East Bassuria UGP	GW6	Bansjora Borewell
VII	SW16, SW17	Kanti Jore	MW7	Bansjora UGP	GW7	Humladih
VIII	SW18, SW19	Kashi Jore	MW8	Dobani UGP	GW8	Ghanudih
IX	SW19, SW20	Kashi Jore	MW9	Jeenagora	GW9	Lodna
X	SW21, SW22	Damodar River	MW10	Bhowrah North	GW10	Bhowrah South
XI	SW23, SW24, SW25, SW26	Jarian Nala, Damodar River	MW11	Bhagbandh UGP	GW11	Bhagbandh
XII	SW27, SW28	Kanti River	MW12	Kapuria	GW12	Kapuria
XIII	SW29, SW30	Damodar River	MW13	Murudih (20/21)	GW13	Murudih
XIV	SW31, SW32	Damodar River	MW14	Lohapatti	GW14	Lohapatti
XV	SW33, SW34	Khudra Nala	MW15	Kharkharree UGP	GW15	Kharkharree
XVI	SW35, SW36	Khudra River	MW16	Dahiban OCP	GW16	Pallabani Village
XVII	SW37, SW38	Barakar River	MW17	Damagoria Colliery	GW17	Chaptoria

HoD (Env.)
Bharat Coking Coal Limited
(Signature)


Regional Officer, Dhanbad
Jharkhand State Pollution Control Board
(Signature)

Legend

- Sampling Locations of Surface Water (Upstream/ Downstream)
- Sampling Locations of Mine Water
- Sampling Locations of Ground/ Drinking Water

Customer	BHARAT COKING COAL LIMITED
Title	WATER SAMPLING LOCATIONS
Subject	MONITORING STATIONS
CMPII	Scale: Not to Scale

**Land Restoration / Reclamation Monitoring of Clusters of
(Opencast + Underground) Coal Mines of Bharat Coking Coal
Limited based on Satellite Data for the Year 2018**



Submitted to
Bharat Coking Coal Limited



cmpdi
A Mini-Ratna Company

**Land Restoration / Reclamation Monitoring of Clusters of
(Opencast + Underground) Coal Mines of Bharat Coking
Coal Limited based on Satellite Data for the Year 2018**

March-2019



**Remote Sensing Cell
Geomatics Division
CMPDI, Ranchi**

CONTENTS

Executive Summary	iii
--------------------------------	------------

1. Background	1
2. Objective	2
3. Methodology	2
4. Land Reclamation Status in Bharat Coking Coal Ltd	6

List of Tables

Table 1 Cluster wise Land Reclamation Status.....	v
Table 2 Area Statistics of Land Use Classes in Clusters	7

List of Figures

Fig. 1 Cluster wise Land Reclamation Status-2018 (BCCL)	vi
Fig. 2 Methodology of Land Reclamation Monitoring	3
Fig. 3 Land Reclamation status of Cluster I	12
Fig. 4 Land Reclamation status of Cluster IV	12
Fig. 5 Land Reclamation status of Cluster VII	13
Fig. 6 Land Reclamation status of Cluster X.....	13

List of Plates

Plate 1 Land Use Map of Cluster I	8
Plate 2 Land Use Map of Cluster IV	9
Plate 3 Land Use Map of Cluster VII	10
Plate 4 Land Use Map of Cluster X.....	11

List of Photographs

Photo 1 Ecological Restoration Site, Damoda Colliery, Cluster I.....	14
Photo 2 Ecological Restoration Site in Cluster IV	14
Photo 3 Ecological Restoration Site in Cluster VII	15
Photo 4 Plantation on OB in Cluster X.....	15

Executive Summary

1. **Project** Land restoration / reclamation monitoring of clusters of (Opencast + Underground) coal mines of Bharat Coking Coal Ltd. (BCCL), based on satellite data, on every three year basis.
2. **Objective** Objective of the land restoration / reclamation monitoring is to assess the area of backfilled, plantation, social forestry, active mining area, water bodies, and distribution of wasteland, agricultural land and forest in the leasehold area of the project. This will help in assessing the progressive status of mined land reclamation and to take up remedial measures, if any, required for environmental protection.
3. **Salient Findings**
 - Four Clusters viz. I, IV, VII, X were selected in 2018-19 for land reclamation/restoration monitoring. These clusters consist of mainly opencast mines.
 - Out of the total leasehold area of 5883.96 Ha., total mined out area is only 1075.76 Ha., belonging to the OC mines.
 - It is evident from the analysis that 58.11% of excavated area is under technical reclamation and 35.02% of the excavated area is under active mining. Cluster wise details are given in Table-1 & Fig-1.
 - 13.61% of total leasehold area has come under plantation (% green cover)
 - Study reveals that out of total mine leasehold area of 5883.96 Ha. of the above mentioned 04 nos. clusters of BCCL taken up for the land reclamation monitoring during the year 2018-19; total excavated area is 1075.76 Ha. (18.28%) out of which 73.92 Ha. (6.87%) has been planted (*Biologically Reclaimed*), 625.15 Ha. (58.11%) is under backfilling (*Technical Reclamation*) and

balance 376.69 Ha. (35.02%) is under active mining

- This report and the findings will act as the basis for further monitoring and reclamation related activities.
- Out of the four clusters of BCCL, maximum land reclamation has been done in Cluster VII (76.09%) followed by Cluster X (71.00%).

Table 1

Land Reclamation Status in Clusters of (Underground + Opencast) Projects of BCCL based on Satellite Data of the Year 2018

(Area in Hectare)										
Sl. No.	Cluster No.	Total Leasehold Area	Technical Reclamation Area under Backfilling	Plantation			Area under Active Mining	Total Excavated Area	Total Area under Plantation (% Green Cover)	Total Area under Reclamation
				Biological Reclamation	Other Plantations					
				Plantation on Excavated / Backfilled Area	Plantation on External Over Burden Dumps	Social Forestry, Avaneue Plantation Etc.				
1	2	3	4	5	6	7	8	9 (=4+5+8)	10 (=5+6+7)	11(=4+5)
1	Cluster I	575.00	10.11	7.29	47.99	25.53	28.39	45.78	80.80	17.40
			22.08%	15.91%			62.00%		14.05%	38.00%
2	Cluster IV	1123.79	147.22	0.00	27.11	165.09	166.67	313.88	192.20	147.22
			46.90%	0.00%			53.10%		17.10%	46.90%
3	Cluster VII	2127.70	351.54	37.47	15.52	238.67	122.23	511.24	291.67	389.01
			68.76%	7.33%			23.91%		13.71%	76.09%
4	Cluster X	2057.47	116.28	29.16	66.09	140.75	59.41	204.86	236.00	145.44
			56.76%	14.23%			29.00%		11.47%	71.00%
	TOTAL	5883.96	625.15	73.92	156.71	570.04	376.69	1075.76	800.66	699.07
			58.11%	6.87%			35.02%	18.28%	13.61%	64.98%
(% is calculated with respect to Excavated Area as applicable)										

Note: In reference of the above Table, different parameters are classified as follows:

1. Area under Biological Reclamation includes Areas under Plantation done on Backfilled Area Only.
2. Area under Technical Reclamation includes Area under Barren Backfilling only
3. Area under Active Mining Includes Coal Quarry, Advance Quarry Site and Quarry filled with water etc., if any.
4. Social Forestry and Plantation on External OB Dumps are not included in Biological Reclamation and are put under separate categories as shown in the above Table.
5. (%) calculated in the above Table is in respect to Total Excavated Area except for "Total Area under Plantation" where % is in terms of "Leasehold Area".




Fig. 1: Cluster wise Land Reclamation Status-2018 (BCCL)

1. Background

- 1.1** Land is the most important natural resource which embodies soil, water, flora, fauna and total ecosystem. All human activities are based on the land which is the scarcest natural resource in our country. Mining is a site specific industry and it could not be shifted anywhere else from the location where mineral occurs. It is a fact that surface mining activities do affect the land environment due to ground breaking. Therefore, there is an urgent need to reclaim and restore the mined out land for its productive use for sustainable development of mining. This will not only mitigate environmental degradation, but would also help in creating a more congenial environment for land acquisition by coal companies in future.
- 1.2** Keeping above in view, Coal India Ltd. (CIL) issued a work order vide letter no. CIL/WBP/ENV/2017/DP/8391 dated 22.06.2017 to Central Mine Planning & Design Institute (CMPDI), Ranchi, for monitoring of clusters with coal mines (both underground and open cast projects) having less than 5 million m³ per annum capacity (Coal +OB) at an interval of three years based on remote sensing satellite data for sustainable development of mining. Earlier, CMPDI used to carry out land reclamation monitoring for individual projects of less than 5 million capacity, but from 2018 the same will be carried out cluster wise for mines of ECL & BCCL. For operational reasons and convenience, underground and opencast mines (often with multiple overlapping seams), have now been clustered together. The result of land reclamation status of all such mines are hosted on the website of CIL, (www.coalindia.in), CMPDI (www.cmpdi.co.in) and the concerned coal companies in public domain. Detailed report is submitted to Coal India and respective subsidiaries.

- 1.3** Land reclamation monitoring of all cluster coal mining projects would also comply the statutory requirements of Ministry of Environment & Forest (MoEF). Such monitoring would not only facilitate in taking timely mitigation measures against environmental degradation, but would also enable coal companies to utilize the reclaimed land for larger socio-economic benefits in a planned way.
- 1.4** Present report is embodying the finding of the study based on satellite data of the year 2018 carried out for four clusters of mines comprising both underground and OC projects for Bharat Coking Coal Ltd.

2. Objective

Objective of the land reclamation/restoration monitoring is to assess the area of backfilled, plantation, OB dumps, social forestry, active mining area, settlements and water bodies, distribution of wasteland, agricultural land and forest land in the leasehold area of the project. This is an important step taken up for assessing the progressive status of mined land reclamation and for taking up remedial measures, if any, required for environmental protection.

3. Methodology

There are number of steps involved between raw satellite data procurement and preparation of final map. National Remote Sensing Centre (NRSC) Hyderabad, being the nodal agency for satellite data supply in India, provides only raw digital satellite data, which needs further digital image processing for extracting the information and map preparation before uploading the same in the website. Methodology for land reclamation monitoring is given in fig 2. Following steps are involved in land reclamation /restoration monitoring:




Fig. 2: Methodology of Land Reclamation Monitoring

3.1 Data Procurement: After browsing the data quality and date of pass on internet, supply order for data is placed to NRSC. Secondary data like leasehold boundary, toposheet are procured for creation of vector database.

3.2 Satellite Data Processing: Satellite data are processed using ERDAS IMAGINE digital image processing s/w. Methodology involves the following major steps:

- **Rectification & Geo-referencing:** Inaccuracies in digital imagery may occur due to 'systematic errors' attributed to earth curvature and rotation as well as 'non-systematic errors' attributed to satellite receiving station itself. Raw digital images contain geometric distortions, which make them

unusable as maps. Therefore, geo-referencing is required for correction of image data using ground control points (GCP) to make it compatible to Sol toposheet.

- **Image enhancement:**

To improve the interpretability of the raw data, image enhancement is necessary. Local operations modify the value of each pixel based on brightness value of neighbouring pixels using ERDAS IMAGINE 14.0 s/w. and enhance the image quality for interpretation.

- **Training set selection**

Training set requires to be selected, so that software can classify the image data accurately. The image data are analysed based on the interpretation keys. These keys are evolved from certain fundamental image-elements such as tone/colour, size, shape, texture, pattern, location, association and shadow. Based on the image-elements and other geo-technical elements like land form, drainage pattern and physiography; training sets were selected/identified for each land use/cover class. Field survey was carried out by taking selective traverses in order to collect the ground information (or reference data) so that training sets are selected accurately in the image. This was intended to serve as an aid for classification.

- **Classification and Accuracy assessment**

Image classification is carried out using the maximum likelihood algorithm. The classification proceeds through the following steps: (a) calculation of statistics [i.e. signature generation] for the identified training areas, and (b) the decision boundary of maximum probability based on the mean vector, variance, covariance and correlation matrix of the pixels. After evaluating the statistical parameters of the training sets, reliability test of training sets is conducted by measuring the statistical separation between

the classes that resulted from computing divergence matrix. The overall accuracy of the classification was finally assessed with reference to ground truth data.

- **Area calculation**

The area of each land use class in the leasehold is determined using ERDAS IMAGINE v. 14.0 s/w.

- **Overlay of Vector data base**

Vector data base is created based on secondary data. Vector layer like drainage, railway line, leasehold boundary, forest boundary etc. are superimposed on the image as vector layer in the Arc GIS database.

- **Pre-field map preparation**

Pre-field map is prepared for validation of the classification result

3.3 Ground Truthing:

Selective ground verification of the land use classes are carried out in the field and necessary corrections if required, are incorporated before map finalization.

3.4 Land reclamation database on GIS:

Land reclamation database is created on GIS platform to identify the temporal changes identified from satellite data of different cut - of dates.

4. Land Reclamation Status in Bharat Coking Coal Ltd.

4.1 In BCCL, a total of twelve clusters of mines are selected for land reclamation monitoring. Following four clusters of mines comprising both underground and OC projects of Bharat Coking Coal Ltd. have been taken up for land reclamation monitoring in 2018.

- Cluster I (Damoda OCP)
- Cluster IV (Salanpur Colliery, Katras Choitudih Colliery, Gaslitand Colliery, Amalgamated Keshalpur West Mudidih Colliery, Angarpathra Colliery & Ramkanali Colliery)
- Cluster VII (Amalgamated East Bhuggatdih Simlabahal Colliery, Ena OC, Vishwakarma OCP, Kustore OCP)
- Cluster X (Bhowrah North, Bhowrah South, Patherdih)

4.2 All the four above clusters, have been mapped during the year 2018 for assessing the progress of land reclamation.

4.3 Area statistics of different land use classes present in OC projects till the year 2018 is given in Table 2. Land use maps derived from the satellite data are given in Plate nos.1, 2, 3 & 4. The land use status are shown in Fig. 3, 4, 5 & 6.


4.4 Study reveals that majority of the mines under the clusters considered for monitoring are of opencast type. 35.02% of excavated area is under active mining in the opencast mines. 58.11% of the excavated area have come under technical reclamation till 2018


Table 2


**Status of Land Use/Reclamation Status in Clusters of (OC + Underground) mines of
Bharat Coking Coal Limited based on Satellite Data of the year 2018**


(Area in Hectare)

			CLUSTER I		CLUSTER IV		CLUSTER VII		CLUSTER X		TOTAL	
			Area	%	Area	%	Area	%	Area	%	Area	%
FORESTS	Dense Forest		5.36	0.93	0.00	0.00	0.00	0.00	0.00	0.00	5.36	0.09
	Open Forest		29.81	5.18	0.00	0.00	0.00	0.00	180.80	8.79	210.61	3.58
	Total Forest		35.17	6.12	0.00	0.00	0.00	0.00	180.80	8.79	215.97	3.67
SCRUBS	Scrubs		194.77	33.87	154.53	13.75	618.49	29.07	559.57	27.20	1527.35	25.96
PLANTATION	Social Forestry/Avenue Plantation		25.53	4.44	165.09	14.69	238.67	11.22	140.75	6.84	570.04	9.69
	Plantation on OB Dump		47.99	8.35	27.11	2.41	15.52	0.73	66.09	3.21	156.71	2.66
	Plantation on Backfill (Biological Reclamation)		7.29	1.27	0.00	0.00	37.47	1.76	29.16	1.42	73.92	1.26
	Total Plantation		80.80	14.05	192.20	17.10	291.67	13.71	236.00	11.47	800.66	13.61
	Total Vegetation		310.75	54.04	346.73	30.85	910.15	42.78	976.37	47.45	2543.99	43.24
ACTIVE MINING	Coal Dump		5.26	0.91	20.40	1.82	16.03	0.75	2.84	0.14	44.53	0.76
	Coal Quarry		8.79	1.53	158.87	14.14	119.18	5.60	46.10	2.24	332.94	5.66
	Advance Quarry Site		3.24	0.56	0.00	0.00	0.00	0.00	0.00	0.00	3.24	0.06
	Quarry Filled With Water		16.36	2.84	7.80	0.69	3.05	0.14	13.31	0.65	40.52	0.69
	Total Area under Active Mining		28.39	4.93	166.67	14.83	122.23	5.74	59.41	2.89	376.69	6.40
	Barren OB Dump		20.58	3.58	154.32	13.73	75.79	3.56	89.57	4.35	340.25	5.78
RECLAIMED	Area Under Backfilling (Technical Reclamation)		10.11	1.76	147.22	13.10	351.54	16.52	116.28	5.65	625.15	10.62
	Total Area under Technical Reclamation		10.11	1.76	147.22	13.10	351.54	16.52	116.28	5.65	625.15	10.62
	Total Area under Mine Operation		64.33	11.19	488.60	43.48	565.59	26.58	268.10	13.03	1386.62	23.57
WASTELAND	Waste Lands		69.03	12.00	51.99	4.63	162.76	7.65	153.62	7.47	437.40	7.43
	Fly Ash Pond / Sand Body		9.94	1.73	0.00	0.00	0.00	0.00	44.69	2.17	54.63	0.93
	Total Wasteland		78.97	13.73	51.99	4.63	162.76	7.65	198.30	9.64	492.02	8.36
WATERBODIES	Reservoir, nallah, ponds		14.43	2.51	14.84	1.32	18.39	0.86	194.65	9.46	242.30	4.12
	Total Waterbodies		14.43	2.51	14.84	1.32	18.39	0.86	194.65	9.46	242.30	4.12
AGRICULTURE	Crop Lands		3.52	0.61	3.45	0.31	37.65	1.77	18.29	0.89	62.91	1.07
	Fallow Lands		79.43	13.81	34.97	3.11	20.73	0.97	91.05	4.43	226.18	3.84
	Total Agriculture		82.95	14.43	38.42	3.42	58.37	2.74	109.35	5.31	289.09	4.91
SETTLEMENTS	Urban Settlement		7.17	1.25	160.59	14.29	380.73	17.89	228.39	11.10	776.88	13.20
	Rural Settlement		13.83	2.41	22.63	2.01	9.93	0.47	57.90	2.81	104.29	1.77
	Industrial Settlement		2.58	0.45	0.00	0.00	21.79	1.02	24.42	1.19	48.80	0.83
	Total Settlement		23.58	4.10	183.21	16.30	412.45	19.38	310.71	15.10	929.96	15.80
	Grand Total		575.00	100.00	1123.79	100.00	2127.70	100.00	2057.47	100.00	5883.96	100.00












Fig. 3: Land Reclamation status of Cluster I




Fig. 4: Land Reclamation status of Cluster IV




Fig. 5: Land Reclamation status of Cluster VII




Fig. 6: Land Reclamation status of Cluster X



Photo 1: Ecological Restoration Site, Damoda Colliery, Cluster I



Photo 2: Ecological Restoration Site in Cluster IV



Photo 3: Ecological Restoration Site in Cluster VII



Photo 4: Plantation on OB in Cluster X



cmpdi
A Mini-Ratna Company

Central Mine Planning & Design Institute Ltd.

(A Subsidiary of Coal India Ltd.)

Gondwana Place, Kanke Road, Ranchi 834031, Jharkhand

Phone : (+91) 651 2230001, 2230002, 2230483, FAX (+91) 651 2231447, 2231851

Website : www.cmpdi.co.in, Email : cmpdihq@cmpdi.co.in

A. Training from Oct '19 to March'20

No of employees (Departmental & Contractual) received training in cluster XIII (Oct' 19 to March'20)	
Type of Training	Number
Refresher Training	16

A. PME from Oct' 19 to March'20

No of employees PME in cluster XIII (Oct' 19 to March'20)	
PME	Number
Murulidih 20/21 pits colliery	23

Progress Report

1st Phase Air Monitoring report for “Source apportionment of ambient air particulate matter in Jharia coalfields region, Jharkhand”

Sponsor

Bharat Coking Coal Limited (BCCL)



**CSIR-National Environmental
Engineering Research Institute,
Nagpur**

2019



Contents

1. Introduction.....	3
1.1 Project Background.....	4
1.2 Project objectives	4
2. Field visit	5
2.1 Jharia coalfield maps:	5
2.2 Site Identification:.....	7
3. Sampler Selection and Procurement	8
4. Monitoring parameters.....	9
4.1 Monitoring Frequency	10
4.2 Filter handling and Weighing:	12
5. Ambient Air Quality Monitoring	12

List of Figures

Figure 2.1 Identified air monitoring station in Jharia Coalfield	8
Figure 4.1 Glimpses of air monitoring of some locations	11

List of Tables

Table 2.1 Jharia coalfields Site visit on cluster-base	6
Table 3.1 Samplers Procured for Monitoring	8
Table 4.1 Ambient Air Quality Sampling/Analysis Methodology for Target Pollutants.....	9
Table 4.1.1 Frequency of Air pollutants sampling in Jharia Coalfield	10
Table 5.1 Physical and Chemical components for characterization of Particulate matter.....	15

1. Introduction

1.1 Project Background

Bharat Coking Coal Limited, a subsidiary of Coal India Limited, has been operating the majority of the coal mines in the Jharia coal field regions since its inception in 1972. Jharia coal mines are special for its low ash content and high calorific value coals. Therefore, they are often used directly in iron and steel plants for metal oxide reduction after washing. Although these coal mines are highly priced for their high quality coal, they are notorious for their mine fires, which causes lot of fugitive gaseous and PM emissions. Hence, Jharia region has been under scrutiny by various public authorities and common public with a vision to improve the ambient air quality.

Various sources contribute to high particular matter concentration in the Jharia region: vehicles, mining activities, re-suspended dusts, fugitive emissions, fuel oils, household LPGs, etc. The percentage contribution of these factors in the ambient depends exclusively on the economic activities of that particular region. In order to improve the existing ambient air quality, the major sources of PM emissions first need to be identified. Hence, the environmental clearance committee of MoEF has directed BCCL to conduct a source apportionment study for particulate matter. In this context, BCCL has approached CSIR-NEERI to conduct a source apportionment study of ambient air particulate matter in Jharia coalfields region in order to quantify the various sources PM emissions and suggest an effective environmental management plan.

1.2 Project objectives

The major objective of the study is to assess the current ambient air quality, sources of air pollution and propose the priorities for the actions for improvement of air quality. The study to include the entire Jharia Coalfield along with area up to 10 Km from the periphery / boundary of BCCL mines.

The detailed objectives are as following:

- i. Ambient Air Monitoring
 - ✓ Monitoring of ambient air quality at selected receptor locations for pollutants including PM₁₀, PM_{2.5}(limited), SO₂, NO_x, PAHs to establish the status of the air quality in Jharia Coalfields along with area up to 10 K.M from the periphery/boundary of BCCL mines. Also, review of the available air quality monitoring data from Central Pollution Control Board (CPCB) /Jharkhand State Pollution Control Board (JSPCB).
 - ✓ To calibrate dispersion modelling predictions using measured air quality parameters.

- ✓ To draw supportive data through specific site related monitoring regarding impact causing sources such as kerbside monitoring.
- ✓ To establish the impact of meteorological conditions on a few select indicator pollutants in different micro meteorological conditions of the Jharia Coalfields.
- ii. Emission Inventory related of Jharia Coalfields along with area up to 10 Km from the periphery / boundary of BCCL mines.
 - ✓ To identify the pollution load grid wise for point, line and area source
 - ✓ To establish possibilities of receptor level concentrations of air pollutants by matching dispersion modelling and air quality-monitoring data.
- iii. Source apportionment related
 - ✓ To identify and apportion the pollution load at receptor level to various sources in the Jharia Coalfields along with area up to 10 Km from the periphery / boundary of BCCL mines.
 - ✓ To carry out the source apportionment using molecular markers for a limited number of samples through a time resolved sample collection at various period of the day and day-of-the-week.
- iv. Any other item in consensus between both BCCL/CIL & NEERI evolved during the study.

2. Field visit

In connection with the above objectives, the NEERI's team and BCCL's team visited BCCL's Jharia coal field for 3 days from 23 September to 27 September 2018. The team covered the entire Jharia coalfield, which spans roughly 30km in length and 22 km wide in three days with the following purpose.

To identified the location for air monitoring station in entire Jharia Coal Field region.

2.1 Jharia coalfield maps:

BCCL environmental department provided the map of the Jharia region. The site visit was carried out with assistance from BCCL's team. The 15 Jharia mines coal fields were segregated into three parts and details of the visit along with mine cluster names are given in Table 2.1.




Table 2.1 Jharia coalfields Site visit on cluster-base

Based on the objectives and outcomes envisaged, the various mine areas were visited to identify sources of emissions such as dumpsite emissions, fugitive emissions, blasting emissions. Furthermore, the already existing PM monitoring sites of BCCL were also visited to explore the possibility of installing NEERI's PM monitoring stations.

2.2 Site Identification:

The Entire Jharia Coal Field (JCF) is divided into 16 clusters. Both opencast and underground mines are operational in JCF. Standard mining operations like drilling, blasting, hauling, accumulation, and transfer are the major sources of emissions and air pollution. Apart from that, a typical emission source, mine fire, is prevailing at JCF. Besides, JCF encompasses large non-mining regions, which have their own emission sources like vehicular emission in congested traffics, road dust, Power Plant emission, other industrial emissions (coke oven plants, brick kilns, stone crushers, etc.), crematoria, domestic burning, open burning etc.

Based on the preliminary field visit by CSIR-NEERI Scientists along with BCCL staffs, the following locations are selected for the establishment of Air Quality Monitoring Stations for source apportionment study;

Core Zone

1. Cluster XIV (Lohapatty) – nearby sources: Chandrapura Thermal Power Plant
2. Cluster VII (Mine rescue station)- nearby sources: Coal Mine, Industry
3. Cluster IV or Cluster V – Banssuriya or Katras
4. Cluster IX (Lodhna)
5. Cluster XI (Moonidih)
6. Cluster X (Patherdih): nearby sources: Coal Mine, Steel Industry
7. Cluster VIII (Bastacola)

Buffer Zone

8. Bank More
9. Harina
10. Bhuli
11. Sindri
12. Parbatpur Electrosteel/ Bhaga

13. Background site (Upwind & away from sources) and also secondary Data from DVC, CCL mines Sail Bokaro and Jharkhand pollution Control Board will be obtained.




Figure 2.1 Identified air monitoring station in Jharia Coalfield

3. Sampler Selection and Procurement

Standard equipment were catered for the parameter required towards ambient air particulate characterization and gaseous sampling in the initial phase of the project.

Table 3.1 Samplers Procured for Monitoring

Sampler	Brief Description of operating conditions
Fine Dust Sampler	Sampling Inlets- PM _{2.5} , PM ₁₀ and TSP Flow rate-16.7LPM
FRM Sampler	Versatile inlet configurations for PM _{2.5} , PM ₁₀ , or TSP sampling FRM quality 24-hour sampling at 16.7 LPM
Gaseous Sampler	Sampling Rate-0.5-1.0 LPM Operation time-8 hours

4. Monitoring parameters

Parameters of monitoring were decided based on the objectives of air pollution and source apportionment study. The source apportionment analysis required air monitoring for particulate matter (PM_{2.5} and PM₁₀) and its chemical speciation to develop signature profiles of pollution sources that can be used in chemical mass balance models. The analysis data could also be used to interpret the overall loading of different chemicals contributed varied sources. Monitoring included air quality attributes such as Particulate matter, Sulphur Dioxide (SO₂) and Oxides of Nitrogen as NO₂, to understand not only the regulatory compliance but also their inter-correlations with other species such as Heavy metals, EC, OC etc. Since the objective of source apportionment study is to determine the contributions from various sources such as industries, vehicular and other area sources additional parameters were also monitored such as Polycyclic Aromatic Hydrocarbons (PAHs). List of all parameters, sampling flow rate and analytical methods are provided in Table 4.1

Table 4.1 Ambient Air Quality Sampling/Analysis Methodology for Target Pollutants

Particulars	Parameters			
	PM ₁₀	PM _{2.5}	NO ₂	SO ₂
Sampling Instrument	Fine Dust Sampler & FRM Sampler	Fine Dust Sampler & FRM Sampler	APM sampler	APM sampler
Sampling Principle	Cyclonic Flow Technique	Cyclonic Flow Technique/ WINS Impactor	Chemical absorption in suitable media	Chemical absorption in suitable media
Flow rate	16.7 LPM	16.7 LPM	0.5 LPM	0.5 LPM
Sampling Period	24 hourly	24 hourly	8 hourly	8 hourly
Sampling Frequency	10 days continuous, Teflon and quartz on alternate days	10 days continuous, Teflon and quartz on alternate days	10 days continuous	10 days continuous

Analytical Instrument	Electronic Micro Balance	Electronic Micro Balance	Spectrophotometer	Spectrophotometer
Analytical Method	Gravimetric	Gravimetric	Colorimetric Improved West & Gaeke Method	Colorimetric Improved West & Gaeke Method
Minimum reportable value	5 $\mu\text{g}/\text{m}^3$	5 $\mu\text{g}/\text{m}^3$	9 $\mu\text{g}/\text{m}^3$	4 $\mu\text{g}/\text{m}^3$

4.1 Monitoring Frequency

All pollutants exhibit diurnal and seasonal variations, which have been taken into account while determining the frequency of the sampling. In order to assess the impact of the diurnal variations in source contributions for a given meteorology of the day, 24 hourly monitoring plan was envisaged (8 hourly sampling for gaseous pollutants and 24 hourly sampling for particulate matter). The field study was planned for a period of 10 days at each monitoring site for the season to represent variation in air quality. The sampling frequency details are presented in Table 4.1.

Table 4.1.1 Frequency of Air pollutants sampling in Jharia Coalfield

Parameter	Number of Days	Change of Filter/ absorbing media	Reporting
PM ₁₀	10	24 hourly, Teflon: 05 days Quartz: 05 days	24 hourly
PM _{2.5}	10	24 hourly Teflon: 05 days Quartz: 05 days	24 hourly
NO ₂	10	8 hourly	8 hourly
SO ₂	10	8 hourly	8 hourly

The glimpses of air monitoring of some locations are shown in Figure 4.1.




Figure 4.1 Glimpses of air monitoring of some locations

4.2 Filter handling and Weighing:

Teflon-membrane and quartz-fibre filter are most commonly used for chemical analysis. Each filter was individually examined prior to labelling for discoloration, pinholes, creases, separation of ring, chaff or flashing, loose material, or other defects.

Gravimetry measured the net mass on a filter by weighing the filter before and after sampling with balance in temperature and relative humidity controlled environment. To minimize particle volatilization and aerosol liquid water bias, PM_{2.5} Filters were equilibrated for 24 hours at a constant (within $\pm 5\%$) relative humidity between 30% and 40% at a constant (within $\pm 2^\circ\text{C}$) temperature between 20°C and 23°C . PM₁₀ filters were equilibrated at 20% to 45% relative humidity ($\pm 5\%$) and 15°C to 30°C temperature ($\pm 3^\circ\text{C}$).

Methods of Chemical characterization:

Sulphur dioxide (SO ₂)	: Modified West and Gaeke method
Nitrogen dioxide (NO ₂)	: Sodium Arsenite method
Suspended Particulate Matter (SPM)	: High Volume method (Gravimetric method)
Respirable suspended Particulate Matter (RSPM)	: Gravimetrically with GFA/EPM 2000 filter paper using respirable dust sampler (Cyclonic Flow Technique)

5. Ambient Air Quality Monitoring

Core Zone

Site 1: Cluster XIV (Lohapatty)

The samplers were installed on the roof of area office of Lohapatty (Latitude 23.737066 and Longitude 86.210894). It was located near residential colony. Coal mine was 1 km away from the sampling site. Coal has been transported through railway line which is 1.5 km away on a daily basis and also through trucks. NH-32 construction was going on 500 m away from the site. The major fuel used for cooking is coal in the study area.

Site 2: Cluster VII Mine rescue Station

Monitoring station was positioned in Mine rescue station, Dhansar on the roof of office building (Latitude 23.768746 and Longitude 86.411141). Mine rescue station is next to

the state highway 12 where continuous movement of heavy vehicles takes place. Mining activities were also observed nearby the location.

Site 3: Cluster V Katras

In Katras, samplers were installed at Expert hostel (Latitude 23.811692 and Longitude 86.335910). There was a settlement residential area nearby. Mining activities was in progress within 500m area. Railway track was nearly at 150m distance from the site. Coal was used for cooking. Many other activities were observed during sampling in the nearby area which may contribute. 'Mela' and continuous 'Hawan' were going on within 100m area. Also road construction was in progress near 7km.

Site 4: Cluster IX (Lodhana)

Samplers were installed at office in Lodhna (Latitude 23.721713 and Longitude 86.410260). Near Lodhna, colliery was 2 km away from the site. Nearest Railway track was 1.5 km away. Coal was mostly used for cooling.

Site 5: Cluster XI (Moonidih)

Moonidih mine is one of the underground mine of BCCL. Sampler was stationed in Area office of Moonidih mine (Latitude 23.742228 and Longitude 86.349494). Since monitoring location was 250-300m from the mine, movement of heavy vehicles was continuous. There is washery also at distance of 500m where trucks and conveyor were used for transportation of coal. So the mining activities nearby contributes to particulate matter emission.

Site 6: Cluster X (Patherdih)

Samplers were stationed in guest house of BCCL in Patherdih area (Latitude 23.693577 and Longitude 86.398728). It is situated beside highway where continuous movement of heavy vehicles observed. TATA steel coal mine is situated 1km away from the location where continuous mining activities takes place. Transportation of coal through railway wagons in same area also contributes to particulate matter emission.

Site 7: Cluster VIII (Bastacola)

The samplers were positioned in area office of Bastacola mine (Latitude 23.763966 and Longitude 86.433635). Here also, coal was used as a cooking media. Railway track was

at Jodaphata which was 3-4 km away from the site. Residential area was nearly 0.5-1km. Mine was situated 3km from the site but no Mining activity was observed during monitoring.

Buffer zone

Site 8: Bank More (BCCL Colony)

Sampling station was installed in BCCL colony, Jawahar Nagar on the roof of a resident (Latitude 23.789463 and Longitude 86.407448). No mining activities were observed but the colony was beside the NH 18 highway so it may contribute to particulate matter emission.

Site 9: Harina

At Harina, the site chosen for air sampling was BCCL colony (Latitude 23.806308 and Longitude 86.212641). Since it was BCCL residential area, fuel used for cooking purpose was LPG. Settlement residential area was observed nearby where coal was used as a media for cooking. Colliery and Railway track were 3km and 2 km away from the site respectively. Highway was 1km away from the site and Coal washery at distance of 4.5km.

Site 10: Bhuli

The samplers were installed on the roof of Saraswati Vidya Mandir, Bhuli (Latitude 23.819554 and Longitude 86.386647). The location was in residential area. Mining activity was going at a distance of 8-10km. A closed Brick factory was located in the nearby area. Fuel used for cooking was mostly coal. Railway track used for coal transportation was 4km from the site. Construction of highway was also going on within 1.5km area during the monitoring.

Site 11: Sindri

Air samplers were installed at BIT Sindri college campus (Latitude 23.653214 and Longitude 86.473022). Transportation of coal was done by railway wagons at distance of 2km from monitoring site. LPG was mostly used for cooking rather than coal. A construction activity was going on nearby. The site was near the highway at a distance of <100m.

Site 12: Parbatpur

The sampling station was installed on roof of a house (Latitude 23.696296 and Longitude 86.348609). Mining activity was no longer going nearby. Coal was primarily used for cooking.

Site 13: Background

The air monitoring samplers were installed on roof of resident's house which was near to the highway at a distance of less than 1 km (Latitude 23.776180 Longitude 86.160177). Construction activities were going on nearby the location. Heavy rainfall also occurred during monitoring period. Mine activities were also observed in radius of 2-3km. Settlement resident's uses coal for cooking purposes.

Sample collection Transportation and Preservation

Ambient PM_{2.5} and PM₁₀ samples were collected using suitable sampler at a desired flow rate. Filters were wrapped carefully with aluminium foil and stored in re-sealable plastic bags. At sampling site, the filter that collected the particle sample on the previous day was taken out of the filter holder and immediately wrapped with aluminium foil and sealed. The sample filters were transported back to the laboratory in an isolated cooler container with ice and then frozen at -10°C until analysis.

Table 5. 1 Physical and Chemical components for characterization of Particulate matter

Components	Filter Matrix	Analytical Methods
PM10/ PM2.5	Teflon/Quartz filter paper	Gravimetric
Elements (Na, Mg, Al, Si, P, S, Cl, Ca, Ti, V, Cr, Mn, Fe, Co, Ni, Cu, Zn, Ga, As, Se, Br, Rb, Sr, Y, Zr, Mo, Pd, Ag, Cr, Cd, In, Sn, Sb, Ba, La, Hg, Ti, and Pb)	Teflon/Quartz filter paper	ICP-OES
Ions (NO ₂ ⁻ , NO ₃ ⁻ , SO ₄ ⁻² , K ⁺ , NH ₄ ⁺ , Na ⁺)	Teflon/Quartz filter paper	Ion chromatography with conductivity detector
Carbon Analysis (OC, EC)	Quartz filter paper	TOR/TOT method
PAHs	Teflon/Quartz filter paper	Extraction followed by GC-MS analysis with and without derivatization